

Edition 3.0 2010-06

INTERNATIONAL STANDARD

Multicore and symmetrical pair/quad cables for digital communications
Part 2-1: Horizontal floor wiring – Blank detail specification

ECNORIN. COM: Click to view the



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

About the IEC

Web: www.iec.ch

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: <u>www.iec.ch/online_news/justpub</u>

Stay up to date on all new IEC publications. Just Published details twood month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional tanguages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.iec.ch/webstore/custserv

ECHORM. Click to If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 3.0 2010-06

INTERNATIONAL **STANDARD**

Multicore and symmetrical pair/quad cables for digital communications
Part 2-1: Horizontal floor wiring – Blank detail specification

Part 2-1: Horizontal floor wiring - Blank detail specification

.nk d .nk d .click to view the

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 33.120.20 ISBN 978-2-88912-039-0

CONTENTS

FO	REWORD	3
1	Scope	5
2	Normative references	5
3	Guidance for preparation of detail specifications	5
4	Blank detail specification for multicore and symmetrical pair/quad cables for digital communication in horizontal floor wiring	7
Bib	liography	. 12

ECNORM.COM. Click to view the full Park of the Consolidation of the Cons

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS

Part 2-1: Horizontal floor wiring – Blank detail specification

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-2-1 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This third edition cancels and replaces the second edition published in 2003. This edition constitutes a technical revision and takes into account the technical changes made in the IEC 61156-2, Edition 3 (2010).

This sectional specification relates to IEC 61156-2:2010. The cables are specifically intended for horizontal floor wiring as defined in ISO/IEC 11801:1995.

The text of this technical report is based on the following documents:

CDV	Report on voting
46C/900/CDV	46C/913/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61156 series, under the general title: Multicore and symmetrical pair/quad cables for digital communications, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the ECON 150 P stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

at a lat

click to view the full poly

click to view the full poly

ECNORM. A bilingual version of this publication may be issued at a later date.

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS

Part 2-1: Horizontal floor wiring – Blank detail specification

1 Scope

This blank detail specification relates to multicore and symmetrical pair/quad cables for digital communications in horizontal floor wiring.

This blank detail specification determines the layout and style for detail specifications describing multicore and symmetrical pair/quad cables for digital communication in horizontal floor wiring. Detail specifications based on the blank detail specification may be prepared by a national standards organization, a manufacturer or a user.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1:2002¹⁾, Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification

IEC 61156-2:2010, Multicore and symmetrical pair/quad cables for digital communications – Part 2: Symmetrical pair/quad cables with transmission characteristics up to 100 MHz – Horizontal floor wiring – Sectional specification

3 Guidance for preparation of detail specifications

It is necessary to keep the transmission characteristics indicated in the relevant sectional specification for the category number (3 or 5) and the characteristic impedance.

NOTE When a characteristic does not apply, then NA (for Not Applicable) may be entered in the appropriate space.

When a characteristic applies but a specific value is not considered necessary, then NS (for Not Specified) should be entered in the appropriate space.

¹⁾ A more recent version of this standard exists (2007), but as not all of the tests cited herein are addressed by the newer edition, it has been decided that the 2002 edition is to be used.

The numbers shown in brackets in this and the following pages correspond to the following items of required information which shall be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable, national reference, trade name, etc.
- [6] A complete description of the cable:
 - a) type and number of elements;
 - b) nominal impedance;
 - c) screening;
 - d) application;
 - e) category;
 - f) other distinguishing performance characteristics.

Example: Detail specification for 4-pairs cable without common screen for digital communications in horizontal floor wiring category 5.

- [7] Details of the cable materials and construction.
- [8] Special requirements for bending radius or operation temperatures.
- [9] List of cable characteristics. They are separated into electrical, transmission, mechanical and environmental characteristics.
- [10] Appropriate subclause references in the sectional specification IEC 61156-2.
- [11] Requirements applicable for this cable. The values entered shall at a minimum meet the requirements of sectional specification IEC 61156-2.
- [12] Relevant remarks.

4 Blank detail specification for multicore and symmetrical pair/quad cables for digital communication in horizontal floor wiring

[1] Prepared by:		[2] Document: Issue: Date:	
[3] Available from:	[4] Generic spe Sectional sp Blank detail		IEC 61156-1:2002 IEC 61156-2 IEC 61156-2-1
[5] Additional refere	ences:		1.2010
[6] Cable descriptio	n:		, 60°,
[7] Cable materials and construction	IEC 61156-2 subclause	Characteristic	comment
	2.2.2	Cable construction	
	2.2.3	Conductor description	
	2.2.4	Insulation description: Nominal thickness Maximum diameter	
	2.2.5 Click to	Colour code of insulation	
	2.2.6	Number and type of elements	
JORN	2.2.7	Screening of the element	
KC/L	2.2.8	Cable make-up Protective wrapping(s) of the cable core:	f
	2.2.9	Screen of the cable core: Tape material Minimum overlap Drain wire Braid wire Braid material Filling factor	

2.2.10	Sheath:	
	Material	
	Nominal thickness	
	Maximum overall diameter Marking Rip cord	
2.2.11	Colour of the sheath	,0
2.2.12	Identification	7:30
2.2.13	Packaging of finished cable	3.

ECNORM. Con. Cick to view the full Pith of

[9]	[10]	[11]	[12]
Characteristics	Subclause	Requirements	Comments
Electrical characteristics	3.2		
Conductor resistance	3.2.1	≤ Ω/km	
Resistance unbalance	3.2.2	≤ %	
Dielectric strength	3.2.3		
conductor/conductor		kV	
conductor/screen		kV	
screen/screen		kV	
Insulation resistance	3.2.4		20/10
conductor/conductor		≥ MΩ·km	K. L
conductor/screen		≥ MΩ·km	- N .
screen/screen		≥ MΩ·km	156.2.1.201
Mutual capacitance	3.2.5		NŞ
Capacitance unbalance	3.2.6		C
pair to ground		≤ pF/500 m	
Transfer impedance at 1 MHz	3.2.7	≤ mΩ/m	
10 MHz		≤ mΩ/m	
30 MHz		≤mΩ/m	
100 MHz		Κ. mΩ/m	
Transmission characteristics	3.3	Ø	
Velocity of propagation (phase velocity)	3.3.1		NS
Phase delay	3.3.1.1		NS for Cat 3
Differential phase delay	3.3.1.2		NS for Cat 3
Environmental effects in the temperature range from –40 °C to +60 °C	3.3.1.2.1		
Attenuation at 1 MHz	3.3.2	≤ dB/100 m	Equation (1)
4 MHz		≤ dB/100 m	
10 MHz		≤ dB/100 m	
Attenuation at 4 MHz 10 MHz 16 MHz 20 MHz		≤ dB/100 m	
20 MHz		≤ dB/100 m	
31,25 MHz		≤ dB/100 m	
62,5 MHz		≤ dB/100 m	
100 MHz		≤ dB/100 m	
Unbalance attenuation near-end (TCL)	3.3.3		NS

[9]	[10]	[11]	[12]
Characteristics	Subclause	Requirements	Comments
Unbalance attenuation far-end (EL-TCTL)	3.3.3		NS
Near-end crosstalk at 1 MHz	3.3.4	≥ dB	Equation (2)
4 MHz		≥ dB	
10 MHz		≥ dB	
16 MHz		≥ dB	
20 MHz		≥ dB	
31,25 MHz		≥ dB	
62,5 MHz		≥ dB	7.7
100 MHz		≥ dB	2,`
Characteristic impedance	3.3.6	Ω	1,000
Input impedance 1 MHz / MHz	3.3.6.2	Ω ±15 Ω	EN TO
Function fitted impedance / mean characteristic impedance	3.3.6.3	Ω	C61/2010
Structural return loss (SRL)	3.3.7	< dB	V
Mechanical characteristics	3.4	OK O	
Dimensional requirements	3.4.1	mm	
Insulation diameter		FULL	
Sheath thickness	**		
Cable diameter	WS.		
Elongation at break of the conductors	3.4.2	≥ %	
Elongation at break of the insulation	3.4.3	≥ %	
Elongation at break of the sheath	3.4.4	≥ %	
Tensile strength of the sheath	3.4.5	≥ MPa	
Crush test of the cable	3.4.6		
Impact test of the cable	3.4.7		
Repeated bending of the cable	3.4.8		
Tensile performance of the cable	3.4.9	N	