

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 6-1: Blank detail specification for CATV drop cables**

IECNORM.COM : Click to view the full PDF of IEC 61196-6-1:2009



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of IEC 61196-0-1:2009



IEC 61196-6-1

Edition 1.0 2009-01

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 6-1: Blank detail specification for CATV drop cables**

IECNORM.COM : Click to view the full PDF of IEC 61196-6-1:2009

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

J

ICS 33.120.10

ISBN 978-2-88910-444-4

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –

Part 6-1: Blank detail specification for CATV drop cables

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61196-6-1 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
46A/917/FDIS	46A/926/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 61196-6-1:2009

COAXIAL COMMUNICATION CABLES –

Part 6-1: Blank detail specification for CATV drop cables

1 Scope

This blank detail specification applies to CATV cables. It specifies the requirements for drop cables for use in cabled television distribution networks operating at temperatures between -40°C and +70°C and in the frequency range from 5 MHz to 1000 MHz or from 5 MHz to 3 000 MHz as described in IEC 61196-6 and is to be read in conjunction with IEC 61196-1 and IEC 61196-6.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1: *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 61196-6, *Coaxial communication cables – Part 6: Sectional specification for CATV drop cables*

IEC 62153-4-4, *Metallic communication cable test methods – Part 4-4: Electromagnetic compatibility (EMC) – Shielded screening attenuation, test method for measuring of the screening attenuation "a_s" up to and above 3 GHz.*

3 Guidance for preparation of a detail specification

The detail specification shall be written in accordance with the layout of the pro-forma blank detail specification that forms part of this standard.

NOTE When a characteristic does not apply, in accordance with IEC 61196-6, then NA (for not Applicable) shall be entered in the appropriate space.

When a characteristic applies but a specific value is considered not necessary, then NS (for Not Specified) shall be entered in the appropriate space.

When NS is used, the appropriate requirement in the sectional specification shall apply.

The numbers shown in brackets on this and the following pages correspond to the following items of required information, which should be entered in the spaces provided.

- [1] Name and address of the manufacturer of the cable.
- [2] IEC document number and date of issue.
- [3] Related IEC documents.
- [4] Product type/model of cable
- [5] Any other reference standards (International, National, etc.) to the cable.
- [6] Parameter or characteristic of the cable.
- [7] Reference to the relevant subclause of the sectional specification
- [8] Manufacturer specification of the cable
- [9] Minimum requirements defined within the generic or sectional specification
- [10] Manufacturer to insert any additional test parameters, methods, specifications, etc.

4 Blank detail specification

[1] Manufacturer and address:	[2] Issue: CEI/IEC 61196-6-1 Date :		
	[3] Generic specification: IEC 61196-1 Sectional specification: IEC 61196-6		
[4] Product type/model:	[5] Additional references:		
[6] Parameter or characteristic Cable construction (dimensions in mm)	[7] IEC 61196-6 subclause	[8] Manufacturer specification	[9] Minimum requirement
Inner conductor	4.2		
Material	4.2.1		NS
Diameter	4.2.2		NS
Tolerance	4.2.2		± 0,03 mm
Dielectric	4.3		
Material	4.3		NS
Diameter	4.3		NS
Tolerance	4.3		± 0,15 mm
Outer conductor	4.4		
Type and construction	4.4		NS
Material	4.4		NS
Diameter	4.4		NS
Tolerance	4.4		± 0,20 mm
Sheath or jacket	4.5		NS
Material	4.5		NS
Thickness	4.5		NS
Diameter	4.5		NS
Tolerance	4.5		± 0,25 mm
Integral messenger	4.5		
Material	4.5		NS
Diameter	4.5		NS
Minimum tensile strength (kgf)	4.5		NS
Elongation	4.5		NS
Corrosion Properties	4.5		NS
Additional information			
Overall dimension (width) of cable	4.6		NS
Standard ratings and characteristics	5.0		NS
Cable identification and markings	6.0		As defined in 6.1.1 of IEC 61196-6
NS: Not specified NA: Not applicable			

			1,5 kV a.c. 1 min note 1
Withstand voltage of sheath	7.1.1.4		3,5 kV d.c. 2,5 kV a.c. 1 min note 1
Current carrying capacity	7.1.1.5		NS
Spark Test	7.1.1.6		2,5 kV a.c. 3,75 kV d.c. or 3,5 kV f
Frequency electrical and mechanical measurements	7.1.2		
Operational frequency			5 MHz to 1 or 5 MHz to 3
Characteristic impedance	7.1.2.1		75 ± 3 Ω
Propagation velocity (velocity ratio)	7.1.2.2		NS
Return loss (uniformity of impedance)	7.1.2.3		5 MHz to 1 ≥ 20 dB; 1000 MHz 2000MHz: ≥ 18 dB; 2000 MHz 3000 MHz The meas inaccuracy be < 1 dB.
Attenuation constant, α	7.1.2.4		α=a+ or for cop conductor α=a+√f+ a=____, b= and if app

[6] Parameter or characteristic	[7] IEC 61196-6 subclause	[8] Manufacturer specification	[9] Minimum requirement
Completed cable tests			
Environmental testing of finished cable	7.2		
Cold bend	7.2.1		Test Method Method B mandrel diameter is Test temperature is... No physical damages of conductors, dielectric and sheaths
Water penetration	7.2.2		NS
Climatic sequence	7.2.3		See IEC 61196-6, Table 3
Damp heat (steady state)	7.2.4		See IEC 61196-6, Table 3
Ultraviolet stability of sheath or jacket	7.2.5		a) No visual cracks b) b) magnitude of change in elongation ≤ 20 % after 720 h c) magnitude of change in tensile strength ≤ 20 % after 720 h
Thermal ageing	7.2.6		Transmission characteristics shall remain within the specified limits
Mechanical characteristics of finished cable	7.3		
Ovality of dielectric	7.3.1		$\leq 7\%$
Ovality of sheath	7.3.2		$\leq 7\%$
Eccentricity of dielectric	7.3.3		$\leq 10\%$
Eccentricity of sheath	7.3.4		$\leq 10\%$
Carbon black content, where applicable	7.3.5		$\geq 2\%$
Tensile strength and elongation of the copper or copper-clad metals	7.3.6		Shall be in accordance with IEC 61196-1, 4.4.1.1
Torsion test for copper-clad metals	7.3.7		Shall be in accordance with IEC 61196-1-310 if applicable
Adhesion testing: inner conductor to dielectric	7.3.8		See IEC 61196-6, Table 4
Bending	7.3.9		NS
Tensile strength of cable (longitudinal pull)	7.3.10		NS
Crush resistance of cable	7.3.11		See IEC 61196-6, Table 4
Abrasion resistance	7.3.12		NS

NOTE 1 Figures provided are the default values. Other values may be specified

NOTE 2 Flexure test method be performed per IEC 61196-1-314, 8.3.2, procedure 2

Radius of pulleys: 10 X diameter of cable,

Tension: As defined in 7.3.10 of this standard,

Speed: ≤ 1 m/s,

Number of cycles: 3

NS: Not specified NA: Not applicable
[10] Additional tests, methods, and other information

IECNORM.COM : Click to view the full PDF of IEC 61196-6-1:2009

Annex A
(normative)**Maximum attenuation**

Frequency specified in MHz	Maximum Attenuation: dB/100m at 20°C
—	—
—	—
—	—
200	—
—	—
—	—
—	—
800	—
—	—
2400	—

IECNORM.COM : Click to view the full PDF of IEC 61196-6-1:2009