

## INTERNATIONAL STANDARD ISO/IEC 15444-1:2000 TECHNICAL CORRIGENDUM 3

Published 2002-08-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION

• MEXGYHAPOGHAЯ OPFAHU3ALUЯ ПО СТАНДАРТИЗАЦИЯ

• ORGANISATION INTERNATIONALE DE NORMALISATION

MEXGYHAPOGHAЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ

• ORGANISATION INTERNATIONALE DE NORMALISATION

COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — JPEG 2000 image coding system —
Part 1:
Core coding system

TECHNICAL CORRIGENDUM 3

Technologies de l'information — Système de codage d'image d'Eleg 2000 —
Partie 1: Système de codage de noyau

RECTIFICATIF TECHNIQUE 3

Technical Corrigendum 3 to ISO/IEC 15444-1:2000 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 29, Coding of audio, picture, multimedia and hypermedia information.

ICS 35.040



## INFORMATION TECHNOLOGY – JPEG 2000 IMAGE CODING SYSTEM - CORE CODING SYSTEM

## **TECHNICAL CORRIGENDUM 3**

- 1) In Annex B.6, between paragraphs 3 and 4, p. 64, add
  "It can happen that *numprecincts* is 0 for a particular tile-component and resolution level. When this happens, there are no packets for this tile-component and resolution level."
- 2) In Annex F.3.8.2, paragraph 3, p. 123, change "Firstly, step 1 is performed for all values of n such that  $\begin{vmatrix} i_0 \\ -1 \end{vmatrix} 1 \le n < \begin{vmatrix} i_1 \\ -1 \end{vmatrix} + 2$ , and step 2 is performed for all values

of *n* such that 
$$\begin{vmatrix} i_0 \\ -2 \end{vmatrix} - 1 \le n < \begin{vmatrix} i_1 \\ -2 \end{vmatrix} + 1$$
."

to

- "Firstly, step 1 is performed for all values of n such that  $\begin{vmatrix} i_0 \\ 2 \end{vmatrix} + 2$ , and step 2 is performed for all values
- of *n* such that  $\left\lfloor \frac{i_0}{2} \right\rfloor 2 \le n < \left\lfloor \frac{i_1}{2} \right\rfloor + 2$ .
- 3) In Annex F.4.8.2, paragraph 7, p. 132, change
  - "Finally, step 5 is performed for all values of n such that  $\left\lceil \frac{i_0}{2} \right\rceil 1 \le n < \left\lceil \frac{i_1}{2} \right\rceil$  and uses values calculated at step 3, and
  - step 6 is performed for all values of n such that  $\left\lceil \frac{i_0}{2} \right\rceil \le n < \left\lceil \frac{i_1}{2} \right\rceil$  and uses values calculated at step 4."

to

- "Finally, step 5 is performed for all values of n such that  $\left\lfloor \frac{i_0}{2} \right\rfloor \le n < \left\lfloor \frac{i_1}{2} \right\rfloor$  and uses values calculated at step 3, and step
- 6 is performed for all values of n such that  $\left\lceil \frac{i_0}{2} \right\rceil \le n < \left\lceil \frac{i_1}{2} \right\rceil$  and uses values calculated at step 4."
- 4) In Annex I.5.3.5, paragraph 2, change
  - If the JP2 Header box contains a Palette box, then the JP2 Header box shall also contain a Component Mapping box. If the JP2 Header box does not contain a Palette box, then the JP2 Header box shall not contain a Component Mapping box. In this case, the components shall be mapped directly to channels, such that component *i* is mapped to channel *i*."

to

"If the JP2 Header box contains a Palette box, then the JP2 Header box shall also contain a Component Mapping box. If the JP2 Header box does not contain a a Component Mapping box, the components shall be mapped directly to channels, such that component *i* is mapped to channel *i*."