

# INTERNATIONAL STANDARD ISO/IEC 9594-4:2008 TECHNICAL CORRIGENDUM 1

Published 2011-11-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

• MEЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

• ORGANISATION INTERNATIONALE DE NORMALISATION

INTERNATIONAL ELECTROTECHNICAL COMMISSION

• MEЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ

• COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

# Information technology — Open Systems Interconnection — The Directory: Procedures for distributed operation

**TECHNICAL CORRIGENDUM 1** 

Technologies de l'information — Interconnexion de systèmes ouverts (OSI) — L'annuaire: Procédures pour le fonctionnement réparti

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO/IEC 9594-42008 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, Subcommittee SC 6, Telecommunications and information exchange between systems, in collaboration with ITU-T. The identical text is published as Rec. ITU T X.518 (2008)/Cor.1 (02/2011).

ICS 35.100.70

Ref. No. ISO/IEC 9594-4:2008/Cor.1:2011(E)

ECHORACOM. Click to view the full poly of the South of th

#### INTERNATIONAL STANDARD RECOMMENDATION ITU-T

## **Information technology – Open Systems Interconnection –** The Directory: Procedures for distributed operation

### **Technical Corrigendum 1**

(covering resolution to defect reports 338 and 339)

#### 1) Correction of the defects reported in defect report 338

Delete 3.5 and renumber subsequent subclauses.

In 10.3 and Annex A: change the nonDapPdu and the streamedResults components to:

```
2008/COR1.2011
                     [22] Not to be used
                     [23] INTEGER OPTIONAL Currently not used
streamedResults
```

Delete item w) and renumber subsequent items.

*Add after new item w):* 

NOTE 6 - This component is currently not used. It might be used in the next edition of this Directory Specification. Otherwise, it will be deprecated.

Modify 10.8 a) as follows:

An AccessPoint value identifies a particular point at which access to the Directory, specifically to a DSA or LDAP server, can occur. When referring to a DSA, the access point shall have a Name, that of the DSA concerned, and may. It shall have a PresentationAddress, to be used in OSI or IDM communications to that DSA or LDAP server (see clause 11 of Rec. ITU-T X.519 | ISO/IEC9594-5 for additional information about NSAP formats)., in which case labeleduri shall not be present.

When referring to an LDAP server, the access point may have a labeleduri component, to be used in LDAP communications to that LDAP server. When the labeleduri component is present, the aetitle component and the address component and the protocolInformation component (if present) shall be ignored. This way of providing LDAP access point information is deprecated. Instead the format specified in 11.4 of ITU T Rec. X.519 | ISO/IEC 9594 5 should be used. Also, in this case the ae-title and protocolInformation components shall be ignored.

```
SET {
AccessPoint
     ae-title
                                  T 0 1
                                       Name,
     address
                                  [1]
                                        PresentationAddress,
                                        SET SIZE (1..MAX) OF ProtocolInformation OPTIONAL _{7}
     protocolInformation
                                  [2]
                                        Not to be used
                                  [61
                                        abeledIRT OPTIONAL
```

Change the first paragraph of 12.1 as shown:

A DSA, having received an operation from a DUA or LDAP client, may elect to construct a chained form of that operation to propagate to another DSA. A DSA, having received a chained form of an operation, may also elect to chain it to another DSA. The DSA invoking a chained form of an operation may sign, enerypt, or sign and enerypt the argument of the operation; the DSA performing the operation, if so requested, may sign, encrypt, or sign and encrypt the result or error returned by the responder of the operation. A DSA, having received an operation from an LDAP elient or having received an LDAP operation from another DSA, may elect to propagate the original LDAP elientsupplied operation to an LDAP server.

#### ISO/IEC 9594-4:2008/Cor.1:2011 (E)

Change the following as shown:

- a) chainedArgument This is a value of ChainingArguments that which contains that the information supplementing the information provided in the argument of , over and above the original DAP requestUA- or LDAP client supplied argument. This additional information is needed in order for the receiving to handle the operation properly, which is needed in order for the performing DSA or LDAP server to carry out the operation. This information type is defined in 10.3.
- b) argument This is a value operation. & Argument and consists of the original DUA-supplied argument, as specified in the appropriate clause of ITU-T Rec. X.511 | ISO/IEC 9594-3, or the original LDAP client supplied argument, as specified in the appropriate clause of IETF RFC 4510.

NOTE 3—It may also be possible to encapsulate PDU types other than those originating from DAP or LDAP if deemed appropriate. Specification of the mechanisms to do so is left for further study.

In 13.1, replace the last sentence with:

If an error occurs during a chained operation, the responding DSA may sign, encrypt, or sign and encrypt, the error returned.

In 15.3.1, replace the second paragraph with:

The argument of a chained request (see 12.1) or subrequest shall be the unmodified operation argument of the original DAP operation. if the operation was initiated by a DUA and shall be the unmodified LDAPMessage if the operation was initiated by an LDAP client. A DSA receiving a chained request shall not change argument when doing request decomposition.

In 16.1.2, delete the last bullet of the list near the end of the subclause.

In 16.1.4.1, 16.2, 16.3.1, 16.3.4, 16.3.5, 16.3.6, 16.3.9, 17.1 and 17.2.2, remove references to LDAP and LDAP client.

In 17.3.3.1, remove the reference to LDAP client, and also in the heading.

Delete the last paragraph of current 17.3.3.3.

In 17.3.7, remove the reference to LDAP client.

In 18.2.1. delete as shown and renumber:

The procedure uses the following arguments:

- a) ChainingArguments.traceInformation;
- b) ChainingArguments.aliasDereferenced;
- c) ChainingArguments.aliasedRDNs;
- d) ChainingArguments.excludeShadows;
- e) ChainingArguments.nameResolveOnMaster;
- f) ChainingArguments.operationProgress (nameResolutionPhase, nextRDNToBeResolved);
- g) ChainingArguments.referenceType;
- h) ChainingArguments.targetObject;
- ChainingArguments.relatedEntry;
- ChainingArguments.streamedResults;
- k) the operation type;
- 1) the operation argument.

In 18.2.4, change as shown:

The procedure uses the following global variables:

- NRcontinuationList list to store the Continuation Reference(s) needed to continue name resolution in the Name Resolution Continuation Reference procedure.
- StreamedResultsOK to store the determination of whether this DSA may chain streamed results in response to this operation.