

INTERNATIONAL
STANDARDIZED
PROFILE

ISO/IEC
ISP
11183-3

First edition
1992-12-15

Corrected and reprinted
1993-04-15

**Information technology — International
Standardized Profiles AOM1n OSI
Management — Management
Communications —**

Part 3:
CMISE/ROSE for AOM11 — Basic
Management Communications

*Technologies de l'information — Profils normalisés internationaux AOM1n
pour la gestion OSI — Gestion de communication —*

*Partie 3: CMISE/ROSE pour AOM11 — Gestion de base de
communication*



Reference number
ISO/IEC ISP 11183-3:1992(E)

Contents	Page
Introduction	vii
1 Scope	1
1.1 General	1
1.2 CMIP/ROSE PDUs support	2
1.3 CMIP functional units	2
1.4 Position within the taxonomy	2
1.5 Scenario	3
2 Normative references	3
3 Definitions and conventions	5
3.1 Base standard	5
3.1.1 Definitions	5
3.1.2 PICS definitions and conventions	5
3.2 Profile	6
3.2.1 Profile support requirement definitions	6
3.2.2 ISPICS requirements list conventions	6
3.2.3 Nesting rules in ISPICS requirements list	7
3.3 Common conditions list conventions	8
4 Abbreviations	9
5 Conformance to AOM11	10
5.1 Conformance statement	10
5.2 CMIP conformance	10
5.3 Association establishment and abort requirements	11
5.4 ROSE conformance	11

Annex

A	ISPICS Requirements List	12
A.1	Global statement of conformance	13
A.2	Capabilities	13
A.2.1	Initiator/Responder capability	13
A.2.2	ASN.1 EXTERNAL type parameters support	14
A.2.3	CMIPUserInfo parameter support	14
A.2.4	CMIPAbortInfo parameter support	16
A.2.5	Major capabilities	16
A.3	Protocol parameters	17
A.3.1	System wide parameters	17
A.3.2	Common protocol parameters	18
A.4	Protocol data units	20
A.5	PDU parameters	33
A.6	Negotiation capabilities	77
A.7	Multi-layer dependencies	77
A.8	List of CMISE Service Errors	78
A.9	List of ASN.1 elements specified with "ANY DEFINED BY" type	79
Table A.1	- Association initialisation	13
Table A.2	- Association release	13
Table A.3	- CMIPUserInfo parameter support (in AARQapdu)	14
Table A.4	- CMIPUserInfo parameter support (in AAREapdu)	15
Table A.5	- CMIPAbortInfo parameter support	16
Table A.6	- Conformance claim	16
Table A.7	- Additional functional unit support	16
Table A.8	- Scope parameter support	17
Table A.9	- FilterItem parameter support - (sending)	17
Table A.10	- FilterItem parameter support - (receiving)	17
Table A.11	- CMISFilter parameter support	17
Table A.12	- CMISFilter complexity limitations	17
Table A.13a	- Common parameter support - (sending)	18
Table A.13b	- Common parameter support - (receiving)	19
Table A.14	- Protocol support for kernel CMIS services	20
Table A.15	- CMIP PDUs required to support M-ACTION service in the invoker role	21
Table A.16	- CMIP PDUs required to support M-ACTION service in the performer role	22
Table A.17	- CMIP PDUs required to support M-CANCEL-GET service in the invoker role	23
Table A.18	- CMIP PDUs required to support M-CANCEL-GET service in the performer role	23
Table A.19	- CMIP PDUs required to support M-CREATE service in the invoker role	23
Table A.20	- CMIP PDUs required to support M-CREATE service in the performer role	24
Table A.21	- CMIP PDUs required to support M-DELETE service in the invoker role	25
Table A.22	- CMIP PDUs required to support M-DELETE service in the performer role	26
Table A.23	- CMIP PDUs required to support M-EVENT-REPORT in the invoker role	27
Table A.24	- CMIP PDUs required to support M-EVENT-REPORT in the performer role	28
Table A.25	- CMIP PDUs required to support M-GET service in the invoker role	29

Table A.26 - CMIP PDUs required to support M-GET service in the performer role	30
Table A.27 - CMIP PDUs required to support M-SET service in the invoker role.....	31
Table A.28 - CMIP PDUs required to support M-SET service in the performer role.....	32
Table A.29 - ROIV-m-Action (sending)	33
Table A.30 - ROIV-m-Action (receiving)	34
Table A.31 - ROIV-m-Action-Confirmed (sending).....	35
Table A.32 - ROIV-m-Action-Confirmed (receiving).....	36
Table A.33 - ROIV-m-Cancel-Get (sending)	36
Table A.34 - ROIV-m-Cancel-Get (receiving)	36
Table A.35 - ROIV-m-Create (sending).....	37
Table A.36 - ROIV-m-Create (receiving)	38
Table A.37 - ROIV-m-Delete (sending)	39
Table A.38 - ROIV-m-Delete (receiving)	40
Table A.39 - ROIV-m-EventReport (sending)	41
Table A.40 - ROIV-m-EventReport (receiving)	41
Table A.41 - ROIV-m-EventReport-Confirmed (sending).....	42
Table A.42 - ROIV-m-EventReport-Confirmed (receiving).....	42
Table A.43 - ROIV-m-Get (sending).....	43
Table A.44 - ROIV-m-Get (receiving)	44
Table A.45 - ROIV-m-LinkedReply-Action (sending).....	45
Table A.46 - ROIV-m-LinkedReply-Action (receiving).....	45
Table A.47 - ROIV-m-LinkedReply-Delete (sending).....	45
Table A.48 - ROIV-m-LinkedReply-Delete (receiving).....	45
Table A.49 - ROIV-m-LinkedReply-Get (sending)	45
Table A.50 - ROIV-m-LinkedReply-Get (receiving)	45
Table A.51 - ROIV-m-LinkedReply-Set (sending).....	45
Table A.52 - ROIV-m-LinkedReply-Set (receiving).....	45
Table A.53 - ROIV-m-Set (sending)	46
Table A.54 - ROIV-m-Set (receiving)	47
Table A.55 - ROIV-m-Set-Confirmed (sending).....	48
Table A.56 - ROIV-m-Set-Confirmed (receiving).....	49
Table A.57 - RORS-m-Action-Confirmed (sending)	50
Table A.58 - RORS-m-Action-Confirmed (receiving)	51
Table A.59 - RORS-m-Cancel-Get (sending).....	51
Table A.60 - RORS-m-Cancel-Get (receiving).....	51
Table A.61 - RORS-m-Create (sending)	52
Table A.62 - RORS-m-Create (receiving)	52
Table A.63 - RORS-m-Delete (sending).....	53
Table A.64 - RORS-m-Delete (receiving).....	53
Table A.65 - RORS-m-EventReport-Confirmed (sending)	54
Table A.66 - RORS-m-EventReport-Confirmed (receiving)	54
Table A.67 - RORS-m-Get (sending)	55
Table A.68 - RORS-m-Get (receiving)	55
Table A.69 - RORS-m-Set-Confirmed (sending)	56
Table A.70 - RORS-m-Set-Confirmed (receiving)	56
Table A.71 - ROER-accessDenied (sending)	57
Table A.72 - ROER-accessDenied (receiving)	57
Table A.73 - ROER-classInstanceConflict (sending)	57
Table A.74 - ROER-classInstanceConflict (receiving).....	58
Table A.75 - ROER-complexityLimitation (sending)	58
Table A.76 - ROER-complexityLimitation (receiving).....	59
Table A.77 - ROER-duplicateManagedObjectInstance (sending).....	59
Table A.78 - ROER-duplicateManagedObjectInstance (receiving).....	60
Table A.79 - ROER-getListError (sending)	60
Table A.80 - ROER-getListError (receiving)	61
Table A.81 - ROER-invalidArgumentValue (sending).....	62
Table A.82 - ROER-invalidArgumentValue (receiving).....	62
Table A.83 - ROER-invalidAttributeValue (sending).....	63

Table A.84 - ROER-invalidAttributeValue (receiving)	63
Table A.85 - ROER-invalidFilter (sending)	63
Table A.86 - ROER-invalidFilter (receiving)	63
Table A.87 - ROER-invalidObjectInstance (sending)	64
Table A.88 - ROER-invalidObjectInstance (receiving)	64
Table A.89 - ROER-invalidScope (sending)	64
Table A.90 - ROER-invalidScope (receiving)	64
Table A.91 - ROER-missingAttributeValue (sending)	65
Table A.92 - ROER-missingAttributeValue (receiving)	65
Table A.93 - ROER-mistypedOperation (sending)	66
Table A.94 - ROER-mistypedOperation (receiving)	66
Table A.95 - ROER-noSuchAction (sending)	66
Table A.96 - ROER-noSuchAction (receiving)	66
Table A.97 - ROER-noSuchArgument (sending)	67
Table A.98 - ROER-noSuchArgument (receiving)	67
Table A.99 - ROER-noSuchAttribute (sending)	68
Table A.100 - ROER-noSuchAttribute (receiving)	68
Table A.101 - ROER-noSuchEventType (sending)	69
Table A.102 - ROER-noSuchEventType (receiving)	69
Table A.103 - ROER-noSuchInvokeld (sending)	70
Table A.104 - ROER-noSuchInvokeld (receiving)	70
Table A.105 - ROER-noSuchObjectClass (sending)	70
Table A.106 - ROER-noSuchObjectClass (receiving)	70
Table A.107 - ROER-noSuchObjectInstance (sending)	71
Table A.108 - ROER-noSuchObjectInstance (receiving)	71
Table A.109 - ROER-noSuchReferenceObject (sending)	72
Table A.110 - ROER-noSuchReferenceObject (receiving)	72
Table A.111 - ROER-operationCancelled (sending)	72
Table A.112 - ROER-operationCancelled (receiving)	72
Table A.113 - ROER-processingFailure (sending)	73
Table A.114 - ROER-processingFailure (receiving)	73
Table A.115 - ROER-setListError (sending)	74
Table A.116 - ROER-setListError (receiving)	75
Table A.117 - ROER-syncNotSupported (sending)	75
Table A.118 - ROER-syncNotSupported (receiving)	75
Table A.119 - RORJ (sending)	76
Table A.120 - RORJ (receiving)	76
Table A.121 - Negotiation capabilities	77
Table A.122 - Rose association and operation class support	77
Table A.123 - Presentation functional unit support	77
Table A.124 - Session functional unit support	77
Table A.125 - CMISE Service Errors	78

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. In addition to developing International Standards, ISO/IEC JTC 1 has created a Special Group on Functional Standardization for the elaboration of International Standardized Profiles.

An International Standardized Profile is an internationally agreed, harmonized document which identifies a standard or group of standards, together with options and parameters, necessary to accomplish a function or set of functions.

Draft International Standardized Profiles are circulated to national bodies for voting. Publication as an International Standardized Profile requires approval by at least 75 % of the national bodies casting a vote.

International Standardized Profile ISO/IEC ISP 11183-3 was prepared with the collaboration of

- OSI Asia-Oceania Workshop (AOW);
- European Workshop for Open Systems (EWOS);
- OSI Implementors Workshop (OIW).

ISO/IEC ISP 11183 consists of the following parts under the general title *Information technology — International Standardized Profiles AOM1n OSI Management — Management Communications*:

- *Part 1: Specification of ACSE, presentation and session protocols for the use by ROSE and CMISE*
- *Part 2: CMISE/ROSE for AOM12 — Enhanced Management Communications*
- *Part 3: CMISE/ROSE for AOM11 — Basic Management Communications*

Annex A forms an integral part of this part of ISO/IEC ISP 11183.

Introduction

This International Standardized Profile (ISP) is defined within the context of functional standardization, in accordance with the principles specified by ISO/IEC TR 10000, "Framework and Taxonomy of International Standardized Profiles". The context of Functional Standardization is one part of the overall field of Information Technology (IT) standardization activities, covering base standards, profiles, and registration mechanisms. A Profile defines a combination of base standards that collectively perform a specific well-defined function. Profiles standardize the use of options and other variations in the base standards, and provide a basis for the development of uniform, internationally recognized conformance test suites.

One of the most important roles for an ISP is to serve as the basis for the development (by organizations other than ISO and IEC) of internationally recognized tests and test centres. ISPs are produced not simply to 'legitimize' a particular choice of base standards and options, but to promote real system interoperability. The development and widespread acceptance of tests based on this and other ISPs is crucial to the successful realization of this goal.

The text for this part of ISO/IEC ISP 11183 was developed in close cooperation among the Network Management Expert Groups of the three International OSI Workshops: NIST Workshop for implementors of OSI (NIST OIW), the European Workshop for Open Systems (EWOS) and the OSI Asia-Oceania Workshop (AOW). This ISP part is harmonized among these three Workshops and it was finally ratified by the Workshops' plenary assemblies.

This part of ISO/IEC ISP 11183 contains one normative annex : annex A, ISPICS Requirements List for AOM11.

The expression "International Standardized Profile" is replaced by the abbreviation "ISP" in the following clauses and in the annex.

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 11183-3:1992

Information technology — International Standardized Profiles AOM1n OSI Management — Management Communications —

Part 3: CMISE/ROSE for AOM11 — Basic Management Communications

1 Scope

1.1 General

This part of ISO/IEC ISP 11183 specifies how the OSI Common Management Information Service Element (CMISE) combined with the OSI Remote Operation Service Element (ROSE) shall be used to provide a basic subset of operation and notification services to the CMISE-service-users of two end systems. It specifies the CMIP/ROSE protocol features for the definition of the Basic Management Communications profile, AOM11. This part of ISO/IEC ISP 11183 can be used together with the part 1 and any connection-mode Transport profile to specify the complete communication requirements for systems management.

This part of ISO/IEC ISP 11183 defines the support level of the OSI management communication features needed by implementations for providing the kernel functional unit only.

The support of this subset of operation and notification services, and of the corresponding protocol elements does not imply that all these features shall be used in all instances of communications. The selection of the features depends on the needs and dynamic requirements of the CMISE-service-users who may choose between :

- application entity roles,
- operation/notification services,
- optional parameters.

It only implies that a conforming implementation of the CMISE/ROSE services provider does not restrict the capabilities of the CMISE-service-users and complies with the static CMIP requirements specified in ISO/IEC 9596-1 and ISO/IEC 9596-2.

This part of ISO/IEC ISP 11183 specifies a true subset of the capabilities included in ISO/IEC ISP 11183-2. Therefore, implementations conforming to the profile AOM11 shall be able to interoperate with implementations conforming to the profile AOM12, based on the subset of functions specified here.

NOTES

- 1 The operations and notifications relate to managed objects. The specification and the support of these managed objects are outside the scope of the profile AOM11.
- 2 This part of ISO/IEC ISP 11183 is based on ISO/IEC 9596-2, (SC21 N-7036, 2 June 1992).

1.2 CMIP/ROSE PDUs support

An implementation conforming to the profile AOM11 shall be able to support the following PDUs:

ROIV-m-Action	ROER-accessDenied
ROIV-m-Action-Confirmed	ROER-classInstanceConflict
ROIV-m-Create	ROER-complexityLimitation
ROIV-m-Delete	ROER-duplicateManagedObjectInstance
ROIV-m-Get	ROER-getListError
ROIV-m-Set	ROER-invalidArgumentValue
ROIV-m-Set-Confirmed	ROER-invalidAttributeValue
ROIV-m-Event Report	ROER-invalidObjectInstance
ROIV-m-Event Report-Confirmed	ROER-missingAttributeValue
	ROER-noSuchAction
RORS-m-Action-Confirmed	ROER-noSuchArgument
RORS-m-Create	ROER-noSuchAttribute
RORS-m-Delete	ROER-noSuchEventType
RORS-m-Get	ROER-noSuchObjectClass
RORS-m-Set-Confirmed	ROER-noSuchObjectInstance
RORS-m-Event Report-Confirmed	ROER-noSuchReferenceObject
	ROER-processingFailure
RORJ	ROER-setListError

1.3 CMIP functional units

The CMIP functional units are defined in ISO/IEC 9595 and ISO/IEC 9596-1. A conforming implementation shall be able to support only the kernel functional unit. All other functional units shall be out of the scope of the profile AOM11, as indicated by the table A.7 in annex A of this part of ISO/IEC ISP 11183.

NOTE - As defined in clause 7.2.3 of ISO/IEC 9595, multiple replies may be defined for an M-ACTION operation requested on single managed objects. Therefore, AOM11 profile may not meet all the requirements of such applications.

1.4 Position within the Taxonomy

This part of ISO/IEC ISP 11183 is the third part of a multipart ISP for OSI Management, which consists of the following parts :

- Part 1: Specification of ACSE, Presentation and Session Protocols for the use by ROSE and CMISE.*
- Part 2: CMISE/ROSE for AOM12, Enhanced Management Communications.*
- Part 3: CMISE/ROSE for AOM11, Basic Management Communications .*

The profile which is defined in this part of ISO/IEC ISP 11183 is identified in ISO/IEC TR 10000-2 as :

- AOM1n - OSI Management - Management Communications -*
- Part 3: CMISE/ROSE for AOM11 - Basic Management Communications.*

It may be combined with any A-Profiles AOM2n, Management Functions.

It may be combined with any T-Profiles (see ISO/IEC TR 10000) specifying the OSI connection-mode transport service.

1.5 Scenario

The general model used in the profile AOM11 is the complementary communications interactions between CMISE-service-users within two end Management Information systems as shown in figure below.




Figure 1 - Communications support for OSI management interactions between two CMISE-service-users

The specifications of the profile AOM11 apply only on the two lines between the end system boxes of the figure.

The common functions required from the supporting protocol stack of ACSE, Presentation and Session are specified in the part 1 of the multipart ISP AOM1n (see also the stack of standards in table 1).

Table 1 - Profile supporting stack

Application Layer	ISO 9595, 9596-1 ISO 9072-1, 9072-2 ISO 8649, 8650 ISO 8649/Amd.1 ISO 8650/Amd.1
Presentation Layer	ISO 8822, 8823 ISO 8824, 8825
Session Layer	ISO 8326, 8327 ISO 8326/Amd.2 ISO 8327/Amd.2

2 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC ISP 11183. At the time of publication, the editions indicated were valid. All documents are subject to revision, and parties to agreements based on this part of ISO/IEC ISP 11183 are warned against automatically applying any more recent editions of the documents listed below, since the nature of references made by ISPs to such documents, is that they may be specific to a particular edition. Members of IEC and ISO maintain registers of currently valid International Standards and ISPs, and CCITT maintains published editions of its current Recommendations.

ISO/IEC ISP 11183-3: 1992 (E)

ISO 7498:1984, *Information processing systems - Open Systems Interconnection - Basic Reference Model*. | CCITT Recommendation X.200:1988, *Reference Model of Open Systems Interconnection for CCITT applications*.

ISO/IEC 7498-4:1989, *Information processing systems - Open Systems Interconnection - Basic Reference Model - Part 4: Management Framework*. | CCITT Recommendation X.700, *Management Framework Definition for Open Systems Interconnection (OSI) for CCITT applications*.

ISO 8326:1987, *Information processing systems - Open Systems Interconnection - Basic connection oriented session service definition*. | CCITT Recommendation X.215:1988, *Session service definition for Open Systems Interconnection for CCITT applications*.

ISO 8327:1987, *Information processing systems - Open Systems Interconnection - Basic connection oriented session protocol specification*. | CCITT Recommendation X.225:1988, *Session protocol specification for Open Systems Interconnection for CCITT applications*.

ISO 8327:1987/Amd.2:¹⁾, *Information processing systems - Open Systems Interconnection - Basic connection oriented session protocol specification - Amendment 2 : Unlimited user data*.

ISO 8649:1988, *Information processing systems - Open Systems Interconnection - Service definition for the Association Control Service Element*. | CCITT Recommendation X.217:1988, *Association control service definition for Open Systems Interconnection for CCITT applications*.

ISO 8649:1988/Amd.1:1990, *Information processing systems - Open Systems Interconnection - Service definition for the Association Control Service Element - Amendment 1: Authentication during association establishment*.

ISO 8650:1988, *Information processing systems - Open Systems Interconnection - Protocol specification for the Association Control Service Element*. | CCITT Recommendation X.227:1988, *Association control protocol specification for Open Systems Interconnection for CCITT applications*.

ISO 8650:1988/Amd.1:1990, *Information processing systems - Open Systems Interconnection - Protocol specification for the Association Control Service Element - Amendment 1: Authentication during association establishment*.

ISO 8822:1988, *Information processing systems - Open Systems Interconnection - Connection oriented presentation service definition*. | CCITT Recommendation X.216:1988, *Presentation service definition for Open Systems Interconnection for CCITT applications*.

ISO 8823:1988, *Information processing systems - Open Systems Interconnection - Connection oriented presentation protocol specification*. | CCITT Recommendation X.226:1988, *Presentation protocol specification for Open Systems Interconnection for CCITT applications*.

ISO/IEC 8824:1990, *Information technology - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1)*. | CCITT Recommendation X.208:1988, *Specification of abstract syntax notation one (ASN.1)*.

ISO/IEC 8825:1990, *Information technology - Open Systems Interconnection - Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1)*. | CCITT Recommendation X.209:1988, *Specification of basic encoding rules for abstract syntax notation one (ASN.1)*.

ISO/IEC 9072-1:1989, *Information processing systems - Text Communication - Remote Operations - Part 1: Model, notation and service definition*. | CCITT Recommendation X.219:1988, *Remote Operations: Model, notation and service definition*.

ISO/IEC 9072-2:1989, *Information processing systems - Text Communication - Remote Operations - Part 2: Protocol specification*. | CCITT Recommendation X.229:1988, *Remote Operations: Protocol specification*.

ISO/IEC 9595:1991, *Information technology - Open Systems Interconnection - Common management information service definition*. | CCITT Recommendation X.710:1991, *Common management information service definition for CCITT applications*.

ISO/IEC 9596-1:1991, *Information technology - Open Systems Interconnection - Common management information protocol - Part 1: Specification*. | CCITT Recommendation X.711:1991, *Common management information protocol specification for CCITT applications*.

ISO/IEC 9596-2:1992, *Information technology - Open Systems Interconnection - Common management information protocol - Part 2: Protocol implementation conformance statement (PICS) proforma*. | CCITT Recommendation X.712:1992, *Common management information protocol: Protocol implementation conformance statement (PICS) proforma*.

CCITT Recommendation X.701:(1992) | ISO/IEC 10040: 1992, *Information technology - Open Systems Interconnection - Systems Management Overview*.

1) To be published.

ISO/IEC TR 10000-1:1992, *Information technology - Framework and taxonomy of International Standardized Profiles - Part 1: Framework*.

ISO/IEC TR 10000-2:1992, *Information technology - Framework and taxonomy of International Standardized Profiles - Part 2: Taxonomy of Profiles*.

3 Definitions and conventions

For the purpose of this part of ISO/IEC ISP 11183, the following definitions apply.

3.1 Base standard

3.1.1 Definitions

For the purpose of this part of ISO/IEC ISP 11183, the definitions given in the normative references listed in clause 2 apply. Among those the following definitions particularly apply:

CMISE-service-user	:	see ISO/IEC 9595
Initiator	:	see ISO/IEC 9072-1
Invoker	:	see ISO/IEC 9072-1
Notification	:	see ISO/IEC 10040
Operation	:	see ISO/IEC 10040
Performer	:	see ISO/IEC 9072-1
Responder	:	see ISO/IEC 9072-1

3.1.2 PICS definitions and conventions

The notations used in the "Base Standard" column of the annex A of this part of ISO/IEC ISP 11183 are derived from the PICS proforma notations, specified in ISO/IEC 9596-2, such as follows:

m	mandatory function or feature or parameter specified in Base Standards text or in ASN.1 abstract syntax definitions.
o	optional function or feature or parameter specified in Base Standards text or in ASN.1 abstract syntax definitions.
o.1	stands for "support of at least one of the choices is required". "o.1" replaces the notations "o.N" of the PICS, where <i>N</i> is an integer value from 1 up to 128.
cn	(<i>n</i> is an integer) stands for conditional parameters whose support depends on a predicate expression such as : c1 up to c15, and whose definitions are recalled in the clause 3.3.
p	stands for a partial support permitted.
x	prohibited feature or parameter.
i	stands for "out of the scope of this part of ISO/IEC ISP 11183". This means that, for the corresponding element, - implementations may use it outside the scope of this ISP part, - conformance tests shall not be provided for it, - implementations may conform to other profiles where it is required, - no requirements are placed on either transmitter or receiver to support it, - receiver actions are unspecified when present.
-	(dash) for not applicable feature or parameter.

The notations set in the "Base Standard" column reflect the static conformance requirements.

3.2 Profile

The following subclauses specify the notation used for support requirements of Functional Units (FUs), PDUs associated with CMIS services and parameters within PDUs, in the "Profile" column of the annex A of this part of ISO/IEC ISP 11183.

3.2.1 Profile support requirement definitions

The Functional Units table A.7 of the annex A of this part of ISO/IEC ISP 11183 only specifies the static requirement of each additional functional unit in the "Profile" column.

The CMIP PDU tables relative to the support of PDUs associated with each CMIS service, (see tables A.15 up to A.28 of annex A), only specify the static requirement of each PDU in the "Profile" column.

In the profile AOM11, the static support of the PDUs relative to the kernel functional unit is always stated as "mandatory to be implemented".

The support notation used in the "Profile" column of the annex A, for each PDU parameter (see tables A.29 up to A.120), results from the association of :

- a) the implementation static capabilities requirement, such as derived from the base standard, and
- b) the implementation dynamic behaviour requirement, depending on the possible instantiations.

Such a notation complies with the recommendations provided in the annex C of ISO/IEC TR 10000-1.

3.2.2 ISPICS requirements list conventions

In order to express these compound requirements a two character notation is defined such as :

the first letter corresponds to the static capabilities requirement and states whether the element	
must be	} implemented
or may be	
or must not be	
the second letter corresponds to the dynamic behaviour requirement and states whether the element	
must be	} present in an instance of the PDU
or may be	
or must not be	

As a general rule, the static capabilities defined as optional in the Base Standard are made mandatory on the sending PDU tables of the annex A to maximize the usability of the profile AOM11.

The two character combinations used in the "Profile" column of the annex A of this part of ISO/IEC ISP 11183, with the respective requirements, static and dynamic, for the sending and the receiving sides, are specified as follows:

mm	Sending	
	Static:	The implementation must be able to send the parameter
	Dynamic:	The parameter must always be sent in each PDU instance
	Receiving	
	Static:	The implementation must be able to receive the parameter
	Dynamic:	The parameter must always be present in each PDU instance
mo	Sending	
	Static:	The implementation must be able to send the parameter
	Dynamic:	The parameter may optionally be sent in a given PDU instance
	Receiving	
	Static:	The implementation must be able to receive the parameter
	Dynamic:	The parameter may optionally be present in a given PDU instance

- mc** Sending
 Static: The implementation must be able to send the parameter
 Dynamic: The parameter may conditionally be sent in a given PDU instance
 Receiving
 Static: The implementation must be able to receive the parameter
 Dynamic: The parameter may conditionally be present in a given PDU instance
- mp** Sending
 Static: The implementation must be able to send the parameter
 Dynamic: The parameter may be partially supported in a given PDU instance
 Receiving
 Static: The implementation must be able to receive the parameter
 Dynamic: The parameter may be partially supported in a given PDU instance
- oo** Sending
 Static: The implementation may optionally be able to send the parameter
 Dynamic: The parameter may optionally be sent in a given PDU instance
 Receiving
 Static: The implementation may optionally be able to receive the parameter
 Dynamic: The parameter may optionally be present in a given PDU instance
- oc** Sending
 Static: The implementation may optionally be able to send the parameter
 Dynamic: The parameter may conditionally be sent in a given PDU instance
 Receiving
 Static: The implementation may optionally be able to receive the parameter
 Dynamic: The parameter may conditionally be present in a given PDU instance
- xx** excluded from any implementation. The feature should not be present.
- ii** stands for "out of the scope of profile AOM11", for static and dynamic requirements.

The conditions on which support and/or presence of a PDU element is required are stated in a note *n* associated with the 'c' abbreviation,

- such as *cn*, when referring to a common condition *n*,
- such as *c(n)*, when referring to a specific condition *n*.

The list of the common conditions is provided in 3.3. The specific conditions *c(n)* are provided locally at the bottom of the PDU table which refers to it.

3.2.3 Nesting rules in ISPICS requirements list

In the annex A of this part of ISO/IEC ISP 11183, each entry of a table is identified by an index number. This index provides a unique reference to PDUs, Functional Units, and parameters. In the specific PDU tables, the level of numbering (1, 1.1, 1.1.1, etc) indicates parameters within constructed parameters and follows the embedded structures of abstract syntax definitions.

Rule 0

Based on ASN.1 rules, a contained element can only be present if its constructor element is present.

Rule 1

For static capabilities requirements, a mandatory element contained within an optional constructor element is mandatory only if the option is taken.

ISO/IEC ISP 11183-3: 1992 (E)

Rule 2

For dynamic behaviour requirements, the status of a parameter is only applicable within the context of its containing structure. If a constructor element is optional, then presence of any elements contained within that constructor element are automatically conditional on the presence of the containing element. If the contained elements are marked mandatory this means they are mandatory if the containing element is present. Elements inherit the conditions of any element in which they are contained.

Rule 3

There are three types of constructor element specifications:

- **Choice.** A choice is coded as "c17", if there is one and only one of its alternatives to be present in a given instance of the PDU. There is an individual entry for each element of the selection.
- **Sequence or Set.** There is one entry for the SET or SEQUENCE element and there are individual entries for each element contained in the data structure.
- **Set of sequence** (e.g. Attribute List). There is one entry for the SET OF SEQUENCE element and there are individual entries for each element of the sequence.

Rule 4

When determining whether a check should be done by CMIPM or CMISE-service-user the criteria used are relative to the ISO/IEC 9596-1 procedures. If stated in the ISO/IEC 9596-1 procedures, then the check is done by the CMIPM, else the check is done by the CMISE-service-user.

3.3 Common conditions list conventions

The present clause defines the terms of the common conditions used in the annex A of this part of ISO/IEC ISP 11183. The conditions c1 up to c15 are defined in ISO/IEC 9596-2. For consistency of the numbering, the condition c16 is used in the "Base Standard" and "Profile" columns: it replaces the equivalent conditions specified at the bottom of the tables A.57, A.63, A.65 and A.69 in the PICS. The conditions c17 and c18 are peculiar to the profile AOM1n. For each value of n , referred to in cn expression, the formal condition statements are the following:

- c1 if A.7.1 then m else -
- c2 if A.7.2 then m else -
- c3 if A.7.3 then m else -
- c4 if A.14.5/1 or A.14.5/2 then o else -
- c5 if A.7.5 then m else -
- c6 if A.7.1 or A.7.2 or A.7.3 or A.7.4 or A.7.5 then m else o
- c7 if A.7.1 then m else o
- c8 if A.6.2 then m else o.1
- c9 if A.7.2 and (A.14.1/1 or A.14.3/1 or A.14.5/1 or A.14.6/1) then m else -
- c10 if A.7.2 and (A.14.1/2 or A.14.3/2 or A.14.5/2 or A.14.6/2) then m else -
- c11 if A.1.1/1 then m else -
- c12 if A.1.1/2 then m else -
- c13 if A.6.1 then x else m
- c14 if A.7.1 and (A.14.1/1 or A.14.3/1 or A.14.5/1 or A.14.6/1) then m else -
- c15 if A.7.1 and (A.14.1/2 or A.14.3/2 or A.14.5/2 or A.14.6/2) then m else -
- c16 Parameter is present only if a result is generated
NOTE - When used as dynamic support in the "Profile" column this condition has the following meaning : if the result parameter is present then the operation-value parameter shall be present. The operation-value parameter shall not be present in any RORS PDU when the result parameter is absent.
- c17 One and only one of the choices at this level must be present
- c18 Allowed to be present unless associated FU is negotiated away

NOTES

- 1 The conditions c9, c10, c14, c15 and c18 do not appear in this part of ISO/IEC ISP 11183. They only occur here to keep the consistency of the numbering specified in the base standard and in other AOM1n profiles.
- 2 The meanings of the condition statements c1 up to c15 are the following:

- c1 if MOS FU is supported then m else -
- c2 if Filter FU is supported then m else -
- c3 if MR FU is supported then m else -
- c4 if M-GET service is supported then o else -
- c5 if Cancel get FU is supported then m else -
- c6 if MOS or Filter or MR or Extended service or Cancel get FUs are supported then m else o
- c7 if MOS FU is supported then m else o
- c8 if all of the Kernel FU is supported then m else o.1
- c9 if Filter FU and (M-ACTION or M-DELETE or M-GET or M-SET) are supported in the invoker role then m else -
- c10 if Filter FU and (M-ACTION or M-DELETE or M-GET or M-SET) are supported in the performer role then m else -
- c11 if association initiator capability is supported then m else -
- c12 if association responder capability is supported then m else -
- c13 if support of some of the kernel CMIS services then x else m
- c14 if MOS FU and (M-ACTION or M-DELETE or M-GET or M-SET) are supported in the invoker role then m else -
- c15 if MOS FU and (M-ACTION or M-DELETE or M-GET or M-SET) are supported in the performer role then m else -

4 Abbreviations

ACSE	Association Control Service Element
AOM	Application OSI Management
APDU	Application Protocol Data Unit
ASN.1	Abstract Syntax Notation One
CMIP	Common Management Information Protocol
CMIPM	Common Management Information Protocol Machine
CMIPDU	Common Management Information Protocol Data Unit
CMIS	Common Management Information Service
CMISE	Common Management Information Service Element
FU	Functional Unit
ISP	International Standardized Profile
ISPICS	ISP Implementation Conformance Statement
MOS	Multiple Object Selection
MR	Multiple Reply
OSI	Open Systems Interconnection
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
ROER	Remote Operation Error
ROIV	Remote Operation Invoke
RORJ	Remote Operation Reject
RORS	Remote Operation Result
ROSE	Remote Operation Service Element
A-Profile	Application Profile (requiring connection-mode Transport Service)
T-Profile	Transport Profile (providing connection-mode Transport Service)

5 Conformance to AOM11

A claim of conformance to the profile AOM11 is a claim that all requirements in the relevant base standards are satisfied, and that all requirements, in the following clauses and in the annex A of this part of ISO/IEC ISP 11183 and also in ISO/IEC ISP 11183-1, are satisfied.

5.1 Conformance statement

A supplier claiming conformance to the profile AOM11 shall make available a statement of support or non-support of each optional function, feature or parameter identified in ISO/IEC ISP 11183-1 and ISO/IEC ISP 11183-3.

5.2 CMIP conformance

An implementation conforming to this part of ISO/IEC ISP 11183 shall satisfy the conformance requirements of ISO/IEC 9596-1 and ISO/IEC 9596-2. This part of ISO/IEC ISP 11183 requires the support of the kernel functional unit and the corresponding PDUs specified in ISO/IEC 9596-1 and ISO/IEC 9596-2. The support of additional functional units, i.e. multiple object selection, filter, multiple reply, extended service and cancel get, shall be out of the scope of the profile AOM11.

In compliance with the static conformance requirements of CMIP, and depending on the scope defined above, conforming implementations shall support all the features mandated by this part of ISO/IEC ISP 11183.

Implementations conforming to the profile AOM11 shall implement all the mandatory 'mm', 'mo', 'mc' and 'mp' features.

They shall state which optional 'oo' features are implemented and used.

They shall state which conditional 'oc' features are implemented and used.

They shall provide a list of the supported CMISE errors for each operation. (See annex A, table 125, for the complete list of the CMISE errors used against the different operations).

They shall support the version 2 of the CMIP protocol and its corresponding abstract syntax, such as defined in ISO/IEC 9596-1, for the kernel functional unit. Version 1 is outside the scope of the profile AOM11.

The elements of procedure as specified in ISO/IEC 9596-1 shall be supported for the kernel functional unit. A CMIPM conforming to the profile AOM11 shall negotiate away the additional functional units specified as "out of the scope".

Conforming implementations shall support the ASN.1 transfer syntax, for the purpose of generating and interpreting the CMISE PDUs as specified in ISO/IEC 9596-1 for the kernel functional unit.

The receiver of an erroneous invoke operation shall issue an error notification type that corresponds to the definition for the original invoke operation.

The specification of the contents type of the parameter "accessControl" in CMIPUserInfo definition is outside the scope of the profile AOM11.

The specification of the contents type of the parameter "userInfo" in CMIPUserInfo and CMIPAbortInfo definitions is outside the scope of the profile AOM11.

The specifications of the contents type of the parameter "access Control", included in "Action Argument", "Create Argument", "Delete Argument", "Get Argument" and "Set Argument" parameters are outside the scope of the profile AOM11.

NOTE - Other profiles, e.g. AOM2nn, provide definitions of parameters specified by the ASN.1 "ANY DEFINED BY" type. These consist of the list of the possible ASN.1 types to be carried by the ANY element for each integer type value or each object identifier value of the associated identifier. (The list of the ASN.1 identifiers of such parameters is provided in annex A).

5.3 Association establishment and abort requirements

An implementation conforming to the profile AOM11 may support any of the configurations, that is, an implementation may be the Initiator or Responder of an association.

NOTES

- 1 For two implementations to interoperate one must act as an Initiator and the other as a Responder of an association.
- 2 The complete association requirements are specified in ISO/IEC ISP 11183-1.

Conforming implementations shall support the "user-information" parameter of AARQ, AARE and ABRT APDUs for the encoding and the decoding of CMIPUserInfo and CMIPAbortInfo parameters.

The usage of "accessControl" and "userInfo" parameters in the CMIPUserInfo sequence, which are of EXTERNAL ASN.1 type, requires that additional Abstract Syntax name(s) be specified and negotiated.

5.4 ROSE conformance

This part of ISO/IEC ISP 11183 specifies implementation options or selections such that conforming implementations will satisfy the conformance requirements of ISO/IEC 9072-2; In particular, according to the "Statement Requirements", (10.1), the application context of conforming implementations shall support the mapping of ROSE APDUs only onto the P-DATA Presentation service.

The profile AOM11 includes some additional requirements above those required in ISO/IEC 9072-2.

Implementations conforming to the profile AOM11 shall implement all the mandatory features and indicate the support of any optional features that have been implemented.

They shall use the ROIV, RORS, ROER and RORJ APDUs definitions to exchange the CMIPDUs.

The support of RORJ APDU is required. The invokeProblem parameter shall be able to carry the "duplicateInvocation", "mistypedArgument", "resourceLimitation" and "unrecognizedOperation" values. These are mapped to the corresponding CMIS error parameters and passed to the CMISE-service-user. The other values specified in ISO/IEC 9072-2 are optional.

The profile AOM11 does not prohibit the use of RORJ APDU as a response to rejected unconfirmed operations. This means that implementations must guard against confusion due to different RORJ APDUs by allowing sufficient amount of time between reuse of the same "InvokeID" value.

ISO/IEC 9596-1 uses the following operation classes, according to the application requirements :

- class 1, for synchronous confirmed operation
- class 2, for asynchronous confirmed operation
- class 5, for asynchronous unconfirmed operation.

The profile AOM11 does not restrain or does not enforce the selection of operation class 1. The support level of this feature is specified as shown in table 2.

Table 2 - Operation classes support

Classes	1	2	3	4	5
Support	o	o(1)	x	x	m

- (1) The performer of operations shall be capable of receiving asynchronous operation invocations.

Annex A

(normative)

ISPICS Requirements List for ISO/IEC ISP 11183-3

AOM11

In the event of a discrepancy becoming apparent in the body of this part of ISO/IEC ISP 11183 and the tables in this annex, this annex is to take precedence.

This annex specifies the support constraints and characteristics of this part of ISO/IEC ISP 11183 that have to or may appear in the implementation columns of an ISPICS.

This annex is based on the annex A of ISO/IEC 9596-2; it uses the numbering, the contents and the structure of the tables which are specified in that document. In particular, the table numbers and the index numbers are aligned with the corresponding table numbers and index numbers of the PICS proforma. It is worth noting that, when a row in a table or a table is not required for this profile, its contents are missing in this part of ISO/IEC ISP 11183; nevertheless, the number and the title of the missing tables are always reproduced.

The "Syntax" column provided in each PDU table of the PICS proforma is not reproduced in this annex. For the parameters which are specified as an ASN.1 CHOICE in the PDU tables of the PICS proforma, the "Profile" support of each element of CHOICE is defined once only in the tables A13a and A13b, entitled "Common parameter support".

The tables contained in this annex correspond to the tables with the same number as in annex A of ISO/IEC ISP 11183-2. The tables that correspond to the features that are not included in this part of ISO/IEC ISP 11183 are indicated to fall outside the scope of the profile AOM11. The tables that are included specify exactly the same requirements as in part 2 for the features that are within the scope of this part of ISO/IEC ISP 11183.

The PDU names are those which are defined in annex B of ISO/IEC 9596-1. The parameter names are those which are specified in 7.3 and 7.4 of ISO/IEC 9596-1.

The abbreviations as used in the headings of the tables are:

Base Std.	conformance requirement as defined in the "Status" column of ISO/IEC 9596-2
Profile	conformance requirement for this part of ISO/IEC ISP 11183
Support	requirement supported by the implementations.

The notations used in the "Base Standard" columns are defined in 3.1.2 and 3.3 of this part of ISO/IEC ISP 11183.

The notations used in the "Profile" columns are defined in 3.2.2 and 3.3 of this part of ISO/IEC ISP 11183.

A.1 Global statement of conformance

The supplier of the implementation shall state whether or not all mandatory capabilities are implemented for ISO/IEC ISP 11183-3. CMIP version 2 is defined in ISO/IEC 9596-1.

	Profile	Support
Version of CMIP Protocol Version	Version 2	
Are all mandatory capabilities implemented?	m	

Answering NO to this question indicates non-conformance to the profile AOM11. Non-supported mandatory capabilities may be listed in the table below.

Capability not implemented	Reason

A.2 Capabilities

A.2.1 Initiator/Responder capability

The supplier of the implementation shall state the capability for initiating and responding to an association request, which specifies the use of CMISE, and for releasing an association, in the tables below.

Table A.1 - Association initialisation

Capability		Association initiator			Association responder		
Index	Does the implementation support:	Base Std.	Profile	Support	Base Std.	Profile	Support
A.1.1	association initialisation ?	o.1	o.1		o.1	o.1	

Table A.2 - Association release

Capability		Release initiator			Release responder		
Index	Does the implementation support:	Base Std.	Profile	Support	Base Std.	Profile	Support
A.2.1	release for an association initiated by the implementation ?	o.1	m		o.1	m	
A.2.1	release for an association not initiated by the implementation ?	o.1	m		o.1	m	

A.2.2 ASN.1 EXTERNAL type parameters support

In some PDUs the following parameters are of the ASN.1 type EXTERNAL:

userInfo in CMIPUserInfo,
 userInfo in CMIPAbortInfo,
 accessControl in CMIPUserInfo,
 accessControl in several CMIP PDUs.

Unlike other parameters, the static "mandatory" support in the "Profile" column indicates that the CMIP implementation shall be able to parse or process all the fields in this EXTERNAL parameter except the "encoding" field (the "encoding" field can be one of the following three types: ANY, OCTET STRING or BIT STRING). The processing of the "encoding" field is out of scope for the CMIP implementation.

A.2.3 CMIPUserInfo parameter support

Table A.3 - CMIPUserInfo parameter support (in AARQapdu)

Index	Parameter name	AARQ Sending			AARQ Receiving		
		Base Std.	Profile	Type, value(s) & range(s)	Base Std.	Profile	Type, value(s) & ranges(s)
A.3.1	CMIPUserInfo	c11	mm		c12	mm	
A.3.1.1	protocolVersion	m	mm	version 2	m	mm	version 2
A.3.1.2	functionalUnits	c6	oo	(1)	m	mo	(1)
A.3.1.3	accessControl	o	mo	(2)	m	mo	(2)
A.3.1.4	userInfo	o	mo	(2)	m	mo	(2)

- (1) The initiator shall be able of proposing kernel FU only, i.e. either the DEFAULT value {} or the empty BIT STRING value of the functional units parameter shall be used. Other FUs are out of scope of AOM11 profile.
- (2) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the EXTERNAL type.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

Table A.4 - CMIPUserInfo parameter support (in AAREapdu)

		AARE Sending			AARE Receiving		
Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)	Base Std.	Profile	Type, value(s) & range(s)
A.4.1	CMIPUserInfo	c12	mm		c11	mm	
A.4.1.1	protocolVersion	m	mm	version 2 (3)	m	mm	version 2 (3)
A.4.1.2	functionalUnits	c6	mo	(1)	m	mo	(1)
A.4.1.3	accessControl	o	mo	(2)	m	mo	(2)
A.4.1.4	userInfo	o	mo	(2)	m	mo	(2)

- (1) Responding CMISE provider shall negotiate down from any set of proposed functional units to either the DEFAULT value {} or the empty BIT STRING value of the functional units parameter.
- (2) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the EXTERNAL type.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

- (3) System may negotiate away Version 1.

A.2.4. CMIPAbortInfo parameter support

Table A.5 - CMIPAbortInfo parameter support

Index	Parameter name	Sender			Receiver		
		Base Std.	Profile	Type, value(s) & range(s)	Base Std.	Profile	Type, value(s) & range(s)
A.5.1	CMIPAbortInfo	m	mm		m	mm	
A.5.1.1	abortSource	m	mm		m	mm	
A.5.1.2	userInfo	o	mo	(1)	m	mo	(1)

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the EXTERNAL type.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

A.2.5 Major capabilities

Table A.6 - Conformance claim

Index	Does the implementation support the protocol required to provide:	Base Std.	Profile	Support
A.6.1	some of the kernel CMIS services in the invoker and/or performer roles?	o	i	
A.6.2	all of the kernel CMIS services in both roles?	c13	m	

Table A.7 - Additional functional unit support

Index	Functional unit	Base Std.	Profile
A.7.1	Multiple object selection	o	i(1)
A.7.2	Filter	o	i(1)
A.7.3	Multiple reply	c7	i(1)
A.7.4	Extended service	o	i(1)
A.7.5	Cancel get	c4	i(1)

- (1) The support 'i' for all the additional FUs does not imply that the support of the functional units parameter in CMIPUserInfo becomes 'i': see tables A.3 and A.4, note (1).

A.3 Protocol parameters

A.3.1 System wide parameters

Table A.8 - Scope parameter support

Out of the scope of profile AOM11

Table A.9 - FilterItem parameter support (sending)

Out of the scope of profile AOM11

Table A.10 - FilterItem parameter support (receiving)

Out of the scope of profile AOM11

Table A.11 - CMISFilter parameter support

Out of the scope of profile AOM11

Table A.12 - CMISFilter complexity limitations

Out of the scope of profile AOM11

A.3.2 Common protocol parameters

Common parameters may have a specification applicable for many PDUs in which they occur.

The "Profile" column in the tables A.13a and A.13b is only referring to the static support.

Table A.13a - Common parameter support - (sending)

Index	Parameter name	Syntax	Profile (1)	Type, value(s) & range(s)
A.13a.1	invokeID	INTEGER	m	See ISP 11183-1,8.3
A.13a.2	linked-ID	INTEGER	-	See ISP 11183-1,8.3
A.13a.3	baseManagedObjectClass	OBJECT IDENTIFIER INTEGER	m i	
A.13a.4	baseManagedObjectInstance	DistinguishedName OCTET STRING RDNSequence	m i m	
A.13a.5	accessControl	EXTERNAL	m	(2)
A.13a.6	synchronization	ENUMERATED	i	0 to 1
A.13a.7	managedObjectClass	OBJECT IDENTIFIER INTEGER	m i	
A.13a.8	managedObjectInstance	DistinguishedName OCTET STRING RDNSequence	m i m	
A.13a.9	currentTime	GeneralizedTime	m	
A.13a.10	actionType	OBJECT IDENTIFIER INTEGER	m i	
A.13a.11	attributeId	OBJECT IDENTIFIER INTEGER	m i	
A.13a.12	eventType	OBJECT IDENTIFIER INTEGER	m i	

- (1) For this part of ISO/IEC ISP 11183, the values for the "Profile" column in this table apply consistently across all PDU parameter tables, which use the corresponding common parameter.
- (2) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the EXTERNAL type. If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

Table A.13b - Common parameter support - (receiving)

Index	Parameter name	Syntax	Profile (1)	Type, value(s) & range(s)
A.13b.1	invokeID	INTEGER	m	See ISP 11183-1,8.3
A.13b.2	linked-ID	INTEGER	-	See ISP 11183-1,8.3
A.13b.3	baseManagedObjectClass	OBJECT IDENTIFIER INTEGER	m m	
A.13b.4	baseManagedObjectInstance	DistinguishedName OCTET STRING RDNSequence	m m m	
A.13b.5	accessControl	EXTERNAL	m	(2)
A.13b.6	synchronization	ENUMERATED	m	0 to 1
A.13b.7	managedObjectClass	OBJECT IDENTIFIER INTEGER	m m	
A.13b.8	managedObjectInstance	DistinguishedName OCTET STRING RDNSequence	m m m	
A.13b.9	currentTime	GeneralizedTime	m	
A.13b.10	actionType	OBJECT IDENTIFIER INTEGER	m m	
A.13b.11	attributeId	OBJECT IDENTIFIER INTEGER	m m	
A.13b.12	eventType	OBJECT IDENTIFIER INTEGER	m m	

- (1) For this part of ISO/IEC ISP 11183, the values for the "Profile" column in this table apply consistently across all PDU parameter tables, which use the corresponding common parameter.
- (2) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the EXTERNAL type. If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

A.4 Protocol data units

Table A.14 - Protocol support for kernel CMIS services

		Invoker role				Performer role			
Index	CMIS service	PDU table	Base Std.	Profile	Support	PDU table	Base Std.	Profile	Support
A.14.1	M-ACTION	A.15	c8	m		A.16	c8	m	
A.14.2	M-CREATE	A.19	c8	m		A.20	c8	m	
A.14.3	M-DELETE	A.21	c8	m		A.22	c8	m	
A.14.4	M-EVENT-REPORT	A.23	c8	m		A.24	c8	m	
A.14.5	M-GET	A.25	c8	m		A.26	c8	m	
A.14.6	M-SET	A.27	c8	m		A.28	c8	m	

The following tables, A.15 up to A.28, provide the sets of PDUs required to support the CMIS services in the invoker and performer roles.

The "Base Standard" column states that all the PDUs for kernel functional unit are mandatory. The PDUs which depend on support of the additional functional units are conditional.

The "Profile" column states that all the PDUs for kernel functional unit are mandatory. The PDUs which depend on support of the additional functional units are stated 'i'.

The column entitled "Support" should be completed in the following tables to state which PDUs are supported by the implementations.

The four CMIS errors "duplicateInvocation", "mismatchedArgument", "resourceLimitation", "unrecognizedOperation" do not result in ROER PDUs, but are mapped onto RORJ PDU (see tables A.119 and A.120).

Table A.15 - CMIP PDUs required to support M-ACTION service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.15.1	ROIV-m-Action	m	m	
A.15.2	ROIV-m-Action-Confirmed	m	m	
A.15.3	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.15.4	RORS-m-Action-Confirmed	m	m	
A.15.5	ROIV-m-LinkedReply-Action	c3	i	
A.15.6	ROER-accessDenied	m	m	
A.15.7	ROER-classInstanceConflict	m	m	
A.15.8	ROER-complexityLimitation	m	m	
A.15.9	ROER-invalidArgumentValue	m	m	
A.15.10	ROER-invalidFilter	c2	i	
A.15.11	ROER-invalidScope	c1	i	
A.15.12	ROER-noSuchAction	m	m	
A.15.13	ROER-noSuchArgument	m	m	
A.15.14	ROER-noSuchObjectClass	m	m	
A.15.15	ROER-noSuchObjectInstance	m	m	
A.15.16	ROER-processingFailure	m	m	
A.15.17	ROER-syncNotSupported	c1	i	
A.15.18	RORJ	m	m	

Table A.16 - CMIP PDUs required to support M-ACTION service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.16.1	ROIV-m-Action	m	m	
A.16.2	ROIV-m-Action-Confirmed	m	m	
A.16.3	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.16.4	RORS-m-Action-Confirmed	m	m	
A.16.5	ROIV-m-LinkedReply-Action	c3	i	
A.16.6	ROER-accessDenied	m	m	
A.16.7	ROER-classInstanceConflict	m	m	
A.16.8	ROER-complexityLimitation	m	m	
A.16.9	ROER-invalidArgumentValue	m	m	
A.16.10	ROER-invalidFilter	c2	i	
A.16.11	ROER-invalidScope	c1	i	
A.16.12	ROER-noSuchAction	m	m	
A.16.13	ROER-noSuchArgument	m	m	
A.16.14	ROER-noSuchObjectClass	m	m	
A.16.15	ROER-noSuchObjectInstance	m	m	
A.16.16	ROER-processingFailure	m	m	
A.16.17	ROER-syncNotSupported	c1	i	
A.16.18	RORJ	m	m	

Table A.17 - CMIP PDUs required to support M-CANCEL-GET service in the invoker role
Out of the scope of profile AOM11

Table A.18 - CMIP PDUs required to support M-CANCEL-GET service in the performer role
Out of the scope of profile AOM11

Table A.19 - CMIP PDUs required to support M-CREATE service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.19.1	ROIV-m-Create	m	m	
A.19.2	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.19.3	RORS-m-Create	m	m	
A.19.4	ROER-accessDenied	m	m	
A.19.5	ROER-classInstanceConflict	m	m	
A.19.6	ROER-duplicateManagedObjectInstance	m	m	
A.19.7	ROER-invalidAttributeValue	m	m	
A.19.8	ROER-invalidObjectInstance	m	m	
A.19.9	ROER-missingAttributeValue	m	m	
A.19.10	ROER-noSuchAttribute	m	m	
A.19.11	ROER-noSuchObjectClass	m	m	
A.19.12	ROER-noSuchObjectInstance	m	m	
A.19.13	ROER-noSuchReferenceObject	m	m	
A.19.14	ROER-processingFailure	m	m	
A.19.15	RORJ	m	m	

Table A.20 - CMIP PDUs required to support M-CREATE service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.20.1	ROIV-m-Create	m	m	
A.20.2	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.20.3	RORS-m-Create	m	m	
A.20.4	ROER-accessDenied	m	m	
A.20.5	ROER-classInstanceConflict	m	m	
A.20.6	ROER-duplicateManagedObjectInstance	m	m	
A.20.7	ROER-invalidAttributeValue	m	m	
A.20.8	ROER-invalidObjectInstance	m	m	
A.20.9	ROER-missingAttributeValue	m	m	
A.20.10	ROER-noSuchAttribute	m	m	
A.20.11	ROER-noSuchObjectClass	m	m	
A.20.12	ROER-noSuchObjectInstance	m	m	
A.20.13	ROER-noSuchReferenceObject	m	m	
A.20.14	ROER-processingFailure	m	m	
A.20.15	RORJ	m	m	

Table A.21 - CMIP PDUs required to support M-DELETE service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.21.1	ROIV-m-Delete	m	m	
A.21.2	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.21.3	RORS-m-Delete	m	m	
A.21.4	ROIV-m-LinkedReply-Delete	c3	i	
A.21.5	ROER-accessDenied	m	m	
A.21.6	ROER-classInstanceConflict	m	m	
A.21.7	ROER-complexityLimitation	m	m	
A.21.8	ROER-invalidFilter	c2	i	
A.21.9	ROER-invalidScope	c1	i	
A.21.10	ROER-noSuchObjectClass	m	m	
A.21.11	ROER-noSuchObjectInstance	m	m	
A.21.12	ROER-processingFailure	m	m	
A.21.13	ROER-syncNotSupported	c1	i	
A.21.14	RORJ	m	m	

Table A.22 - CMIP PDUs required to support M-DELETE service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.22.1	ROIV-m-Delete	m	m	
A.22.2	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.22.3	RORS-m-Delete	m	m	
A.22.4	ROIV-m-LinkedReply-Delete	c3	i	
A.22.5	ROER-accessDenied	m	m	
A.22.6	ROER-classInstanceConflict	m	m	
A.22.7	ROER-complexityLimitation	m	m	
A.22.8	ROER-invalidFilter	c2	i	
A.22.9	ROER-invalidScope	c1	i	
A.22.10	ROER-noSuchObjectClass	m	m	
A.22.11	ROER-noSuchObjectInstance	m	m	
A.22.12	ROER-processingFailure	m	m	
A.22.13	ROER-syncNotSupported	c1	i	
A.22.14	RORJ	m	m	

Table A.23 - CMIP PDUs required to support M-EVENT-REPORT service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.23.1	ROIV-m-EventReport	m	m	
A.23.2	ROIV-m-EventReport-Confirmed	m	m	
A.23.3	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.23.4	RORS-m-EventReport-Confirmed	m	m	
A.23.5	ROER-invalidArgumentValue	m	m	
A.23.6	ROER-noSuchArgument	m	m	
A.23.7	ROER-noSuchEventType	m	m	
A.23.8	ROER-noSuchObjectClass	m	m	
A.23.9	ROER-noSuchObjectInstance	m	m	
A.23.10	ROER-processingFailure	m	m	
A.23.11	RORJ	m	m	

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 11183-3:1992

Table A.24 - CMIP PDUs required to support M-EVENT-REPORT service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.24.1	ROIV-m-EventReport	m	m	
A.24.2	ROIV-m-EventReport-Confirmed	m	m	
A.24.3	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.24.4	RORS-m-EventReport-Confirmed	m	m	
A.24.5	ROER-invalidArgumentValue	m	m	
A.24.6	ROER-noSuchArgument	m	m	
A.24.7	ROER-noSuchEventType	m	m	
A.24.8	ROER-noSuchObjectClass	m	m	
A.24.9	ROER-noSuchObjectInstance	m	m	
A.24.10	ROER-processingFailure	m	m	
A.24.11	RORJ	m	m	

Table A.25 - CMIP PDUs required to support M-GET service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.25.1	ROIV-m-Get	m	m	
A.25.2	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.25.3	RORS-m-Get	m	m	
A.25.4	ROIV-m-LinkedReply-Get	c3	i	
A.25.5	ROER-accessDenied	m	m	
A.25.6	ROER-classInstanceConflict	m	m	
A.25.7	ROER-complexityLimitation	m	m	
A.25.8	ROER-getListError	m	m	
A.25.9	ROER-invalidFilter	c2	i	
A.25.10	ROER-invalidScope	c1	i	
A.25.11	ROER-noSuchObjectClass	m	m	
A.25.12	ROER-noSuchObjectInstance	m	m	
A.25.13	ROER-operationCancelled	c5	i	
A.25.14	ROER-processingFailure	m	m	
A.25.15	ROER-syncNotSupported	c1	i	
A.25.16	RORJ	m	m	

Table A.26 - CMIP PDUs required to support M-GET service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.26.1	ROIV-m-Get	m	m	
A.26.2	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.26.3	RORS-m-Get	m	m	
A.26.4	ROIV-m-LinkedReply-Get	c3	i	
A.26.5	ROER-accessDenied	m	m	
A.26.6	ROER-classInstanceConflict	m	m	
A.26.7	ROER-complexityLimitation	m	m	
A.26.8	ROER-getListError	m	m	
A.26.9	ROER-invalidFilter	c2	i	
A.26.10	ROER-invalidScope	c1	i	
A.26.11	ROER-noSuchObjectClass	m	m	
A.26.12	ROER-noSuchObjectInstance	m	m	
A.26.13	ROER-operationCancelled	c5	i	
A.26.14	ROER-processingFailure	m	m	
A.26.15	ROER-syncNotSupported	c1	i	
A.26.16	RORJ	m	m	

Table A.27 - CMIP PDUs required to support M-SET service in the invoker role

Invoker sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.27.1	ROIV-m-Set	m	m	
A.27.2	ROIV-m-Set-Confirmed	m	m	
A.27.3	RORJ	m	m	
Invoker receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.27.4	RORS-m-Set-Confirmed	m	m	
A.27.5	ROIV-m-LinkedReply-Set	c3	i	
A.27.6	ROER-accessDenied	m	m	
A.27.7	ROER-classInstanceConflict	m	m	
A.27.8	ROER-complexityLimitation	m	m	
A.27.9	ROER-invalidFilter	c2	i	
A.27.10	ROER-invalidScope	c1	i	
A.27.11	ROER-noSuchObjectClass	m	m	
A.27.12	ROER-noSuchObjectInstance	m	m	
A.27.13	ROER-processingFailure	m	m	
A.27.14	ROER-setListError	m	m	
A.27.15	ROER-syncNotSupported	c1	i	
A.27.16	RORJ	m	m	

Table A.28 - CMIP PDUs required to support M-SET service in the performer role

Performer receiving				
Index	Protocol data unit	Base Std.	Profile	Support
A.28.1	ROIV-m-Set	m	m	
A.28.2	ROIV-m-Set-Confirmed	m	m	
A.28.3	RORJ	m	m	
Performer sending				
Index	Protocol data unit	Base Std.	Profile	Support
A.28.4	RORS-m-Set-Confirmed	m	m	
A.28.5	ROIV-m-LinkedReply-Set	c3	i	
A.28.6	ROER-accessDenied	m	m	
A.28.7	ROER-classInstanceConflict	m	m	
A.28.8	ROER-complexityLimitation	m	m	
A.28.9	ROER-invalidFilter	c2	i	
A.28.10	ROER-invalidScope	c1	i	
A.28.11	ROER-noSuchObjectClass	m	m	
A.28.12	ROER-noSuchObjectInstance	m	m	
A.28.13	ROER-processingFailure	m	m	
A.28.14	ROER-setListError	m	m	
A.28.15	ROER-syncNotSupported	c1	i	
A.28.16	RORJ	m	m	

A.5 PDU parameters

Table A.29 - ROIV-m-Action (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.29.1	invokeID	m	mm	
A.29.2	linked-ID	x	xx	
A.29.3	operation-value	m	mm	6
A.29.4	ActionArgument	m	mm	
A.29.4.1	baseManagedObjectClass	m	mm	
A.29.4.2	baseManagedObjectInstance	m	mm	
A.29.4.3	accessControl	o	mo	(1)
A.29.4.4	synchronization	c1	ii	0 to 1
A.29.4.5	scope	c1	ii	
A.29.4.6	filter	c2	ii	
A.29.4.7	ActionInfo	m	mm	
A.29.4.7.1	actionType	m	mm	
A.29.4.7.2	actionInfoArg	o	mo	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

Table A.30 - ROIV-m-Action (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.30.1	invokeID	m	mm	
A.30.2	linked-ID	x	xx	
A.30.3	operation-value	m	mm	6
A.30.4	ActionArgument	m	mm	
A.30.4.1	baseManagedObjectClass	m	mm	
A.30.4.2	baseManagedObjectInstance	m	mm	
A.30.4.3	accessControl	m	mo	(1)
A.30.4.4	synchronization	c1	ii	0 to 1
A.30.4.5	scope	c1	ii	
A.30.4.6	filter	c2	ii	
A.30.4.7	ActionInfo	m	mm	
A.30.4.7.1	actionType	m	mm	
A.30.4.7.2	actionInfoArg	m	mo	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

Table A.31 - ROIV-m-Action-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.31.1	invokeID	m	mm	
A.31.2	linkedID	x	xx	
A.31.3	operation-value	m	mm	7
A.31.4	ActionArgument	m	mm	
A.31.4.1	baseManagedObjectClass	m	mm	
A.31.4.2	baseManagedObjectInstance	m	mm	
A.31.4.3	accessControl	o	mo	(1)
A.31.4.4	synchronization	c1	ii	0 to 1
A.31.4.5	scope	c1	ii	
A.31.4.6	filter	c2	ii	
A.31.4.7	ActionInfo	m	mm	
A.31.4.7.1	actionType	m	mm	
A.31.4.7.2	actionInfoArg	o	mo	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

Table A.32 - ROIV-m-Action-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.32.1	invokeID	m	mm	
A.32.2	linked-ID	x	xx	
A.32.3	operation-value	m	mm	7
A.32.4	ActionArgument	m	mm	
A.32.4.1	baseManagedObjectClass	m	mm	
A.32.4.2	baseManagedObjectInstance	m	mm	
A.32.4.3	accessControl	m	mo	(1)
A.32.4.4	synchronization	c1	ii	0 to 1
A.32.4.5	scope	c1	ii	
A.32.4.6	filter	c2	ii	
A.32.4.7	ActionInfo	m	mm	
A.32.4.7.1	actionType	m	mm	
A.32.4.7.2	actionInfoArg	m	mo	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

Table A.33 - ROIV-m-Cancel-Get (sending)

Out of the scope of profile AOM11

Table A.34 - ROIV-m-Cancel-Get (receiving)

Out of the scope of profile AOM11

Table A.35 - ROIV-m-Create (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.35.1	invokeID	m	mm	
A.35.2	linked-ID	x	xx	
A.35.3	operation-value	m	mm	8
A.35.4	CreateArgument	m	mm	
A.35.4.1	managedObjectClass	m	mm	
A.35.4.2	instance (2)	o	mo	
A.35.4.2.1	managedObjectInstance	m	mc17	
A.35.4.2.2	superiorObjectInstance	m	mc17	
A.35.4.3	accessControl	o	mo	(1)
A.35.4.4	referenceObjectInstance	o	mo	
A.35.4.5	attributeList	o	mo	
A.35.4.5.1	attributeId	m	mm	
A.35.4.5.2	attributeValue	m	mm	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

- (2) Identifier only provided for naming convenience.

Table A.36 - ROIV-m-Create (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.36.1	invokeID	m	mm	
A.36.2	linked-ID	x	xx	
A.36.3	operation-value	m	mm	8
A.36.4	CreateArgument	m	mm	
A.36.4.1	managedObjectClass	m	mm	
A.36.4.2	instance (2)	m	mo	
A.36.4.2.1	managedObjectInstance	m	mc17	
A.36.4.2.2	superiorObjectInstance	m	mc17	
A.36.4.3	accessControl	m	mo	(1)
A.36.4.4	referenceObjectInstance	m	mo	
A.36.4.5	attributeList	m	mo	
A.36.4.5.1	attributeId	m	mm	
A.36.4.5.2	attributeValue	m	mm	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

- (2) Identifier only provided for naming convenience.

Table A.37 - ROIV-m-Delete (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.37.1	invokeID	m	mm	
A.37.2	linked-ID	x	xx	
A.37.3	operation-value	m	mm	9
A.37.4	DeleteArgument	m	mm	
A.37.4.1	baseManagedObjectClass	m	mm	
A.37.4.2	baseManagedObjectInstance	m	mm	
A.37.4.3	accessControl	o	mo	(1)
A.37.4.4	synchronization	c1	ii	0 to 1
A.37.4.5	scope	c1	ii	
A.37.4.6	filter	c2	ii	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

Table A.38 - ROIV-m-Delete (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.38.1	invokeID	m	mm	
A.38.2	linked-ID	x	xx	
A.38.3	operation-value	m	mm	9
A.38.4	DeleteArgument	m	mm	
A.38.4.1	baseManagedObjectClass	m	mm	
A.38.4.2	baseManagedObjectInstance	m	mm	
A.38.4.3	accessControl	m	mo	(1)
A.38.4.4	synchronization	c1	ii	0 to 1
A.38.4.5	scope	c1	ii	
A.38.4.6	filter	c2	ii	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

Table A.39 - ROIV-m-EventReport (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.39.1	invokeID	m	mm	
A.39.2	linked-ID	x	xx	
A.39.3	operation-value	m	mm	0
A.39.4	EventReportArgument	m	mm	
A.39.4.1	managedObjectClass	m	mm	
A.39.4.2	managedObjectInstance	m	mm	
A.39.4.3	eventTime	o	mo	
A.39.4.4	eventType	m	mm	
A.39.4.5	eventInfo	o	mo	

Table A.40 - ROIV-m-EventReport (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.40.1	invokeID	m	mm	
A.40.2	linked-ID	x	xx	
A.40.3	operation-value	m	mm	0
A.40.4	EventReportArgument	m	mm	
A.40.4.1	managedObjectClass	m	mm	
A.40.4.2	managedObjectInstance	m	mm	
A.40.4.3	eventTime	m	mo	
A.40.4.4	eventType	m	mm	
A.40.4.5	eventInfo	m	mo	

Table A.41 - ROIV-m-EventReport-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.41.1	invokeID	m	mm	
A.41.2	linked-ID	x	xx	
A.41.3	operation-value	m	mm	1
A.41.4	EventReportArgument	m	mm	
A.41.4.1	managedObjectClass	m	mm	
A.41.4.2	managedObjectInstance	m	mm	
A.41.4.3	eventTime	o	mo	
A.41.4.4	eventType	m	mm	
A.41.4.5	eventInfo	o	mo	

Table A.42 - ROIV-m-EventReport-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.42.1	invokeID	m	mm	
A.42.2	linked-ID	x	xx	
A.42.3	operation-value	m	mm	1
A.42.4	EventReportArgument	m	mm	
A.42.4.1	managedObjectClass	m	mm	
A.42.4.2	managedObjectInstance	m	mm	
A.42.4.3	eventTime	m	mo	
A.42.4.4	eventType	m	mm	
A.42.4.5	eventInfo	m	mo	

Table A.43 - ROIV-m-Get (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.43.1	invokeID	m	mm	
A.43.2	linked-ID	x	xx	
A.43.3	operation-value	m	mm	3
A.43.4	GetArgument	m	mm	
A.43.4.1	baseManagedObjectClass	m	mm	
A.43.4.2	baseManagedObjectInstance	m	mm	
A.43.4.3	accessControl	o	mo	(1)
A.43.4.4	synchronization	c1	ii	0 to 1
A.43.4.5	scope	c1	ii	
A.43.4.6	filter	c2	ii	
A.43.4.7	attributeIdList	o	mo	
A.43.4.7.1	attributeId	m	mm	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

Table A.44 - ROIV-m-Get (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.44.1	invokeID	m	mm	
A.44.2	linked-ID	x	xx	
A.44.3	operation-value	m	mm	3
A.44.4	GetArgument	m	mm	
A.44.4.1	baseManagedObjectClass	m	mm	
A.44.4.2	baseManagedObjectInstance	m	mm	
A.44.4.3	accessControl	m	mo	(1)
A.44.4.4	synchronization	c1	ii	0 to 1
A.44.4.5	scope	c1	ii	
A.44.4.6	filter	c2	ii	
A.44.4.7	attributeIdList	m	mo	
A.44.4.7.1	attributeId	m	mm	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

Table A.45 - ROIV-m-LinkedReply-Action (sending)

Out of the scope of profile AOM11

Table A.46 - ROIV-m-LinkedReply-Action (receiving)

Out of the scope of profile AOM11

Table A.47 - ROIV-m-LinkedReply-Delete (sending)

Out of the scope of profile AOM11

Table A.48 - ROIV-m-LinkedReply-Delete (receiving)

Out of the scope of profile AOM11

Table A.49 - ROIV-m-LinkedReply-Get (sending)

Out of the scope of profile AOM11

Table A.50 - ROIV-m-LinkedReply-Get (receiving)

Out of the scope of profile AOM11

Table A.51 - ROIV-m-LinkedReply-Set (sending)

Out of the scope of profile AOM11

Table A.52 - ROIV-m-LinkedReply-Set (receiving)

Out of the scope of profile AOM11

Table A.53 - ROIV-m-Set (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.53.1	invokeID	m	nm	
A.53.2	linked-ID	x	xx	
A.53.3	operation-value	m	nm	4
A.53.4	SetArgument	m	nm	
A.53.4.1	baseManagedObjectClass	m	nm	
A.53.4.2	baseManagedObjectInstance	m	nm	
A.53.4.3	accessControl	o	mo	(1)
A.53.4.4	synchronization	c1	ii	0 to 1
A.53.4.5	scope	c1	ii	
A.53.4.6	filter	c2	ii	
A.53.4.7	modificationList	m	nm	
A.53.4.7.1	modifyOperator	o	mo	0 to 3 Default:0 for replace
A.53.4.7.2	attributeId	m	nm	
A.53.4.7.3	attributeValue	m	mc(2)	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

- (2) Shall be present if modifyOperator parameter value is not "setDefault".

Table A.54 - ROIV-m-Set (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.54.1	invokeID	m	mm	
A.54.2	linked-ID	x	xx	
A.54.3	operation-value	m	mm	4
A.54.4	SetArgument	m	mm	
A.54.4.1	baseManagedObjectClass	m	mm	
A.54.4.2	baseManagedObjectInstance	m	mm	
A.54.4.3	accessControl	m	mo	(1)
A.54.4.4	synchronization	c1	ii	0 to 1
A.54.4.5	scope	c1	ii	
A.54.4.6	filter	c2	ii	
A.54.4.7	modificationList	m	mm	
A.54.4.7.1	modifyOperator	m	mo	0 to 3 Default:0 for replace
A.54.4.7.2	attributeId	m	mm	
A.54.4.7.3	attributeValue	m	mc(2)	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

- (2) Shall be present if modifyOperator parameter value is not "setToDefault".

Table A.55 - ROIV-m-Set-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.55.1	invokeID	m	mm	
A.55.2	linked-ID	x	xx	
A.55.3	operation-value	m	mm	5
A.55.4	SetArgument	m	mm	
A.55.4.1	baseManagedObjectClass	m	mm	
A.55.4.2	baseManagedObjectInstance	m	mm	
A.55.4.3	accessControl	o	mo	(1)
A.55.4.4	synchronization	c1	ii	0 to 1
A.55.4.5	scope	c1	ii	
A.55.4.6	filter	c2	ii	
A.55.4.7	modificationList	m	mm	
A.55.4.7.1	modifyOperator	o	mo	0 to 3 Default:0 for replace
A.55.4.7.2	attributeId	m	mm	
A.55.4.7.3	attributeValue	m	mc(2)	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present in a user request, the CMIP machine shall include it in the CMIP PDU sent. The CMIP machine does not interpret this parameter.

- (2) Shall be present if modifyOperator parameter value is not "setToDefault".

Table A.56 - ROIV-m-Set-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.56.1	invokeID	m	mm	
A.56.2	linked-ID	x	xx	
A.56.3	operation-value	m	mm	5
A.56.4	SetArgument	m	mm	
A.56.4.1	baseManagedObjectClass	m	mm	
A.56.4.2	baseManagedObjectInstance	m	mm	
A.56.4.3	accessControl	m	mo	(1)
A.56.4.4	synchronization	c1	ii	0 to 1
A.56.4.5	scope	c1	ii	
A.56.4.6	filter	c2	ii	
A.56.4.7	modificationList	m	mm	
A.56.4.7.1	modifyOperator	m	mo	0 to 3 Default:0 for replace
A.56.4.7.2	attributeId	m	mm	
A.56.4.7.3	attributeValue	m	mc(2)	

- (1) In order to parse or process this, there must be an agreement as to what abstract syntax will be used in the external.

If this parameter is present on a received CMIP PDU, the CMIP machine shall pass the parameter to the CMISE user. The CMIP machine does not interpret this parameter.

- (2) Shall be present if modifyOperator parameter value is not "setToDefault".

Table A.57 - RORS-m-Action-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.57.1	invokeID	m	mm	
A.57.2	operation-value	c16	mc16	7
A.57.3	ActionResult	o	mo	
A.57.3.1	managedObjectClass	o	oo	
A.57.3.2	managedObjectInstance	o	oo	
A.57.3.3	currentTime	o	mo	
A.57.3.4	ActionReply	o	mo	
A.57.3.4.1	actionType	m	mm	
A.57.3.4.2	actionReplyInfo	m	mm	

IECNORM.COM : Click to view the full PDF of ISO/IEC ISP 11183-3:1992

Table A.58 - RORS-m-Action-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.58.1	invokeID	m	mm	
A.58.2	operation-value	m	mc16	7
A.58.3	ActionResult	m	mo	
A.58.3.1	managedObjectClass	m	mo	
A.58.3.2	managedObjectInstance	m	mo	
A.58.3.3	currentTime	m	mo	
A.58.3.4	ActionReply	m	mo	
A.58.3.4.1	actionType	m	mm	
A.58.3.4.2	actionReplyInfo	m	mm	

Table A.59 - RORS-m-Cancel-Get (sending)

Out of the scope of profile AOM11

Table A.60 - RORS-m-Cancel-Get (receiving)

Out of the scope of profile AOM11

Table A.61 - RORS-m-Create (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.61.1	invokeID	m	mm	
A.61.2	operation-value	m	mc16	8
A.61.3	CreateResult	m	mo	
A.61.3.1	managedObjectClass	o	oo	
A.61.3.2	managedObjectInstance	m	mc(1)	
A.61.3.3	currentTime	o	mo	
A.61.3.4	attributeList	o	oo	
A.61.3.4.1	attributeId	m	mm	
A.61.3.4.2	attributeValue	m	mm	

- (1) ManagedObjectInstance shall be present if it is not supplied in the ROIV-m-Create PDU. An ASN.1 comment in CMIP standard reflects this requirement by reference to ISO/IEC 9595, 8.3.4.1.3.

Table A.62 - RORS-m-Create (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.62.1	invokeID	m	mm	
A.62.2	operation-value	m	mc16	8
A.62.3	CreateResult	m	mo	
A.62.3.1	managedObjectClass	m	mo	
A.62.3.2	managedObjectInstance	m	mc(1)	
A.62.3.3	currentTime	m	mo	
A.62.3.4	attributeList	m	mo	
A.62.3.4.1	attributeId	m	mm	
A.62.3.4.2	attributeValue	m	mm	

- (1) ManagedObjectInstance shall be present if it is not supplied in the ROIV-m-Create PDU. An ASN.1 comment in CMIP standard reflects this requirement by reference to ISO/IEC 9595, 8.3.4.1.3.

Table A.63 - RORS-m-Delete (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.63.1	invokeID	m	mm	
A.63.2	operation-value	c16	mc16	9
A.63.3	DeleteResult	o	mo	
A.63.3.1	managedObjectClass	o	oo	
A.63.3.2	managedObjectInstance	o	oo	
A.63.3.3	currentTime	o	mo	

Table A.64 - RORS-m-Delete (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.64.1	invokeID	m	mm	
A.64.2	operation-value	m	mc16	9
A.64.3	DeleteResult	m	mo	
A.64.3.1	managedObjectClass	m	mo	
A.64.3.2	managedObjectInstance	m	mo	
A.64.3.3	currentTime	m	mo	

Table A.65 - RORS-m-EventReport-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.65.1	invokeID	m	mm	
A.65.2	operation-value	c16	mc16	1
A.65.3	EventReportResult	o	mo	
A.65.3.1	managedObjectClass	o	oo	
A.65.3.2	managedObjectInstance	o	oo	
A.65.3.3	currentTime	o	mo	
A.65.3.4	EventReply	o	mo	
A.65.3.4.1	eventType	m	mm	
A.65.3.4.2	eventReplyInfo	o	mo	

Table A.66 - RORS-m-EventReport-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.66.1	invokeID	m	mm	
A.66.2	operation-value	m	mc16	1
A.66.3	EventReportResult	m	mo	
A.66.3.1	managedObjectClass	m	mo	
A.66.3.2	managedObjectInstance	m	mo	
A.66.3.3	currentTime	m	mo	
A.66.3.4	EventReply	m	mo	
A.66.3.4.1	eventType	m	mm	
A.66.3.4.2	eventReplyInfo	m	mo	

Table A.67 - RORS-m-Get (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.67.1	invokeID	m	mm	
A.67.2	operation-value	m	mc16	3
A.67.3	GetResult	m	mm(1)	
A.67.3.1	managedObjectClass	o	oo	
A.67.3.2	managedObjectInstance	o	oo	
A.67.3.3	currentTime	o	mo	
A.67.3.4	attributeList	m	mm(1)	
A.67.3.4.1	attributeId	m	mm	
A.67.3.4.2	attributeValue	m	mm	

- (1) The subclause 8.3.1.1.13 of CMIS requires that attributeList be present in a success confirmation. If an empty list is supplied in the attributeIdList parameter of ROIV-m-Get, (as distinct from no list), the attributeList parameter returned shall be empty. An ASN.1 comment in CMIP requires that Result be present in a single reply.

Table A.68 - RORS-m-Get (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.68.1	invokeID	m	mm	
A.68.2	operation-value	m	mc16	3
A.68.3	GetResult	m	mm(1)	
A.68.3.1	managedObjectClass	m	mo	
A.68.3.2	managedObjectInstance	m	mo	
A.68.3.3	currentTime	m	mo	
A.68.3.4	attributeList	m	mm(1)	
A.68.3.4.1	attributeId	m	mm	
A.68.3.4.2	attributeValue	m	mm	

- (1) The subclause 8.3.1.1.13 of CMIS requires that attributeList be present in a success confirmation. If an empty list is supplied in the attributeIdList parameter of ROIV-m-Get, (as distinct from no list), the attributeList parameter returned shall be empty. An ASN.1 comment in CMIP requires that Result be present in a single reply.

Table A.69 - RORS-m-Set-Confirmed (sending)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.69.1	invokeID	m	mm	
A.69.2	operation-value	c16	mc16	5
A.69.3	SetResult	o	mo	
A.69.3.1	managedObjectClass	o	oo	
A.69.3.2	managedObjectInstance	o	oo	
A.69.3.3	currentTime	o	mo	
A.69.3.4	attributeList	o	mo	
A.69.3.4.1	attributeId	m	mm	
A.69.3.4.2	attributeValue	m	mm	

Table A.70 - RORS-m-Set-Confirmed (receiving)

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.70.1	invokeID	m	mm	
A.70.2	operation-value	m	mc16	5
A.70.3	SetResult	m	mo	
A.70.3.1	managedObjectClass	m	mo	
A.70.3.2	managedObjectInstance	m	mo	
A.70.3.3	currentTime	m	mo	
A.70.3.4	attributeList	m	mo	
A.70.3.4.1	attributeId	m	mm	
A.70.3.4.2	attributeValue	m	mm	

Table A.71 - ROER-accessDenied (sending)

Valid return only for invoked operationValues: 3, 5, 7, 8, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.71.1	invokeID	m	mm	
A.71.2	error-value	m	mm	2

Table A.72 - ROER-accessDenied (receiving)

Valid return only for invoked operationValues: 3, 5, 7, 8, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.72.1	invokeID	m	mm	
A.72.2	error-value	m	mm	2

Table A.73 - ROER-classInstanceConflict (sending)

Valid return only for invoked operationValues: 3, 5, 7, 8, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.73.1	invokeID	m	mm	
A.73.2	error-value	m	mm	19
A.73.3	BaseManagedObjectId	m	mm	
A.73.3.1	baseManagedObjectClass	m	mm	
A.73.3.2	baseManagedObjectInstance	m	mm	

Table A.74 - ROER-classInstanceConflict (receiving)

Valid return only for invoked operationValues: 3, 5, 7, 8, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.74.1	invokeID	m	mm	
A.74.2	error-value	m	mm	19
A.74.3	BaseManagedObjectId	m	mm	
A.74.3.1	baseManagedObjectClass	m	mm	
A.74.3.2	baseManagedObjectInstance	m	mm	

Table A.75 - ROER-complexityLimitation (sending)

Valid return only for invoked operationValues: 3, 5, 7, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.75.1	invokeID	m	mm	
A.75.2	error-value	m	mm	20
A.75.3	ComplexityLimitation	o	ii	
A.75.3.1	scope	o	ii	
A.75.3.2	filter	o	ii	
A.75.3.3	sync	o	ii	0 to 1

Table A.76 - ROER-complexityLimitation (receiving)

Valid return only for invoked operationValues: 3, 5, 7, 9

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.76.1	invokeID	m	mm	
A.76.2	error-value	m	mm	20
A.76.3	ComplexityLimitation	m	mo	
A.76.3.1	scope	m	mo(1)	
A.76.3.2	filter	m	mo(1)	
A.76.3.3	sync	m	mo(1)	0 to 1

(1) The presence of these parameters is a protocol error.

Table A.77 - ROER-duplicateManagedObjectInstance (sending)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.77.1	invokeID	m	mm	
A.77.2	error-value	m	mm	11
A.77.3	ObjectInstance	m	mm	

Table A.78 - ROER-duplicateManagedObjectInstance (receiving)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.78.1	invokeID	m	mm	
A.78.2	error-value	m	mm	11
A.78.3	ObjectInstance	m	mm	

Table A.79 - ROER-getListError (sending)

Valid return only for invoked operationValues: 3

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.79.1	invokeID	m	mm	
A.79.2	error-value	m	mm	7
A.79.3	GetListError	m	mm	
A.79.3.1	managedObjectClass	o	oo	
A.79.3.2	managedObjectInstance	o	oo	
A.79.3.3	currentTime	o	mo	
A.79.3.4	getInfoList	m	mm	
A.79.3.4.1	AttributeIdError	m	mc17	
A.79.3.4.1.1	errorStatus	m	mm	2,5
A.79.3.4.1.2	attributeId	m	mm	
A.79.3.4.2	Attribute	m	mc17	
A.79.3.4.2.1	attributeId	m	mm	
A.79.3.4.2.2	attributeValue	m	mm	

Table A.80 - ROER-getListError (receiving)

Valid return only for invoked operationValues: 3

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.80.1	invokeID	m	nm	
A.80.2	error-value	m	nm	7
A.80.3	GetListError	m	nm	
A.80.3.1	managedObjectClass	m	mo	
A.80.3.2	managedObjectInstance	m	mo	
A.80.3.3	currentTime	m	mo	
A.80.3.4	getInfoList	m	nm	
A.80.3.4.1	AttributeIdError	m	mc17	
A.80.3.4.1.1	errorStatus	m	nm	2,5
A.80.3.4.1.2	attributeId	m	nm	
A.80.3.4.2	Attribute	m	mc17	
A.80.3.4.2.1	attributeId	m	nm	
A.80.3.4.2.2	attributeValue	m	nm	

Table A.81 - ROER-invalidArgumentValue (sending)

Valid return only for invoked operationValues: 1, 7

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.81.1	invokeID	m	nm	
A.81.2	error-value	m	nm	15
A.81.3	InvalidArgumentValue	m	nm	
A.81.3.1	actionValue	m	mc17	
A.81.3.1.1	actionType	m	nm	
A.81.3.1.2	actionInfoArg	o	mo	
A.81.3.2	eventValue	m	mc17	
A.81.3.2.1	eventType	m	nm	
A.81.3.2.2	eventInfo	o	mo	

Table A.82 - ROER-invalidArgumentValue (receiving)

Valid return only for invoked operationValues: 1, 7

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.82.1	invokeID	m	nm	
A.82.2	error-value	m	nm	15
A.82.3	InvalidArgumentValue	m	nm	
A.82.3.1	actionValue	m	mc17	
A.82.3.1.1	actionType	m	nm	
A.82.3.1.2	actionInfoArg	m	mo	
A.82.3.2	eventValue	m	mc17	
A.82.3.2.1	eventType	m	nm	
A.82.3.2.2	eventInfo	m	mo	

Table A.83 - ROER-invalidAttributeValue (sending)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.83.1	invokeID	m	mm	
A.83.2	error-value	m	mm	6
A.83.3	Attribute	m	mm	
A.83.3.1	attributeId	m	mm	
A.83.3.2	attributeValue	m	mm	

Table A.84 - ROER-invalidAttributeValue (receiving)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.84.1	invokeID	m	mm	
A.84.2	error-value	m	mm	6
A.84.3	Attribute	m	mm	
A.84.3.1	attributeId	m	mm	
A.84.3.2	attributeValue	m	mm	

Table A.85 - ROER-invalidFilter (sending)

Out of the scope of profile AOM11

Table A.86 - ROER-invalidFilter (receiving)

Out of the scope of profile AOM11

Table A.87 - ROER-invalidObjectInstance (sending)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.87.1	invokeID	m	mm	
A.87.2	error-value	m	mm	17
A.87.3	ObjectInstance	m	mm	

Table A.88 - ROER-invalidObjectInstance (receiving)

Valid return only for invoked operationValues: 8

Index	Parameter name	Base Std.	Profile	Type, value(s) & range(s)
A.88.1	invokeID	m	mm	
A.88.2	error-value	m	mm	17
A.88.3	ObjectInstance	m	mm	

Table A.89 - ROER-invalidScope (sending)

Out of the scope of profile AOM11

Table A.90 - ROER-invalidScope (receiving)

Out of the scope of profile AOM11