# INTERNATIONAL STANDARD

ISO 17573-3

First edition 2023-08

# Electronic fee collection System architecture for vehicle related tolling —

Part 3:

Data dictionary

Perception de télépéage — Architecture de systèmes pour le péage lié aux véhicules —

Partie 3: Dictionnaire de données

Citck to vier de données

TANDARDSISO.



STANDARDSISO.COM. Click to view the full Political STANDARDSISO.COM.



# COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Co	ntents				Page
For	eword				vi
Intr	oduction				vii
1	Scope				1
2	_		eferences		
3			efinitions		
4	Abbre	viated	terms		4
5	EFC co	mmor	data object definitions al	ည်	5
	5.1	Gener	al		5
	O. <b>_</b>		pes of simple data types		6
		5.2.1	AccountStatus	<b>A</b> , 9	6
		5.2.2	ActualNumberOfPassengers		6
		5.2.3	Altitude		6
		5.2.4 5.2.5	Axles CabType ChassisType Co2EmissionClass Co2EmissionValue Co2EmissionValue Co2EmissionValue Co2EmissionValue		/
		5.2.5 5.2.6	ChassisType		/ 7
		5.2.7	Co2EmissionClass	. 0	
		= 0 0	Co2EmissionValue		 0
		5.2.0 5.2.9	Co2EmissionValue Co2EmissionValueLoad Co2Scheme ContractAuthenticator ContractSerialNumber CopValue CountryCode DetectionMode		q
	•	5.2.7	Co2Scheme		رq
		5.2.10	ContractAuthenticator		9
		5.2.12	ContractSerialNumber		9
		5.2.13	ConValue		10
		5.2.14	CountryCode		10
		5.2.15	DetectionMode		10
		5.2.16	EmissionUnit		11
			EngineCharacteristics		
			EquipmentIccId		
			EquipmentObuId		
		5.2.20	Equipment Status		14
		5.2.21	EuroValue		14
		5.2.22	DistanceUnit		14
		_	Issuerldentifier		_
			Latitude		
			LocalVehicleClassId		
			LocationClassId		
			Longitude		
			PaymentSecurityData		
			PayUnit		
	<b>V</b>		Personal Account Number		
			RearWheelsSteeringType		
			ReceiptAuthenticator ReceiptDistance		
			ResultFin		
			ReceiptIccId		
			ReceiptObuId		
			ResultOp		
			ReceiptServiceSerialNumber		
			ReceiptText		
			StationType		
			SuspensionType		
			TariffClassId		
			Time		22

# ISO 17573-3:2023(E)

	5.2.44	TimeClassId	22
		TimeUnit	
		TrailerType	
		TyreConfiguration	
		UserClassId	
		VehicleAuthenticator	
		VehicleClass	
		VehicleCurrentMaxTrainWeight	
		VehicleTechnicalPermissibleMaxLadenMass	
		VehicleTotalDistance	
		VehicleUsageCategoryType	
		VehicleWeightLaden	
	5.2.56	WeekDay	<u>/</u> 26
5.3	Single	level data types	26
	5.3.1	AbsolutePosition2d AbsolutePosition3d	26
	5.3.2	AbsolutePosition3d	27
	5.3.3	AxleWeightLimit	27
	5.3.4	AxleWeightLimits	27
	5.3.5	DateCompact	28
	5.3.6	DieselEmissionValues	28
	5.3.7	DriverCharacteristics	20 28
	5.3.8	DriverCharacteristics Distance	20
	5.5.0 E 2.0	Duration	20 20
	5.5.9 F 2.10	Duration Dataila	29 20
	5.3.10	EngineDetails	29
	5.3.11	Duration EngineDetails EuVehicleGroup	29
	5.3.12	ExhaustEmissionValues FutureCharacteristics NumberOfAxles Obeld	29
	5.3.13	FutureCharacteristics	30
	5.3.14	NumberOtAxles	30
	5.3.15	Obeld	31
	5.3.16	Particulate PassengerCapacity PaymentFee Period	31
	5.3.17	Passenger Capacity	31
	5.3.18	PaymentFee	31
	5.3.19	Period	32
	5.3.20	Provider	32
	5.3.21	RelativePosition3d	32
		SessionClass	
		SessionLocation	
	5.3.24	SignedValue	33
		SoundLevel	
		TariffClassDescription	
		TimeCompact	
		TrailerDetails	
		Wheels Configuration	
5.4		vel data types	
5.4	5.4.1	AxlesWeightLimits	
	5.4.2	ChargeObjectId	
	5.4.3	ContractValidity	
	5.4.4	DateAndTime	
	5.4.5	EnvironmentalCharacteristics	
	5.4.6	InitialVehicleRegistrationDate	
	5.4.7	Lpn	36
	5.4.8	PaymentMeans	
	5.4.9	PaymentMeansBalance	
	5.4.10	Point	
	5.4.11	PurseBalance	38
	5.4.12	TrailerCharacteristics	38
	5.4.13	ValidityOfContract	
		VehicleAxlesNumber	

5.5	5.4.15 VehicleDimensions 5.4.16 VehicleIdentificationNumber 5.4.17 VehicleWeightLimits Three-level data types 5.5.1 EfcContextMark 5.5.2 ReceiptContract 5.5.3 ReceiptData 5.5.4 ReceiptFinancialPart 5.5.5 ReceiptServicePart 5.5.6 UserId		39 40 40 41 42
5.6	5.5.7 VehicleAxles 5.5.8 VehicleSpecificCharacteristics Complex data types 5.6.1 AggregatedSingleTariffClassSession 5.6.2 DetectedChargeObject 5.6.3 VehicleDescription	4 4 3 4 4 4	13 14 14 15 16
Annex A (no	ormative) <b>EFC common data type definitions</b>	4	7
STAN	ormative) EFC common data type definitions hy		
S`			

# **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <a href="www.iso.org/patents">www.iso.org/patents</a>. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 278, *Intelligent transport systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This first edition cancels and replaces the first edition (ISO/TS 17573-3:2021), which has been technically revised.

The main changes are as follows:

- CO<sub>2</sub> emission class data types have been added to underpin the revised Directive 1999/62/EC<sup>[15]</sup> (i.e. Eurovignette directive regarding the charging of vehicles for the use of certain infrastructure), updated by Directive (EU) 2022/362;<sup>[21]</sup>
- a second level of version identifier (i.e. minor version) of the abstract syntax notation one (ASN.1) module has been added to provide enhanced support to standards that import data types from this document.

A list of all parts in the ISO 17573 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

# Introduction

This document is a part of the ISO 17573 series which defines the system architecture for vehiclerelated tolling. ISO 17573-1 gives a reference model for the system architecture. ISO/TS 17573-2 provides a collection of terms and definitions within the field of electronic fee collection (EFC) and road user charging that are used in the different documents published in ISO and CEN under the general title, *Electronic fee collection.* 

This document (ISO 17573-3) provides a data dictionary that contains the definitions of ASN.1 (data) types and the associated semantics.

The document is intended to be used as a reference by editors of ISO and CEN documents in EFC and in related areas of standardization (such as Intelligent transport systems, ITS).

STANDARDS 50. COM. Click to view the full Polit of 180 Click to view the 180 Click to view the full Polit of 180 Click to view the full Po It is foreseen that the library of ASN.1 (data) types contained in this document will be augmented with additional definitions as these become available.

vii

STANDARDS SO. COM. Click to View the full PDF of ISO 17673-3:2023

# Electronic fee collection — System architecture for vehicle-related tolling —

# Part 3:

# **Data dictionary**

# 1 Scope

This document specifies the syntax and semantics of data objects in the field of electronic fee collection (EFC). The definitions of data types and assignment of semantics are provided in accordance with the abstract syntax notation one (ASN.1) technique, as specified in ISO/IEC 8824 1. This document defines:

- ASN.1 (data) types within the fields of EFC;
- ASN.1 (data) types of a more general use that are used more specifically in standards related to EFC.

This document does not seek to define ASN.1 (data) types that are primarily related to other fields that operate in conjunction with EFC, such as cooperative intelligent transport systems (C-ITS), the financial sector, etc.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 17573-2, Electronic fee collection — System architecture for vehicle related tolling — Part 2: Vocabulary

ISO 612, Road vehicles — Dimensions of motor vehicles and towed vehicles — Terms and definitions

ISO 3166-1, Codes for the representation of names of countries and their subdivisions — Part 1: Country code

ISO 1176, Road vehicles — Masses — Vocabulary and codes

ISO 4217, Codes for the representation of currencies

ISO/IEC 7812-1, Identification cards — Identification of issuers — Part 1: Numbering system

ISO/IEC 7812-2, Identification cards — Identification of issuers — Part 2: Application and registration procedures

ISO/IEC 8824-1, Information technology — Abstract Syntax Notation One (ASN.1) — Part 1: Specification of basic notation

 ${\tt ISO/IEC~8859-1}$ , Information technology — 8-bit single-byte coded graphic character sets — Part 1: Latin alphabet No. 1

 ${\tt ISO/IEC~8859-2}$ , Information technology — 8-bit single-byte coded graphic character sets — Part 2: Latin alphabet No. 2

ISO/IEC 8859-3, Information technology — 8-bit single-byte coded graphic character sets — Part 3: Latin alphabet No. 3

# ISO 17573-3:2023(E)

ISO/IEC 8859-4, Information technology — 8-bit single-byte coded graphic character sets — Part 4: Latin alphabet No. 4

ISO/IEC 8859-5, Information technology — 8-bit single-byte coded graphic character sets — Part 5: Latin/Cyrillic alphabet

ISO/IEC 8859-6, Information technology — 8-bit single-byte coded graphic character sets — Part 6: Latin/Arabic alphabet

ISO/IEC 8859-7, Information technology — 8-bit single-byte coded graphic character sets — Part 7: Latin/Greek alphabet

ISO/IEC 8859-8, Information technology — 8-bit single-byte coded graphic character sets — Part & Latin/Hebrew alphabet

ISO/IEC 8859-9, Information technology — 8-bit single-byte coded graphic character sets — Part 9: Latin alphabet No. 5

ISO/IEC 8859-10, Information technology — 8-bit single-byte coded graphic character sets — Part 10: Latin alphabet No. 6

# 3 Terms and definitions

For the purposes of this document, the terms and definitions given in 180/TS 17573-2 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>

### 3.1

### **BITSTRING**

<type> simple type (3.14) whose distinguished values are an ordered sequence of zero, one or more bits

[SOURCE: ISO/IEC 8824-1:2021, 3.87] modified — Term modified from "BITSTRING type" to "BITSTRING" and domain "<type>" added.]

### 3.2

# **CHOICE**

<type> type defined by referencing a list of distinct types; each value of the choice type is derived from the value of one of the *component types* (3.4)

Note 1 to entry: Each value of the choice type is derived from the value of one of the component types.

[SOURCE: ISO/NEC 8824-1:2021, 3.8.14, modified — Term modified from "CHOICE type" to "CHOICE" and domain "Type>" added. Note 1 to entry also added.]

### 3.3

### complex data type

one type that has more than three levels (3.17)

### 3.4

### component type

one of the types referenced when defining a CHOICE (3.2), SET (3.12), SEQUENCE (3.10), SET OF (3.13), or SEQUENCE OF (3.11)

[SOURCE: ISO/IEC 8824-1:2021, 3.8.15]

### 3.5

# data type

categorization of an abstract set of possible values, characteristics, and set of operations for an attribute

[SOURCE: ISO/IEC 25012:2008, 4.7 — modified, NOTE removed.]

### 3.6

### INTEGER

<type> simple type (3.14) with distinguished values which are the positive and negative whole numbers, including zero (as a single value)

[SOURCE: ISO/IEC 8824-1:2021, 3.8.48, modified — Term modified from "INTEGER type" to "INTEGER" and domain "<type>" added.]

### 3.7

### object

well-defined piece of information, definition or specification which requires a name in order to identify its use in an instance of communication

[SOURCE: ISO/IEC 8824-1:2021, 3.8.52]

### 3.8

### **OCTET STRING**

<type> simple type (3.14) whose distinguished values are an ordered sequence of zero, one or more octets, each octet being an ordered sequence of eight bits

[SOURCE: ISO/IEC 8824-1:2021, 3.8.55, modified — Term modified from "OCTET STRING type" to "OCTET STRING" and domain "<type>" added.]

### 3.9

### parent type

type that is being constrained when defining a *subtype* (3.16), and which governs the subtype notation

[SOURCE: ISO/IEC 8824-1:2021, 3.8.58, modified — Term modified from "parent type (of a subtype)" to "parent type".]

### 3.10

# **SEQUENCE**

<type> type defined by referencing a fixed, ordered list of types (some of which can be declared to be optional)

Note 1 to entry: Each value of the SEQUENCE type is an ordered list of values, one from each component type (3.4).

[SOURCE: ISO/IEC 8824-1:2021, 3.8.67, modified — Term modified from "SEQUENCE types" to "SEQUENCE" and domain "<type>" added. Second part of original definition moved to Note 1 to entry.]

# 3.11

# **SEQUENCE-OF**

<type> type defined by referencing a single component type (3.4)

Note 1 to entry: Each value in the SEQUENCE-OF type is an ordered list of zero, one or more values of the component type.

[SOURCE: ISO/IEC 8824-1:2021, 3.8.68, modified — Term modified from "SEQUENCE-OF types" to "SEQUENCE" and domain "<type>" added. Second part of original definition moved to Note 1 to entry.]

### 3.12

### **SET**

<type> type defined by referencing a fixed, unordered, list of types (some of which may be declared to be optional)

Note 1 to entry: Each value in the SET type is an unordered list of values, one from each *component type* (3.4).

# ISO 17573-3:2023(E)

Note 2 to entry: Where a component type is declared to be optional, a value of the SET type need not contain a value of that component type.

[SOURCE: ISO/IEC 8824-1:2021, 3.8.72, modified — Term modified from "SET types" to "SET" and domain "<type>" added. Second part of original definition moved to Note 1 to entry. Note 1 to entry updated as Note 2 to entry.]

### 3.13

### **SET-OF**

<type> types defined by referencing a single component type (3.4)

Note 1 to entry: Each value in the SET-OF type is an unordered list of zero, one or more values of the component type.

[SOURCE: ISO/IEC 8824-1:2021, 3.8.73, modified — Term modified from "SET-OF types" to SET-OF" and domain "<type>" added. Second part of original definition moved to Note 1 to entry.]

### 3.14

### simple type

type defined by directly specifying the set of their values

[SOURCE: ISO/IEC 8824-1:2021, 3.8.74]

### 3.15

### single-level data type

data type (3.5) which is a SEQUENCE (3.10), or SEQUENCE OF (3.11) defined by referencing a simple type (3.14) or a subtype (3.16) of a simple type

### 3.16

### subtype

<parent type> type whose values are a subset (or the complete set) of the values of some other type
(the parent type) (3.9)

[SOURCE: ISO/IEC 8824-1:2021, 3.8.76, modified — Term modified from "subtype (of a parent type)" to "subtype" and domain "parent type>" added.]

### 3.17

### three-level data type

data type (3.5) which is a CHOICE (3.2), SEQUENCE (3.10), or SEQUENCE OF (3.11) defined by referencing a two-level data type (3.18)

# 3.18

# two-level data type

data type (3.5) which is a CHOICE (3.2), SEQUENCE (3.10), or SEQUENCE OF (3.11) defined by referencing a single-level data type (3.15)

# 4 Abbreviated terms

ASN.1 abstract syntax notation one

BCD binary coded decimal

CO carbon monoxide

CO<sub>2</sub> carbon dioxide

DSRC dedicated short-range communication

EFC electronic fee collection

GLONASS global navigation satellite system of the Russian Federation

**GNSS** global navigation satellite system

**GPS** global positioning system

GTRF global terrestrial reference system

hydrocarbon HC

ICC integrated circuit(s) card

**ITRF** international terrestrial reference frame

Jickto view the full PDF of 150 17573.2023
Jickto view the full PDF of 150 17573.2023 **ITRS** international terrestrial reference system

IGS Japan satellite navigation geodetic system

LAC localization augmentation communication

 $NO_{\rm x}$ nitrogen oxides

on-board equipment OBE

OBU on-board unit

**QZSS** quasi-zenith satellite system

**RSE** roadside equipment

**TSP** toll service provider

VAT value-added tax

# **EFC** common data object definitions

# 5.1 General

In this clause, the structure of all EFC common data objects is described. The formal definition provided in Annex A in terms of data type definitions applies. In addition to the structure description, each data object is also given a semantics.

Each one of the common data types defined herein is used by more than one document in the suite of CEN or ISO documents in the field of EFC. These documents may also define their own data types when no one of the common data types defined herein satisfies their need.

The definitions of the EFC common data types are ordered according to their data type level:

- first subtypes based on simple data types (e.g. INTEGER or OCTET STRING),
- then two-level data types,
- then three-level data types,
- then complex data types.

Data types are ordered alphabetically within each level.

# 5.2 Subtypes of simple data types

### 5.2.1 AccountStatus

The data type  ${\tt AccountStatus}$  shall be of the simple type as specified in  ${\tt \underline{Table \ 1}}.$ 

Table 1 — AccountStatus

Subtype	Parent type	Semantics
-	INTEGER	AccountStatus provides the status of the user's account. The following semantics are assigned:
		<ul> <li>ok: The amount stored in the account is above or equal to the predefined threshold;</li> </ul>
		<ul> <li>low: The amount stored in the account has fallen below a predefined threshold;</li> </ul>
		<ul> <li>empty: The amount stored in the account is zero;</li> </ul>
		<ul> <li>negative: The amount stored in the account has fallen below zero.</li> </ul>

# 5.2.2 ActualNumberOfPassengers

The data type ActualNumberOfPassengers shall be of the subtype as specified in <a href="Table 2">Table 2</a>.

Table 2 — ActualNumber Of Passengers

Subtype	Parent type	Semantics
Int1Unsigned		Actual Number Of Passengers represents the actual number of passengers (i.e. persons) present in the vehicle, including the driver.  This information can affect the applicability of tolls or the value of the tariff to be applied, e.g. in High Occupancy Tolling or High Occupancy Vehicle lanes.

# 5.2.3 Altitude

The data type  $\tt Altitude$  shall be of the simple type as specified in  $\tt Table\ 3$ .

Table 3 — Altitude

Subtype	Parent type	Semantics
Int2Signed		Altitude provides the ellipsoidal height (in units of 0,25 m) above or below the WGS84 <sup>[5]</sup> ellipsoid of the geographical point. The range in m is from -8 192,00 to +8 191,75.
		NOTE WGS84 <sup>[10]</sup> represents a broadly adopted global geodetic reference system for the Earth for practical applications of mapping, geo-positioning and navigation. Other terrestrial reference frames exist, notably the International Terrestrial Reference Frame (ITRF, the latest edition currently being ITRF 2020). It is possible to convert between the most commonly used terrestrial reference frames and the differences between them are typically in the order of centimetres. The international terrestrial reference frame is becoming increasingly recognized and used as the primary feference frame. All recent and up-to-date Global Navigation Satellite System (GNS-S)-specific terrestrial reference frames (WGS 84 for GPS, PZ-90 for GLONASS, the GTRF for Galileo, CGCS2000 for BeiDou, and the JGS for QZSS) are aligned to a primary ITRS <sup>[11]</sup> realization, according to ISO 19161-1:2020, Annex C.

# **5.2.4** Axles

The data type Axles shall be of the simple type as specified in Table 4.

Table 4 🚜xles

Subtype	Parent type	Semantics
-	INTEGER	Axles provides the number of axles of either the tractor or
	×	trailer including drop axles.

# 5.2.5 CabType

The data type CabType shall be of the simple constrained type as specified in <u>Table 5</u>.

Table 5 — CabType

Subtype	Parent type	Semantics
- 205	INTEGER	CabType provides information about the cabin type of a vehicle according to Regulation (EU) 2019/1242, [18] Annex I.
ANDA		The following semantics are assigned:  — dayCab: A type of cabin that is not a sleeper cabin;
5		— sleeperCab: A type of cabin that has a compartment behind the driver's seat intended to be used for sleeping as reported in accordance with Regulation (EU) 2018/956, [20] Annex I, Part B, Data no. 84.

# 5.2.6 ChassisType

The data type  $\mathtt{ChassisType}$  shall be of the simple constrained type as specified in <u>Table 6</u>.

Table 6 — ChassisType

Subtype	Parent type	Semantics
-	INTEGER	ChassisType provides information about the type of chassis of a vehicle according to Regulation (EU) 2019/1242 and Regulation (EU) 2018/858.
		The following semantics are assigned:
		— rigidLorry: A type of chassis, that is not designed or constructed for the towing of a semitrailer, as defined in Regulation (EU) 2019/1242,[18] Article 3 (6);
		— tractor: A type of chassis, that is designed and constructed exclusively or principally to tow semitrailers, as defined in Regulation (EU) 2019/1242,[18] Article 3 (7);
		<ul> <li>van: A lorry with the compartment where the driver is located and cargo area within a single unit, as defined in Regulation (EU) 2018/858,[19] Annex 1, Part C, 4.2.</li> </ul>

### 5.2.7 Co2EmissionClass

The data type Co2EmissionClass shall be of the simple type as specified in Table 7.

Table 7 — Co2EmissionClass

Subtype	Parent type	Semantics
-	INTEGER	Co2EmissionClass indicates the ${\rm CO_2}$ emission class according to the selected ${\rm CO_2}$ scheme.
		The following semantics are assigned:
		<ul> <li>noEntry: No CO<sub>2</sub> emission class assigned;</li> </ul>
		cco2EmissionClass1: CO <sub>2</sub> emission class 1;
		co2EmissionClass2: CO <sub>2</sub> emission class 2;
	COW	— co2EmissionClass3: CO <sub>2</sub> emission class 3;
	60.	— co2EmissionClass4: CO <sub>2</sub> emission class 4;
	35	— co2EmissionClass5: CO <sub>2</sub> emission class 5;
	20	— co2EmissionClass6: CO <sub>2</sub> emission class 6;
		— co2EmissionClass7: CO <sub>2</sub> emission class 7.

EXAMPLE The values of Co2EmissionClass for heavy-duty vehicles have the meaning as specified in Directive 1999/62/EC,[15] Article 7ga when the Co2Scheme is set to eU:

- co2EmissionClass1, indicating the  $\rm CO_2$  emission class 1 (vehicles that do not belong to any of the other  $\rm CO_2$  emission classes);
- co2EmissionClass2, indicating the  $\rm CO_2$  emission class 2 (vehicles with  $\rm CO_2$  emissions more than 5 % below the emission reduction trajectory);
- co2EmissionClass3, indicating the  $CO_2$  emission class 3 (vehicles with  $CO_2$  emissions more than 8 % below the emission reduction trajectory);
- co2EmissionClass4, indicating the CO $_2$  emission class 4 (low-emission heavy-duty vehicles);
- co2EmissionClass5, indicating the  $CO_2$  emission class 5 (zero emission vehicles).

### 5.2.8 Co2EmissionValue

The data type Co2EmissionValue shall be of the subtype as specified in <a href="Table 8">Table 8</a>.

Table 8 — Co2EmissionValue

Subtype	Parent type	Semantics
Int2Unsigned		$\label{locality} {\tt Co2EmissionValue} \ represents \ the \ vehicle's \ CO_2 \ emission \ value \ according \ to \ vehicle \ registration \ documents, in \ g/km.$

# 5.2.9 Co2EmissionValueLoad

The data type  ${\tt Co2EmissionValueLoad}$  shall be of the subtype as specified in <u>Table 9</u>.

Table 9 — Co2EmissionValueLoad

Subtype	Parent type	Semantics
Int2Unsigned		Co2EmissionValueLoad represents the vehicle's $\rm CO_2$ emission value according to vehicle registration documents, in 0,01 g/tkm steps. EXAMPLE: A value of 10 000 represents a $\rm CO_2$ emission of 100 g/tkm.

# **5.2.10 Co2Scheme**

The data type Co2Scheme shall be of the simple type as specified in Table 10.

Table 100— Co2Scheme

Subtype	Parent type	Semantics
-	INTEGER	Co2Scheme indicates the ${\rm CO_2}$ emission class scheme applied to the values defined in Co2EmissionClass.
		The following semantics are assigned:
	cOp.	— noEntry: No CO <sub>2</sub> scheme applied;
S	0.	<ul> <li>eu: CO<sub>2</sub> scheme according to Directive 1999/62/EC<sup>[15]</sup>, Article 7ga for heavy-duty vehicles and Article 7gb for light- duty vehicles.</li> </ul>

# 5.2.11 ContractAuthenticator

The data type ContractAuthenticator shall be of the simple type as specified in Table 11.

Table 11 — ContractAuthenticator

Subtype	Parent type	Semantics
-		ContractAuthenticator is an authenticator calculated by the toll service provider (TSP) when issuing the contract, to prevent tampering with contract data.

### 5.2.12 ContractSerialNumber

The data type ContractSerialNumber shall be of the subtype as specified in <a href="Table 12">Table 12</a>.

Table 12 — ContractSerialNumber

Subtype	Parent type	Semantics
Int4Unsigned		ContractSerialNumber is an integer designating the individual contract, assigned at the discretion of the TSP.

# 5.2.13 CopValue

The data type CopValue shall be of the simple type as specified in <a href="Table 13">Table 13</a>.

Table 13 — CopValue

Subtype	Parent type	Semantics
-	INTEGER	CopValue represents the vehicle's carbon dioxide pollution values expressed in g/km. The following semantics are assigned:
		— noEntry: Value not defined;
		— co2Class1: For pollution values below 101 g/km;
		— co2Class2: For pollution value from 101 g/km to 120 g/km;
		— co2Class3: For pollution values from 121 g/km to 140 g/km;
		— co2Class4: For pollution values from 141 g/km to 160 g/km;
		— co2Class 5: For pollution values from 161 g/km to 200 g/km;
		— cocclass6: For pollution values from 201 g/km to 250 g/km;
		co2Class7: For pollution values above 250 g/km.

NOTE The carbon dioxide pollution value of a vehicle is stated in field V.7 in European Vehicle Registration Documents according to Directive 2003/127/EC.[16]

# 5.2.14 CountryCode

The data type CountryCode shall be of the simple type as specified in Table 14.

Table 14 — CountryCode

	Subtype	Parent type	Semantics
-	5		CountryCode represents a ISO 3166-1 country code. Values are encoded in accordance with the ITA-2 encoding of the ISO 3166-1 country code.
			EXAMPLE 1 Austria (AT) = 11000 00001.
			EXAMPLE 2 Belgium (BE) = 10011 10000.

# 5.2.15 DetectionMode

The data type DetectionMode shall be of the simple type as specified in Table 15.

Table 15 — DetectionMode

Subtype	Parent type	Semantics
-	INTEGER	DetectionMode indicates how the charge object was detected. The following semantics are assigned:
		<ul> <li>measured: The charge object was detected by evaluation of positioning data using regular rules defined for recognizing charge objects;</li> </ul>
		<ul> <li>inferred: The charge object was not detected by evaluation of positioning data, but was inferred from the overall trip logic;</li> </ul>
		<ul> <li>lac: For implementation reasons in special cases, the normal charge object detection technology could be supported by localization augmentation communication (LAC) beacon, which communicates its location, usually using short-range communication technology.</li> </ul>

### 5.2.16 EmissionUnit

The data type EmissionUnit shall be of the simple constrained type as specified in Table 16.

Table 16 — Emission Unit

Subtype	Parent type	Semantics
-	INTEGER	EmissionUnit represents the unit of emission values as an integer on one octet. The following semantics are assigned:  — emission unit represents the unit of emission values are assigned:  — emission unit represents the unit of emission values are assigned:  — emission unit represents the unit of emission values are assigned:  — emission unit represents the unit of emission values as an integer of one octet. The following semantics are assigned:  — emission unit represents the unit of emission values as an integer of one octet. The following semantics are assigned:  — emission unit represents the unit of emission values as an integer of one octet. The following semantics are assigned:  — emission unit represents the unit of emission values are expressed in milligrams per kilometre,
	, K	1: mg/kWh, indicating the emission values are expressed in milligrams per Kilowatt-hour.

# 5.2.17 EngineCharacteristics

The data type EngineCharacteristics shall be of the simple type as specified in Table 17.

Table 17 — EngineCharacteristics

	Subtype	Parent type	Semantics
-		INTEGER	EngineCharacteristics provides information about the vehi-
	$\mathcal{O}_{k}$		cle's engine type and fuel characteristics.

The following semantics have been assigned:

- noEntry, indicating that no information is available;
- noEngine, indicating that the vehicle has no engine;
- petrolUnleaded, indicating engine operating with unleaded petrol;
- petrolLeaded, indicating engine operating with leaded petrol;
- diesel, indicating engine operating with diesel;
- lpg, indicating engine operating with liquefied petroleum gas;
- battery, indicating vehicle powered exclusively by battery;
- solar, indicating engine operating with solar energy;

# ISO 17573-3:2023(E)

- hybrid, value kept for legacy compatibility (more differentiated values are available);
- hydrogen, indicating engine operating with hydrogen;
- multiFuel, indicating multi fuel engine;
- bivalentPetrolLpg, indicating bivalent operating engine with petrol or liquefied petroleum gas;
- bivalentPetrolong, indicating bivalent operating engine with petrol or compressed natural gas;
- combinedPetrolElectric, indicating combined operation with petrol and electric engine;
- cng, indicating engine operating with compressed natural gas;
- lng, indicating engine operating with liquefied natural gas;
- combinedDieselElectric, indicating combined operation of diesel and electric engine;
- combinedHydrogenElectric, indicating combined operation of hydrogen and electric engine;
- bivalentHydrogenPetrol, indicating bivalent operating engine with hydrogen or petrol;
- bivalentHydrogenPetrolElectricEngine, indicating bivalent operating engine with hydrogen or petrol combined with electric engine;
- fuelCellHydrogen, indicating fuel cell with hydrogen as primary energy source and electric engine;
- fuelCellPetrol, indicating fuel cell with petrol as primary energy source and electric engine;
- fuelCellMethanol, indicating fuel cell with methanol asprimary energy source and electric engine;
- fuelCellEthanol, indicating fuel cell with ethanol as primary energy source and electric engine;
- fuelCellDiesel, indicating fuel cell with diesel as primary energy source and electric engine;
- combinedMultiFuelElectricEngine, indicating combined operation of multifuel and electric engine;
- combinedCngElectricEngine, indicating combined operation with compressed natural gas and electric engine;
- combinedLngElectricEngine, indicating combined operation with liquefied natural gas and electric engine;
- petrolEthanol, indicating fuel mix of petrol and mainly ethanol, e.g. E85;
- combinedLpgElectricEngine, indicating combined operation of liquefied petroleum gas and electric engine;
- hybridPetrolExternalBattery, indicating hybrid drive with petrol and external rechargeable battery (plug-in hybrid);
- hybridDieselExternalBattery, indicating hybrid drive with diesel and external rechargeable battery (plug-in hybrid);
- hybridLpgExternalBattery, indicating hybrid drive with liquefied petroleum gas and external rechargeable battery (plug-in hybrid);
- hybridHydrogenExternalBattery, indicating hybrid drive with hydrogen and external rechargeable battery (plug-in hybrid);
- hybridMultiFuelExternalBattery, indicating hybrid drive with multifuel and external rechargeable battery (plug-in hybrid);

- hybridCngExternalBattery, indicating hybrid drive with compressed natural gas and external rechargeable battery (plug-in hybrid);
- hybridLngExternalBattery, indicating hybrid drive with liquefied natural gas and external rechargeable battery (plug-in hybrid);
- hybridBivalentHydrogenPetrolExternalBattery, indicating hybrid drive with bivalent operating hydrogen and petrol engine and external rechargeable battery (plug-in hybrid);
- hydrogenchg, indicating a fuel mix of hydrogen and compressed natural gas;
- hydrogenlng, indicating a fuel mix of hydrogen and liquefied natural gas;
- hybridHydrogenCngExternalBattery, indicating hybrid drive with hydrogen and compressed natural gas and external chargeable battery (plug-in hybrid);
- hybridHydrogenLngExternalBattery, indicating hybrid drive with hydrogen and liquefied natural gas and external chargeable battery (plug-in hybrid);
- ethanol, indicating ethanol or fuel mix of ethanol and other fuel (except petrol) or additives, e.g.
   E95;
- hybridFuelCellHydrogen, indicating hybrid drive with fuel cell (electric engine) and hydrogen (combustion engine);
- hybridFuelCellHydrogenExternalBattery, indicating hybrid drive with fuel cell (electric engine)
  and hydrogen (combustion engine) and external chargeable battery (plug-in hybrid);
- dualFuelLngDiesel, indicating dual operation with liquefied natural gas and diesel;
- electricExternal, indicating electric engine with external power supply;
- biogas, indicating mixture of different gases produced by the breakdown of organic matter;
- bioDiesel, indicating vegetable oil or animal fat-based diesel fuel;
- bioPetrol, indicating petrol fully or partly based on vegetable sources;
- bivalentPetrolBiogas, indicating bivalent operating engine with petrol or biogas;
- combinedBiogasElectricEngine, indicating combined operation of biogas and electric engine;
- dualFuelCngDiesel, indicating dual operation with compressed natural gas and diesel;
- other

### 5.2.18 EquipmentIccId

The data type EquipmentIccId shall be of the simple type as specified in Table 18.

# Table 18 — EquipmentIccId

Subtype	Parent type	Semantics
-		EquipmentIccId represents the identification number of the integrated circuit(s) card (ICC).

### 5.2.19 EquipmentObuId

The data type EquipmentObuld shall be of the simple type as specified in Table 19.

Table 19 — EquipmentObuId

Subtype	Parent type	Semantics
-		EquipmentObuId represents the unique identification of the onboard unit (OBU) within the context of the associated manufacturer.
		NOTE As an example of usage, EN 15509 expresses this value using four octets. Depending on the encoding rules used, an additional octet indicating the length can be inserted.

# 5.2.20 EquipmentStatus

The data type EquipmentStatus shall be of the constrained simple type as specified in <a href="Table 20.">Table 20.</a>

Table 20 — EquipmentStatus

Subtype	Parent type	Semantics
-		EquipmentStatus provides operator-specific EFC application-related information pertaining to the status of the equipment, stored in a bitstring of two octets.

# 5.2.21 EuroValue

The data type EuroValue shall be of the simple type as specified in Table 21.

Table 21 — EuroValue

	T	
Subtype	Parent type	Semantics
-	INTEGER	EuroValue represents the vehicle's Euro emission category as defined in the EU Regulation cited in Reference [13].
	NOTE It is of ENUMERATED type (ISO 14906).	The following semantics are assigned:
	W.	noEntry: Indicating that no Euro emission category value is provided;
	COL	— euro1: Indicating Euro emission category 1;
	60.	— euro2: Indicating Euro emission category 2;
	0515	— euro3: Indicating Euro emission category 3;
,	82	— euro4: Indicating Euro emission category 4;
<u> </u>		— euro5: Indicating Euro emission category 5;
CAM		— euro6: Indicating Euro emission category 6;
9		— euro7: Indicating Euro emission category 7;
		— eev: Indicating Enhanced Environmentally Friendly Vehicle class.
		NOTE The value euro7 is reserved for upcoming Euro emission category 7.

# 5.2.22 DistanceUnit

The data type DistanceUnit shall be of the simple type as specified in <a href="Table 22">Table 22</a>.

Table 22 — DistanceUnit

Subtype	Parent type	Semantics
-	INTEGER	DistanceUnit identifies units of distance. The following semantics are assigned:
		— kilometres,
		— metres,
		<pre>— decimetres,</pre>
		— centimetres,
		— millimetres.
		Values identifying non-ISO units are maintained in the ASN.1
		definition for backward compatibility, although deprecated.

# 5.2.23 IssuerIdentifier

The data type IssuerIdentifier shall be of the simple type as specified in Table 23.

Table 23 — IssuerIdentifier

Subtype	Parent type	Semantics
-		IssuerIdentifier provides the identifier of an organization according to the corresponding registry.  NOTE See Table 76 for an example of a specific registry usage.

# 5.2.24 Latitude

The data type Latitude shall be of the subtype as specified in Table 24.

### Table 24 — Latitude

Subtype	Parent type	Semantics
Int4Signed	60.	Latitude provides the latitude (in micro degrees) of the geographical point, with a range of 90° in the north or south hemisphere. Positive values are used for latitude north of the Equator, and negative values are used for latitude south of the Equator. So, the effective range of Latitude is (-90000000 90000000).

# 5.2.25 LocalVehicleClassId

The data type LocalVehicleClassId shall be of the subtype as specified in <a href="Table 25">Table 25</a>.

Table 25 — LocalVehicleClassId

Subtype	Parent type	Semantics
Int2Unsigned		LocalVehicleClassId provides the unique identifier of the local vehicle class.

# 5.2.26 LocationClassId

The data type LocationClassId shall be of the subtype as specified in <a href="Table 26">Table 26</a>.

Table 26 — LocationClassId

Subtype	Parent type	Semantics
Int4Unsigned		$\label{locationClassId} \begin{tabular}{l} Location ClassId\ provides\ the\ unique\ identifier\ of\ the\ location \\ class. \end{tabular}$

# 5.2.27 Longitude

The data type Longitude shall be of the subtype as specified in <a href="Table 27">Table 27</a>.

# Table 27 — Longitude

Subtype	Parent type	Semantics
Int4Signed		Longitude provides the longitude (in micro degrees) of the geographical point, providing a range of 180° to the east or to the west of the prime meridian (which passes through the Royal Observatory, Greenwich, England). Negative values are used for longitudes to the west, and positive values are used for longitudes to the east. So, the effective range of Longitude is (-179999999180000000).

# 5.2.28 PaymentSecurityData

The data type PaymentSecurityData shall be of the simple type as specified in Table 28.

Table 28 — PaymentSecurityData

Subtype	Parent type	Semantics
-		PaymentSecurityData provides security-related data for the authentication of the data integrity.

# 5.2.29 PayUnit

The data type PayUnit shall be of the simple constrained type as specified in Table 29.

### Table 29 — PavUnit

Subtype	Parent type	Semantics
-	OCTET STRING	PayUnit represents the unique designation of a factor to express a payment means value in multiples or fractions of a value and a currency in accordance with ISO 4217.
CTAND		The first character (4 bit) expresses a company-specific token or a "charging unit code" as used in the unit in which the fee is expressed. The following semantics are assigned:

Table 29 (continued)

Subtype	Parent type	Semantics
		— 0 'H: Currency in main units;
		— 1 'H: Currency in minor units of 10 :1 ('dime');
		— 2 'H: Currency in minor units of 100 :1 ('cents');
		— 3 'H: Currency in minor units of 1 000 :1;
		— 4 'H: Currency in 'major' units / 10 (e.g. EUR 10);
		— 5 'H: Currency in 'major' units / 100 (e.g. USD 100s);
		— 6 'H: Currency in 'major' units / 1 000;
		— 7'H: Currency in 'major' units / 10000;
		— 8 'H: Currency in 'major' units \ 100 000;
		— 9 'H: Currency in minor units of 10 000 :1;
		— A 'H: Currency in minor units of 100 000 :1;
		— в'H: Currency in minor units of 1 000 000 :1;
		— c'H: Tokens, specifying a Purse Provider specific coding;
		<ul> <li>D 'H: Charging Unit Codes denoting quantification of the serwice provided (e.g. worker-hours).</li> </ul>
		The last 3 characters (12 bit) is the binary coded decimal (BCD) representation of "Currency" as defined in ISO 4217.

# 5.2.30 PersonalAccountNumber

The data type Personal Account Number shall be of the simple type as specified in Table 30.

# Table 30 — PersonalAccountNumber

Subtype	Parent type	Semantics
	OCTET STRING	PersonalAccountNumber represents the personal account number structure in accordance with ISO/IEC 7812-1 and ISO/IEC 7812-2 using BCD sub-structures.

# 5.2.31 RearWheelsSteeringType

The data type RearWheelsSteeringType shall be of the simple type as specified in <u>Table 31</u>.

Table 31 — RearWheelsSteeringType

Subtype	Parent type	Semantics
-	INTEGER	RearWheelsSteeringType represents the type of steering for rear wheels. The following semantics are assigned:
		— noRearWheels: None of the rear wheels are steered;
		— foreMostRearWheels: The foremost of the rear wheels are steered;
		<pre>— rearMostRearWheels: The rear-most of the rear wheels are steered;</pre>
		— allRearWheels: All of the rear wheels are steered

# 5.2.32 ReceiptAuthenticator

The data type ReceiptAuthenticator shall be of the simple type as specified in Table 32.

Table 32 — ReceiptAuthenticator

Subtype	Parent type	Semantics
-		ReceiptAuthenticator contains an Authenticator over some attributes of the data group Receipt, calculated by the session service provider.

# 5.2.33 ReceiptDistance

The data type ReceiptDistance shall be of the subtype as specified in <a href="Table 33">Table 33</a>.

Table 33 — ReceiptDistance

Subtype	Parent type	·ij	Semantics
Int3Unsigned		vel	ceiptDistance contains the total distance covered by the nicle, since the beginning of its existence, in units of 100 m pressed as an integer.

# 5.2.34 ResultFin

The data type  ${\tt ResultFin}$  shall be of the simple constrained type as specified in <u>Table 34</u>.

Table 34 — ResultFin

Subtype	, All	Parent type	Semantics
-	5	OCTET STRING	ResultFin represents in one octet the operational result of the financial transaction. The following semantics are assigned:
			— Most significant 4 bits: 0 means OK:
			— '0x'H OK;
			— Most significant 4 bits > 0 means not OK:
			<ul><li>— '1x'H Not OK, not specified further;</li></ul>
			— '2x'H Not OK, Abnormal (First or Previous) Event;
			<ul><li>– '3x'H Not OK, Contract not accepted;</li></ul>
			<ul> <li>'4x'H Not OK, Account or Purse not accepted;</li> </ul>
			Least significant 4 bits mean:

Table 34 (continued)

Subtype	Parent type	Semantics
		<ul><li>— 'x0'H not specified further;</li></ul>
		<ul><li>– 'x1'H Balance close to zero;</li></ul>
		— 'x2'H Balance now negative;
		<ul><li>– 'x3'H Balance overflow;</li></ul>
		<ul><li>— 'x4'H Provider not accepted;</li></ul>
		— 'x5'H Authentication failure;
		<ul> <li>– 'x6'H Vehicle class incorrect.</li> </ul>

# 5.2.35 ReceiptIccId

The data type ReceiptIccId shall be of the simple type as specified in Table 35

Table 35 — ReceiptIccId

Subtype	Parent type	Semantics
-		ReceiptIccId provides the identification number of the smart card (ICC) used in the session.

# 5.2.36 ReceiptObuId

The data type ReceiptObuId shall be of the simple type as specified in Table 36.

Table36 — ReceiptObuId

	Subtype	Parent type	Semantics
-		OCTET STRING	ReceiptObuId represents the serial number of the OBU used in
		<b>M</b> .	the session, unique within the context of the manufacturer.

NOTE This type is only maintained for backward compatibility reasons. Its usage is deprecated.

# 5.2.37 ResultOp

The data type Resultop shall be of the simple type as specified in <u>Table 37</u>.

Table 37 — ResultOp

	Subtype	Parent type	Semantics
-		INTEGER	ResultOp represents the operational result of the EFC session. The following semantics are assigned:

 Table 37 (continued)

Subtype	Parent type	Semantics
		— correctTransaction, the transaction has been accepted;
		— obeStatusNotAccepted, not acceptable OBEStatus;
		<pre>— equipmentStatusNotAccepted, not acceptable   equipmentStatus;</pre>
		— contractNotInWhiteList, contract shall be in white list;
		— contractIdentifierInBlackList, contract blacklisted;
		<pre>— contractIdentifierNotCorrect, contract identifier not    valid;</pre>
		— expiredContract, contract expired;
		— contractRestrictionsNotFulfilledrestrictions in the contract not fulfilled;
		— claimedVehicleCharacteristicsNotValid, vehicle characteristics not conforming to those detected;
		— vehicleClassAuthenticationFailed, failure in vehicle class authentication;
		<ul> <li>entryVehicleClassDifferentFromExitVehicleClass, vehicle class in exit not conforming to vehicle class in entry;</li> </ul>
		— entryReceiptMissing, missing proof of entry;
		— entryReceiptNotValid, invalid proof of entry;
		<pre>— entryTollStationNotValid, invalid entry station;</pre>
		equipmentNotCertified, equipment not certified;
	-ON	timeDifference, problem with the time difference of the two last receipts;
	-0.	— accessCredentialsNotAccepted, invalid access credentials;
	205150	— contractAuthenticatorNotAccepted, invalid contract authenticator;
STAND		— receiptAuthenticatorNotAccepted, invalid receipt authenticator;
STAIL		— claimedVehicleCharacteristicsMissing, vehicle characteristics not detected;
		— paymentMeansNotAccepted, payment means not accepted;
		— paymentAuthenticatorNotAccepted, invalid payment authenticator;
		— paymentMeansInBlackList, payment means blacklisted;
		— paymentMeansNotCorrect, incorrect payment means;
		<pre>— expiredPaymentMeans, expired payment means;</pre>
		— paymentMeansRestrictionsNotFulfilled, restrictions in payment means not fulfilled.

# 5.2.38 ReceiptServiceSerialNumber

The data type ReceiptServiceSerialNumber shall be of the subtype as specified in <a href="Table 38">Table 38</a>.

Table 38 — ReceiptServiceSerialNumber

Subtype	Parent type	Semantics
Int3Unsigned		ReceiptServiceSerialNumber represents a specific serial number of the EFC session.
		NOTE The issuer of this number can be, for example, in a dedicated short-range communication (DSRC)-based toll system, or roadside equipment (RSE).

		roadside equipment (RSE).
5.2.39 ReceiptText The data type Receip		simple type as specified in Table 39.
Subtype	Parent type	Semantics
-	OCTET STRING	ReceiptText contains plain text decodable by the on-board equipment (OBE).

# 5.2.40 StationType

The data type  $\tt StationType$  shall be of the simple type as specified in <u>Table 40</u>.

Table 40 StationType

Subtype	Parent type 💃	Semantics
-	INTEGER	StationType represents the type of EFC Station. The following semantics are assigned:
	W.	— unspecified: No type is specified;
		— closedEntryWithPayment: A payment entry station in a closed system;
200		— closedEntryWithoutPayment: An entry station in a closed system without payment;
ETANDARDS		— closedTransit: A transit station in a closed system;
AMIL		— closedExit: An exit station in a closed system;
5		<ul> <li>closedCredit: A station where payment is by means of a rechargeable OBE;</li> </ul>
		— mixed: A multi-purpose station;
		— passage: An exit station in an open system;
		— checkpoint: A checkpoint station;
		<ul> <li>reload: A station where a rechargeable OBE can be recharged.</li> </ul>

# 5.2.41 SuspensionType

The data type SuspensionType shall be of the simple type as specified in <a href="Table 41">Table 41</a>.

Table 41 — SuspensionType

Subtype	Parent type	Semantics
-	INTEGER	SuspensionType represents the type of suspension of a vehicle. The following semantics are assigned:
		— noEntry: No information available;
		<ul> <li>airSuspension: Indicating that the vehicle is equipped with an air suspension;</li> </ul>
		— hydraulicSuspension: Indicating that the vehicle is equipped with a hydraulic suspension;
		— electricSuspension: Indicating that the vehicle is equipped with an electric suspension.

# 5.2.42 TariffClassId

The data type TariffClassId shall be of the subtype as specified in <a href="Table 42">Table 42</a>.

Table 42 — TariffClassId

Subtype	Parent type	Semantics
Int4Unsigned		TariffClassId provides the unique identifier of the tariff class.
		The default value is 0.

# 5.2.43 Time

The data type Time shall be of the subtype as specified in Table 43.

Table 43 — Time

Subtype	Parent type \	Semantics
Int4Unsigned		Time represents the number of seconds since midnight at the start of 1970-01-01.

# 5.2.44 TimeClassId

The data type TimeClassid shall be of the subtype as specified in <a href="Table 44">Table 44</a>.

Table 44 — TimeClassId

Subtype	Parent type	Semantics
Int2Unsigned		TimeClassId provides the unique identifier of the time class.

# 5.2.45 TimeUnit

The data type TimeUnit shall be of the simple type as specified in <u>Table 45</u>.

Table 45 — TimeUnit

Subtype	Parent type	are
-	INTEGER	${\tt TimeUnit} \ provides the unit of time. The following semantics are assigned:$
		— seconds,
		— minutes,
		— hours,
		— days,
		— months,
		— years

# 5.2.46 TrailerType

The data type TrailerType shall be of the simple type as specified in Table 46.

Table 46 — TrailerType

Subtype	Parent type	Semantics
-	INTEGER	TrailerType provides information about the type of trailer. The following semantics are assigned:  — notPresent: Indicating trailer not attached;  — trailer: Indicating trailer (also known as pull-bar trailer) attached;
	٤,,	semiTrailer: Indicating semitrailer (also known as articulate trailer) attached.

# **5.2.47 TyreConfiguration**

The data type TyreConfiguration shall be of the simple type as specified in Table 47.

Table 47 — TyreConfiguration

Subtype	Parent type	Semantics
- NDAR	INTEGER	TyreConfiguration provides information about the tyre configuration on the axles of the vehicle. The following semantics are assigned:
GTR.		— notSpecified: Indicating no values are provided;
		— singleTyre: Indicating single tyre on all axles;
		<ul> <li>dualTyres: Indicating dual tyres on at least one axle.</li> </ul>

# 5.2.48 UserClassId

The data type  ${\tt UserClassId}$  shall be of the subtype as specified in <u>Table 48</u>.

Table 48 — UserClassId

Subtype	Parent type	Semantics
Int1Unsigned		UserClassId provides the unique identifier of the user class.

# 5.2.49 VehicleAuthenticator

The data type VehicleAuthenticator shall be of the simple type as specified in Table 49.

Table 49 — Vehicle Authenticator

Subtype	Parent type	Semantics
-		VehicleAuthenticator provides an authenticator calculated by the entity entering the data elements at time of entry or modification.

### 5.2.50 VehicleClass

The data type VehicleClass shall be of the simple type as specified in <u>Table 50</u>.

# Table 50 — VehicleClass

Subtype	Parent type	Semantics
-		VehicleClass provides a TSP with specific information pertaining to the vehicle.  NOTE A more specific definition and an example of usage of VehicleClass is available in EN 15509.

# 5.2.51 VehicleCurrentMaxTrainWeight

The data type VehicleCurrentMaxTrainWeight shall be of the Subtype as specified in Table 51.

Table 51 — VehicleCurrentMaxTrainWeight

Subtype	Parent type	Semantics
Int2Unsigned	•	VehicleCurrentMaxTrainWeight represents the maximum permissible weight of the complete vehicle train that is currently in operation, which shall be stated in 10 kg units, in accordance with ISO 1176, rounded down to the next 10 kg step.  NOTE This weight can be lower than VehicleTrainMaximumWeight as it represents the current maximum train weight and not the maximum weight by design.

# 5.2.52 VehicleTechnicalPermissibleMaxLadenMass

The data type VehroleTechnicalPermissibleMaxLadenMass shall be of the subtype as specified in Table 52.

Table 52 — VehicleTechnicalPermissibleMaxLadenMass

Subtype	Parent type	Semantics
Int2Unsigned		VehicleTechnicalPermissibleMaxLadenMass represents the maximum technically permissible laden mass of the complete vehicle train, which shall be stated in 10 kg units, in accordance with ISO 1176, rounded down to the next 10 kg step.
		NOTE VehicleTechnicalPermissibleMaxLadenMass corresponds to "F.1" (maximum technically permissible laden mass, except for motorcycles) as defined in the European registration documents for vehicles. $\boxed{14}$

### 5.2.53 VehicleTotalDistance

The data type VehicleTotalDistance shall be of the subtype as specified in <a href="Table 53">Table 53</a>.

Table 53 — VehicleTotalDistance

Subtype	Parent type	Semantics
Int4Unsigned		VehicleTotalDistance represents the total travelled distance as measured by the vehicle, in 10 m resolution, continuously incremented.
		NOTE The initial value of this data type can be either the value zero or the vehicle's kilometre reading at the time of personalization of the OBE.

### 5.2.54 VehicleUsageCategoryType

The data type VehicleUsageCategoryType shall be of the simple type as specified in <u>Table 54</u>.

Table 54 — VehicleUsageCategoryType

Subtype	Parent type	Semantics
-		VehicleUsageCategoryType shall be used to specify the types of vehicles.

In addition to the data type specification the following semantic has been assigned:

- noEntry, indicating that there is no category available for the vehicle;
- handicappedPeople, indicating vehicles with special permissions for people with disabilities;
- military, indicating vehicles used by military forces;
- police, indicating vehicles used by police forces;
- roadMaintenance, indicating vehicles for maintaining roads and supply infrastructure;
- circusTruck, indicating vehicles used by travelling circus companies;
- mobileShopTruck, indicating vehicles used by mobile trader;
- truckCarryingMak, indicating trucks for milk transportation;
- truckCarryingTimber, indicating timber trucks;
- public Transport, indicating vehicles of local public traffic and intercity transport;
- enforcementAgent, indicating vehicles with special authorizations to enforce toll obligation.
- ambulance, indicating vehicles for medical transportation;
- fireBrigade, indicating vehicles used by firefighting crews;
- officialAuthority, indicating vehicles of public authority, government leaders or diplomatic mission;
- agriculturalVehicle, indicating vehicles with special characteristics for agricultural services;
- bus, indicating vehicles for passenger transportation;
- mobileHome, indicating motorhome or caravan pulled by car, van or truck;
- mobileCrane, indicating heavy duty vehicle with crane unit installed on it;

# ISO 17573-3:2023(E)

- exceptionalTransport, indicating vehicles that drive with a special traffic permission;
- emperor, indicating vehicles used by members of royal or imperial families;
- vocational Vehicle; vocational vehicle; [22]
- vehicleLiableToToll, indicating that the vehicle is liable to toll in general.

# 5.2.55 VehicleWeightLaden

The data type VehicleWeightLaden shall be of the subtype as specified in <a href="Table 55">Table 55</a>.

Table 55 — VehicleWeightLaden

Subtype	Parent type	Semantics
Int2Unsigned		VehicleWeightLaden represents the actual weight of the vehicle including load in 10 kg units, rounded down to the next 10 kg step.

The data type WeekDay shall be of the simple type as specified in Table 56.

Subtype	Parent type	Semantics
-	INTEGER	WeekDay represents the day of the week. The following seman-
		tics are assigned:
		— Monday
		— The day,
		Wednesday,
		— Thursday,
	COL	— Friday,
	60.	— Saturday,
	5	— Sunday.

# Single level data types

### AbsolutePosition2d 5.3.1

The data type Absolute Position 2d is an ordered list and shall consist of two components that identify a position in a 2-dimensional map as specified in <u>Table 57</u>.

Table 57 — AbsolutePosition2d

Component name	Component type	Semantics
gnssLon	Longitude, see Table 27	gnsslon provides the longitudinal coordinate of a geodetic position.
gnssLat	Latitude, see Table 24	gnssLat provides the latitudinal coordinate of a geodetic position.

### 5.3.2 AbsolutePosition3d

The data type AbsolutePosition3d is an ordered list and shall consist of two mandatory components and one optional component that identify a position in a 3-dimensional map as specified in <u>Table 58</u>.

Table 58 — AbsolutePosition3d

Component name	Component type	Semantics
longitude	Longitude, see <u>Table 27</u>	longitude provides the longitudinal coordinate of a point.
latitude	Latitude, see <u>Table 24</u>	latitude provides the latitudinal coordinate of a point.
altitude	Altitude, optional, see Table 3	altitude provides the altitude of a point?

# 5.3.3 AxleWeightLimit

The data type <code>AxleWeightLimit</code> is an ordered list and shall consist of two components that identify an axle of a vehicle and its related weight limit, as specified in <a href="Table 59">Table 59</a>.

Table 59 — AxleWeightLimit

Component name	Component type	Semantics
axleNumber	IntlUnsigned	axleNumber indicates the ordinal number of the vehicle axle, counted from the front axle.
maxLadenWeightOnAxle		maxLadenWeightOnAxle represents the technically permissible maximum laden weight on the axle of the vehicle, in 10 kg units, rounded down to the next 10 kg step.

# 5.3.4 AxleWeightLimits

The data type AxleWeightLimits is an ordered list and shall consist of five components that identify the weight limits on five axles, as specified in <u>Table 60</u>.

Table 60 — AxleWeightLimits

Component name	Component type	Semantics
maxLadenWeightOnAxleI	Int2Unsigned	MaxLadenWeightOnAxle1 represents the technically permissible maximum laden weight on axle 1 of the vehicle, in 10 kg units, rounded down to the next 10 kg step, according to the registration certificate of the vehicle.
maxLadenWeightOnAxle2	Int2Unsigned	MaxLadenWeightOnAxle2 represents the technically permissible maximum laden weight on axle 2 of the vehicle, in 10 kg units, rounded down to the next 10 kg step, according to the registration certificate of the vehicle.
maxLadenWeightOnAxle3	Int2Unsigned	MaxLadenWeightOnAxle3 represents the technically permissible maximum laden weight on axle 3 of the vehicle, in 10 kg units, rounded down to the next 10 kg step, according to the registration certificate of the vehicle.
maxLadenWeightOnAxle4	Int2Unsigned	MaxLadenWeightOnAxle4 represents the technically permissible maximum laden weight on axle 4 of the vehicle, in 10 kg units, rounded down to the next 10 kg step, according to the registration certificate of the vehicle.

Table 60 (continued)

Component name	Component type	Semantics
maxLadenWeightOnAxle5		MaxLadenWeightOnAxle5 represents the technically permissible maximum laden weight on axle 5 of the vehicle, in 10 kg units, rounded down to the next 10 kg step, according to the registration certificate of the vehicle.

# **5.3.5** DateCompact

The data type DateCompact is an ordered list and shall consist of three components that identify ayear, a month and a day, as specified in <a href="Table 61">Table 61</a>.

Table 61 — DateCompact

Component name	Component type	Semantics
year	INTEGER	year represents the year of the date in the Gregorian calendar.
month	INTEGER	month represents the month of the date in the Gregorian calendar.
day	INTEGER	day represent the day of the date in the Gregorian calendar.

### 5.3.6 DieselEmissionValues

The data type DieselEmissionValues is an ordered list and shall consist of two components that identify the emission value, as specified in Table 62.

Table 62 — DieselEmissionValues

Component name	Component type	Semantics
particulate	Particulate, see Table 72	particulate represents the type and value of the particulate.
absorptionCoeff	•	absorptionCoeff represents the corrected absorption coefficient for diesel, according to the registration certificate of the vehicle, in $10^{-3}~\text{m}^{-1}$ .

# 5.3.7 DriverCharacteristics

The data type <code>DriverCharacteristics</code> is an ordered list of two components that identify the driver's characteristics, as specified in <a href="Table 63">Table 63</a>.

Table 63 — DriverCharacteristics

Component name	Component type	Semantics
driverClas	Int1Unsigned	driverClass provides a description of the driver's characteristics as pertinent to the calculation of the tariff; contract provider specific coding.
tripPurpose	Int1Unsigned	tripPurpose provides a parameter indicating the purpose of the trip of the user as pertinent to the calculation of the tariff; contract provider specific coding.

### 5.3.8 Distance

The data type Distance is an ordered list of two components that identify a distance, as specified in Table 64.

Table 64 — Distance

Component name	Component type	Semantics
distanceValue	Int4Unsigned	distanceValue provides the value of the distance.
distanceUnit		distanceUnit provides the unit with which the distance is measured. It defaults to kilometres.

### 5.3.9 Duration

The data type Duration is an ordered list of two components as specified in <a href="Table 65">Table 65</a>.

Table 65 — Duration

Component name	Component type	Semantics Semantics
durationValue	Int4Unsigned	durationValue provides the length of time defining a duration.
durationUnit	TimeUnit, see Table 45	durationUnit provides the unit of time in which the duration is measured.

# 5.3.10 EngineDetails

The data type EngineDetails is an ordered list of two components that describe the characteristics of an engine, as specified in <a href="Table 66">Table 66</a>.

Table 66 — EngineDetails

Component name	Component type	Semantics
engineCapacity	Int2Unsigned	engine apacity represents the capacity of the vehicle's engine in cm.
enginePower	Int2Unsigned	enginePower represents the maximum net power of the vehicle's engine, in kW, as defined in Commission Directive 1999/37/EC,[14] Annex I, II.5, (P.2).

# 5.3.11 EuVehicleGroup

The data type <code>EuVehicleGroup</code> is an ordered list of two components that describe the EU vehicle group and subgroup, as specified in <a href="Table 67">Table 67</a>.

Table 67 — EuVehicleGroup

Component name	Component type	Semantics
mainEuVehicleGroup		mainEuVehicleGroup as defined in Commission Regulation (EU) 2017/2400, $^{[17]}$ Annex I.
subGroup	UTF8String	subGroup as defined in (EU) 2019/1242, $^{[18]}$ Annex I, $^{Table\ 1}$ - Vehicle sub-groups (sg).

### 5.3.12 ExhaustEmissionValues

The data type <code>ExhaustEmissionValues</code> is an ordered list of five components that specify emission values, as specified in <a href="Table 68">Table 68</a>.

Table 68 — ExhaustEmissionValues

Component name	Component type	Semantics
unitType	EmissionUnit, see Table 15	unitType represents the unit associated to the values in the other components.
emissionCo	INTEGER	emissionCo represents the exhaust emission of CO, according to vehicle registration documents, in $10^{-3}$ g/km or g/kWh.
emissionHc	Int2Unsigned	emissionHc represents the exhaust emission of hydrocarbon (HC), according to vehicle registration documents, in $10^{-3}$ g/km or g/kWh.
emissionNox	Int2Unsigned	emissionNox represents the exhaust emission of nitrogen oxides (NO $_{\rm X}$ ), according to vehicle registration documents, in $10^{-3}$ g/km or g/kWh.
emissionHcNox	Int2Unsigned	emissionHcNox represents the exhaust emission of HC+NO $_{\rm X}$ , according to vehicle registration documents, in $10^{-3}$ g/km or g/kWh.

NOTE If the emissions are measured directly on the engine test bed, the values are declared in g/kWh.

### 5.3.13 FutureCharacteristics

The data type FutureCharacteristics is an ordered list of four components that specify vehicle parameters, as specified in Table 69.

Table 69 — FutureCharacteristics

Component name	Component type	Semantics
futureElement	INTEGER	futureElement indicates a future characteristic. No semantics defined at the moment.
co2Scheme	Co2Scheme	See semantic definition of co2Scheme in Table 10.
co2Class	Co2EmissionClass	See semantic definition of co2Class in <u>Table 7</u> .
suspensionType	SuspensionType	See semantic definition of suspensionType in Table 42.

NOTE The ordered list is still 8 bits long if transferred as a an element encoded using the basic encoding rules. The different bits have been split up in different components according to the components defined above (fSSCCCss).

# 5.3.14 NumberOfAxles

The data type Number of axles shall consist of two components that specify the number of axles in the trailer and in the tractor, as specified in <u>Table 70</u>.

Table 70 — Number Of Axles

Component name	Component type	Semantics
trailerAxles	Axles, see <u>Table 4</u>	trailerAxles represents the number of axles of the trailer including drop axles.
		The value zero indicates no trailer present.
tractorAxles	Axles, see <u>Table 4</u>	$\label{tractorAxles} \begin{tabular}{l} tractorAxles \ represents the number of axles of the tractor including drop axles. \end{tabular}$
		A zero value indicates "not known".

### 5.3.15 Obeld

The data type <code>Obeld</code> shall consist of two components that identify the manufacturer and the identifier of an OBU, as specified in <a href="Table 71">Table 71</a>. An OBE may consist of separately manufactured parts, however it can be identified, for the purpose of this document, through the identifier of the OBU.

Table 71 — Obeld

Component name	Component type	Semantics
manufacturerId	Int2Unsigned	manufacturerId provides the unique identifier of the OBU manufacturer as defined according to ISO 14816.  NOTE See <a href="https://www.itsstandards.eu/registries/register-of-manufacturers-cs2/">www.itsstandards.eu/registries/register-of-manufacturers-cs2/</a> for a list of assigned values.
equipmentObuId	EquipmentObuId, see Table 19	Unique identifier as assigned by the manufacturer identified by component manufacturerId.

### 5.3.16 Particulate

The data type Particulate is an ordered list and shall consist of two components that identify the type and value of the particulate emitted by a diesel engine, as specified in Table 72.

Table 72 — Particulate

Component name	Component type	Semantics
unitType	EmissionUnit, see Table 16	unitType represents the units in which the particulate is expressed.
value	INTEGER	value represents the particulates for diesel, according to the registration certificate of the vehicle.

### 5.3.17 PassengerCapacity

The data type PassengerCapacity is an ordered list of two components that indicate a vehicle's capacity in terms of passengers, as specified in <u>Table 73</u>.

Table 73 — PassengerCapacity

Component name	Component type	Semantics
numberOfSeats	IntlUnsigned	numberOfSeats represents the number of seats of the vehicle, including the driver's seat, according to the registration certificate of the vehicle.
numberOfStandingPlaces	IntlUnsigned	numberOfStandingPlaces represents the number of standing places of the vehicle, according to the registration certificate of the vehicle.

### 5.3.18 PaymentFee

The data type PaymentFee is an ordered list of two components that specify a payment, as specified in Table 74.

Table 74 — PaymentFee

Component name	Component type	Semantics
paymentFeeAmount	IntlUnsigned	paymentFeeAmount represents the value of the fee being charged.
paymentFeeUnit		paymentFeeUnit represents the unit in which the fee is expressed.

### 5.3.19 Period

The data type Period is an ordered list of two components that specify a period of time in terms of a start time and an end time, as specified in <u>Table 75</u>.

Table 75 — Period

Component name	Component type	Semantics
beginOfPeriod	GeneralizedTime	beginOfPeriod defines the begin of a period.
endOfPeriod	GeneralizedTime	endOfPeriod defines the end of a period.

### 5.3.20 Provider

The data type Provider is an ordered list of two components that identify an organization as specified in Table 76.

Table 76 — Provider

Component name	Component type	Semantics
countryCode	CountryCode, see Table 14	countryCode identifies the country code of the country of the national registration administrator for issuers according to ISO 14816.
providerIdentifier	IssuerIdentifier, see Table 23	providerIdentifier identifies the organization according to the national ISO 14816 register for issuers.  NOTE See Reference [24] for a list of national registration administrators and their respective registers.  EXAMPLE An organization can be a toll charger or a toll service provider (TSP) according to ISO 17573-1.

### 5.3.21 RelativePosition3d

The data type RelativePosition3d is an ordered list of two mandatory and one optional component that identify a position in a 3-dimensional map in relation to another position, as specified in <u>Table 77</u>.

Table 77 — RelativePosition3d

Component name	Component type	Semantics
longitude	Int2Signed	longitude provides the relative longitudinal coordinate (in microdegrees) of a point with respect to a specified reference point.
latitude	int2Signed	latitude provides the relative latitudinal coordinate (in microdegrees) of a point with respect to a specified reference point.
altitude	Int2Signed	altitude provides the relative altitude (in 0,25 metre units) of a point with respect to a specified reference point.

# 5.3.22 SessionClass

The data type SessionClass is an ordered list of two components that identify a class and its related tariff for a vehicle in a given session, as specified in Table 78.

Table 78 — SessionClass

Component name	Component type	Semantics
sessionTariffClass	Int1Unsigned	sessionTariffClass provides a TSP-specific tariff class applied in the session.
sessionClaimedClass	Int1Unsigned	sessionClaimedClass provides a TSP-specific vehicle class derived from claimed characteristics.

### 5.3.23 SessionLocation

The data type SessionLocation is an ordered list of two components that identify the location of a session in terms of a direction and of a lane number, as specified in Table 79.

Table 79 — SessionLocation

Component name	Component type	Semantics
ascendingKilometrage	BOOLEAN	ascendingKilometrage provides a travel direction indicator. The following semantics are assigned:  — True: Means "according to ascending kilometrage of the road".  — False: Means "according to descending kilometrage of the road".
laneCodeNumber	INTEGER	laneCodeNumber provides a lane number.

# 5.3.24 SignedValue

The data type SignedValue is an ordered list of two components that are used to identify positive or negative values, as specified in Table 80.

Table 80 — SignedValue

Component name	Component type	Semantics
positive	INTEGER	positive represents positive integer values.
negative	INTEGER	negative represents negative integer values.

# 5.3.25 SoundLevel

The data type <code>SoundLevel</code> is an ordered list of two components that identify the levels of sound of a vehicle, as specified in <a href="Table 81">Table 81</a>.

Table 81 — SoundLevel

Component name	Component type	Semantics
soundStationary	Int1Unsigned	soundStationary represents the stationary sound of the vehicle in dB(A), according to the registration certificate of the vehicle.
soundDriveBy		soundDriveBy represents the sound of the vehicle when driving in dB(A), according to the registration certificate of the vehicle.

# 5.3.26 TariffClassDescription

The data type TariffClassDescription is an ordered list of five optional components, the first one of which is assigned a default value, that are used to specify a tariff class, as specified in <a href="Table 82">Table 82</a>.

Table 82 — TariffClassDescription

Component name	Component type	Semantics
tariffClassId	TariffClassId	See semantic definition of TariffClassId in Table 42.
		If this component is not specified, its value is defaulted to 0 (zero).
localVehicleClassId	LocalVehicleClassId	See semantic definition of Local Vehicle Class I d in Table 25.
timeClassId	TimeClassId	See semantic definition of TimeClassId in Table 44.
locationClassId	LocationClassId	See semantic definition of LocationCtassId in Table 26.
userClassId	UserClassId	See semantic definition of UserClassId in Table 48.

# 5.3.27 TimeCompact

The data type TimeCompact is an ordered list of three components that identify a time, as specified in Table 83.

Table 83 — TimeCompact

Component name	Component type	Semantics
Hours	INTEGER	hours expresses the number of hours of the time of the day after midnight.
Mins	INTEGER	mins expresses the number of minutes after the hour of the time of the day.
doubleSecs	INTEGER	doubleses expresses the number of two-seconds after the minute of the time of the day.

# 5.3.28 TrailerDetails

The data type TrailerDetails is an ordered list of two components that specify a trailer, as specified in Table 84.

Table 84 — TrailerDetails

Component name	Component type	Semantics
trailerType	TrailerType	See semantic definition of TrailerType in Table 46.
trailerAxles	Axles, see <u>Table 4</u>	trailerAxles represents the number of axles of the trailer including drop axles.
5		The value zero indicates no trailer present.

# 5.3.29 WheelsConfiguration

The data type <code>WheelsConfiguration</code> is an ordered list of four components that specify the wheels configuration of a vehicle, as specified in <a href="Table 85">Table 85</a>.

Table 85 — WheelsConfiguration

Component name	Component type	Semantics
numberOfWheels	INTEGER	Total number of wheels on a vehicle train. Twin-mounted tyres count as one wheel.
numberOfDrivenWheels	INTEGER	Number of driven wheels on a vehicle train.
numberOfSteeredWheels	INTEGER	Number of steered wheels on a vehicle train.
rearWheelsSteeringType	RearWheelsSteeringType, see Table 31	Type of rear steering wheels on a vehicle train.

# 5.4 Two-level data types

# 5.4.1 AxlesWeightLimits

The data type AxlesWeightLimits is a list of components of the same type that specify the weight limits for all axles of a vehicle, as specified in Table 86.

Table 86 — AxlesWeightLimits

Component name	Component type	Semantics
axleWeightLimits		The component axleWeightLimits contains the list of axle weight limits.

# 5.4.2 ChargeObjectId

The data type <code>ChargeObjectId</code> is an ordered list of one optional component and one mandatory component that identify a charge object, as specified in <a href="Table 88">Table 88</a>.

Table 87 — ChargeObjectId

Component name	Component type	Semantics
chargeObjectOperator		chargeObjectOperator identifies the entity operating the EFC regime in which the charge object is contained.
chargeObjectDesignation	Int4Unsigned	chargeObjectDesignation identifies the charge object within the given operator.

# 5.4.3 ContractValidity

The data type <code>ContractValidity</code> is an ordered list of two components that specify the validity of a contract, as specified in <a href="Table 88">Table 88</a>.

Table 88 — ContractValidity

Component name	Component type	Semantics
contractRestrictions	OCTET STRING	contractRestrictions contains a TSP-specific coding of the validity restrictions of a contract.
contractExpiryDate	DateCompact, see Table 61	contractExpiryDate contains the end-date of the validity of the contract. The validity ends at 24 h of the calendar day specified in contractExpiryDate.

### 5.4.4 DateAndTime

The data type <code>DateAndTime</code> is an ordered list of two components that specify a date and a time, as specified in <a href="Table 89">Table 89</a>.

Table 89 — DateAndTime

Component name	Component type	Semantics
timeDate	DateCompact, see Table 61	timeDate expresses the date according to the Gregorian calendar.
timeCompact	TimeCompact, see Table 83	timeCompact expresses time of the day in h, min and s.

### 5.4.5 EnvironmentalCharacteristics

The data type EnvironmentalCharacteristics is an ordered list of two components that specify environmental characteristics of a vehicle, as specified in Table 90.

Table~90-Environmental Characteristics

Component name	Component type	Semantics
euroValue		euroValue provides information about the vehicle's EURO value, according to the registration certificate of the vehicle.
copValue	CopValue, see Table 13	copValue provides information about the vehicle's carbon dioxide pollution values, according to the registration certificate of the vehicle.

# 5.4.6 InitialVehicleRegistrationDate

The data type InitialVehicleRegistrationDate shall be of the parent type as specified in Table 91.

Table 91 — Initial Vehicle Registration Date

Component name	Component type	Semantics
		InitialVehicleRegistrationDate expresses the date of first registration of a vehicle (Directive 1999/37/EC, $^{[14]}$ Annex I, field B).

### 5.4.7 Lpn

The data type  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as specified in  $_{Lpn}$  shall consist of three components that identify a licence plate number, as  $_{Lpn}$  shall consist of  $_{Lpn}$  shall consist of

Table 92 — Lpn

Component name	Component type	Semantics
countryCode	CountryCode, see Table 14	countryCode represents the country code associated with the licence plate number.
alphabetIndicator	ENUMERATED	alphabetIndicator indicates the type of alphabet used to represent the licence plate number. The following semantics are assigned:

Table 92 (continued)

Component name	Component type	Semantics
		— latinAlphabetNo1: Latin-1 in accordance with ISO/IEC 8859-1,
		— latinAlphabetNo2: Latin-2 in accordance with ISO/IEC 8859-2,
		— latinAlphabetNo3: latin-3 in accordance with ISO/IEC 8859-3,
		— latinAlphabetNo4: Latin-4 in accordance with ISO/IEC 8859-4,
		— latinCyrillicAlphabet: Cyrillic in accordance with ISO/IEC 8859-5,
		— latinArabicAlphabet Arabic in accordance with ISO/IEC 8859-6,
		— latinGreekAlphapet: Greek in accordance with ISO/IEC 8859-7,
		— latinHebrewAlphabet: Hebrew in accordance with ISO/IEC 8859-8,
		— lat hAlphabetNo5: Latin-5 in accordance with ISO/IEC 8859-9,
	.ev	latinAlphabetNo6: Latin-6 in accordance with ISO/IEC 8859-10,
	"O THE	— twoOctetBMP: value deprecated and not to be used,
	cjick to view	— fourOctetCanonical: value deprecated and not to be used.
	7.	NOTE ISO 14906:2022, Annex D, provides a mapping from LatinAlphabetNo1.
licencePlateNumber	OCTET STRING	licencePlateNumber contains the licence plate number coded in accordance to the alphabet indicated by the component alphabetIndicator.

# 5.4.8 PaymentMeans

The data type FaymentMeans is an ordered list of three components that identify the means used to perform a payment, as specified in  $\underline{\text{Table } 93}$ .

Table 93 — PaymentMeans

Component name	Component type	Semantics
personalAccountNumber	PersonalAccountNumber, see Table 31	personalAccountNumber represents the number of the payment means.
paymentMeansExpiryDate	DateCompact, see Table 61	paymentMeansExpiryDate represents the expiry date of the payment means. Payment means expires at 24 h of paymentMeansExpiryDate.
paymentMeansUsageControl	OCTET STRING	paymentMeansUsageControl indicates issuer's specified restrictions on the geographic usage and services allowed for the applications.

### 5.4.9 PaymentMeansBalance

The data type PaymentMeansBalance shall be of the parent type as specified in Table 94.

Table 94 — PaymentMeansBalance

Subtype	Parent type	Semantics
-		PaymentMeansBalance represents the Balance of payment means in units of PaymentMeansUnit.

### 5.4.10 Point

The data type Point provides a choice of three components, each of which can be used to identify a point in a map, as specified in <u>Table 95</u>.

Table 95 — Point

Component name	Component type	Semantics
pointIdentifier	Int4Unsigned	pointIdentifier provides the identi- fier of a point defined elsewhere.
absolutePointCoordinates	AbsolutePosition3d, see Table 58	absolutePointCoordinates provides the absolute coordinates of a point.
relativePointCoordinates	RelativePosition3d, see Table 77	relativePointCoordinates provides the relative coordinates of a point.

### 5.4.11 PurseBalance

The data type PurseBalance is an ordered list of two components that identify a value stored in an electronic purse, as specified in <u>Table 96</u>.

Table 96 — PurseBalance

Component name	Component type	Semantics
purseValue		purseValue represents the balance on the (electronic) purse, expressed in a currency.
purseUnit	PayUnit, see Table 29	purseUnit represents the unit of currency associated to the balance.

# 5.4.12 TrailerCharacteristics

The data type TrailerCharacteristics is an ordered list of three components that specify the characteristics of a trailer, as specified in Table 97.

Table 97 — TrailerCharacteristics

Component name	Component type	Semantics
trailerDetails	TrailerDetails, see Table 84	trailerDetails provides information on trailer presence, type and number of axles.
trailerMaxLadenWeight	Int2Unsigned	trailerMaxLadenWeight represents the maximum permissible total weight of the trailer including payload, which shall be stated in 10 kg units, in accordance with ISO 1176, rounded down to the next 10 kg step.
trailerWeightUnladen	Int2Unsigned	trailerWeightUnladen represents the nominal unladen weight of the trailer, which shall be stated in 10 kg units, in accordance with ISO 1176, rounded down to the next 10 kg step.