
**Plastics — Polyols for use in the
production of polyurethanes —
Determination of basicity (total amine
value), expressed as percent nitrogen**

*Plastiques — Polyalcools utilisés pour la production de
polyuréthannes — Détermination de la basicité (valeur totale d'amines)
en pourcentage d'azote*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 25761:2008



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Sampling	2
6 Interference	2
7 Reagents	2
8 Procedure	3
9 Expression of results	3
10 Precision and bias	4
11 Test report	5
Annex A (informative) Determination of the factor F for 0,1 mol/l perchloric acid in acetic acid	6
Bibliography	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 25761 was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 12, *Thermosetting materials*.

STANDARDSISO.COM : Click to view the full PDF of ISO 25761:2008

Introduction

Polyurethanes are produced by the catalysed reaction of isocyanates with polyols. The basicity of the polyol employed affects the rate of reaction and speed of cure of the product. It is therefore necessary to determine the basicity in order to predict reactivity and monitor product quality.

STANDARDSISO.COM : Click to view the full PDF of ISO 25761:2008

[STANDARDSISO.COM](https://standardsiso.com) : Click to view the full PDF of ISO 25761:2008

Plastics — Polyols for use in the production of polyurethanes — Determination of basicity (total amine value), expressed as percent nitrogen

SAFETY STATEMENT — Persons using this document should be familiar with normal laboratory practice, if applicable. This document does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any regulatory requirements.

1 Scope

1.1 The method specified in this International Standard measures the basic constituents in polyols that are soluble in glacial acetic acid and reactive with perchloric acid. Samples containing 0,3 % to 10 % of nitrogen have been evaluated by this method. The method is applicable to polyether polyols and polyether polyol blends that are used in polyurethane reactions. The results are measures of batch-to-batch uniformity and may be used to estimate reactivity in polyurethane reactions.

1.2 It is also permissible to express the results in equivalents of base per gram of sample.

1.3 This method is technically equivalent to that in ASTM D 6979-03.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

ISO 6353-1, *Reagents for chemical analysis — Part 1: General test methods*

ISO 6353-2, *Reagents for chemical analysis — Part 2: Specifications — First series*

ISO 6353-3, *Reagents for chemical analysis — Part 3: Specifications — Second series*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

polyol

polymer based on ethylene oxide and/or propylene oxide which contains two or more hydroxyl groups

3.2

polyurethane

polymer prepared by the reaction of an organic di- or polyisocyanate with a compound containing two or more hydroxyl groups

3.3

percent nitrogen

quantity of perchloric-acid-titratable base in a sample, expressed as a mass percentage of nitrogen

3.4

alkalinity

quantity of perchloric-acid-titratable base in a sample, expressed as mg of KOH/g of sample.

3.5

total amine value

quantity of perchloric-acid-titratable base in a sample, identified only as amines and expressed as mg of KOH/g of sample

4 Principle

A test portion of the sample is dissolved in glacial acetic acid. The resulting single-phase solution is titrated at room temperature to a potentiometric end point with a standardized solution of perchloric acid in acetic acid. The result is reported as percent nitrogen or mg of KOH/g of sample.

5 Sampling

Draw samples from a well-mixed vessel into a thoroughly cleaned and dry borosilicate-glass container (soft-glass containers are not acceptable). If sampling from a line or valve, flush the line thoroughly with the product before starting to draw the sample. Seal the sample until analysis.

6 Interference

Any acidic or basic materials inadvertently introduced into the sample will cause errors in the analysis. Any material capable of serving as a buffer may interfere with the analysis by obscuring the titration end point.

7 Reagents

Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of ISO 6353-1, ISO 6353-2 and ISO 6353-3, as applicable. Other grades may be used, however, provided that it is first determined that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

Unless otherwise indicated, references to water shall be understood to mean grade 2 water as defined in ISO 3696.

7.1 **Glacial acetic acid.**

7.2 **Acetic anhydride.**

7.3 **Perchloric acid**, nominal concentration 70 %.

7.4 **Perchloric acid in acetic acid**, concentration 0,10 mol/l.

One way of preparing the 0,10 mol/l perchloric acid in acetic acid is as follows. In a 1 000 ml volumetric flask, mix 8,7 ml of perchloric acid (7.3) with 500 ml of glacial acetic acid (7.1). Add 25 ml of acetic anhydride (7.2) and dilute to volume with glacial acetic acid.

WARNING — Perchloric acid is extremely irritating to the skin, eyes and mucous membranes, highly toxic via oral and inhalation routes, and can form explosive mixtures when mixed with carbonaceous material or allowed to dry. Concentrated perchloric acid should only be used in a hood approved for perchloric acid use. Chemically resistant gloves should be worn. In the event of skin contact, wash with soap and water. Goggles or safety glasses with side shields should be worn. In the event of eye contact, flush with copious amounts of water for 15 minutes. In the event of inhalation, move the victim to an uncontaminated area. In the event of ingestion, do not induce vomiting. For all exposures, seek professional medical advice.

It is strongly recommended that reference articles on perchloric acid safety be consulted to determine safe-handling and clean-up procedures (see References [1] to [6] and references cited therein).

8 Procedure

8.1 Weigh a test portion of the sample into a suitable container, calculating the mass of the test portion as follows:

$$M' = 2/P$$

where

M' is the mass of the test portion, in g;

P is the expected percent nitrogen content of the sample.

For test portion masses below 10,0 g, record the mass to the nearest 0,1 mg; for test portion masses greater than 10,0 g, record the mass to the nearest 0,01 g.

8.2 Add 100 ml of glacial acetic acid and stir gently until the test portion has dissolved completely.

If necessary, the mixture can be heated gently until the test portion has completely dissolved.

8.3 Titrate the test solution potentiometrically with 0,10 mol/l perchloric acid (7.4) through the end point which occurs at about 600 mV.

Colorimetric end point determination can also be used. A suitable indicator is patent blue VF. Use ten drops of indicator solution (0,3 % by mass of indicator in glacial acetic acid).

8.4 Under normal circumstances, the blank value is negligibly small and is not included in the calculation. However, a solvent blank should preferably be evaluated at suitable intervals to confirm that the solvent blank is indeed a negligible value.

NOTE Some laboratories report using this general procedure for lower levels of basicity, employing 0,01 mol/l perchloric acid as the titrant. Better results are reported at low levels with a colorimetric end point determination. No blank is needed since the solvent is neutralized to a green end point before the test solution is added. Precision data reported in this International Standard are based on the range 0,3 % to 10 % nitrogen. Precision data at lower ranges of nitrogen are not available at the current time. Therefore, precision studies will be necessary before the method is applied to ranges below 0,3 % nitrogen.

9 Expression of results

9.1 Calculate the basicity of the sample, as percent nitrogen (% N) as follows:

$$\% \text{ N} = \frac{V \times F \times 1,4}{m \times 1000} \times 100$$

where

- V is the volume of titrant used to reach the end point of the test solution titration, in ml;
- F is the factor for the concentration of the perchloric acid solution used as the titrant (calculated as described in Annex A);
- m is the mass of the sample, in g;
- 1,4 is the product of the atomic mass of nitrogen (14) and the nominal concentration of the perchloric acid (0,1 mol/l);
- 1 000 is a conversion factor to convert grams to milligrams.

9.2 It is permissible to also report the results as alkalinity in mg of KOH/g of sample, as follows:

$$\text{Alkalinity (total amine value as mg KOH/g)} = \frac{V \times F \times 5,61}{m}$$

where

5,61 is the product of the molecular mass of KOH (56,1) and the nominal concentration of the perchloric acid (0,1 mol/l);

the other symbols are as defined in 9.1 above.

10 Precision and bias

10.1 General

Table 1 is based on a round-robin involving seven laboratories and conducted in 2002 in accordance with ASTM E 180. All laboratories used potentiometric titration for the generation of the data used in this study. All of the samples were prepared at one source, but the individual test solutions were prepared at the laboratories that tested them. Each test result was the average of two individual determinations. Each laboratory made duplicate determinations on each material on each of two days.

Table 1 — Round-robin percent nitrogen data

Values in percent nitrogen

Material	Average	s_r	s_R	r	R	DF
A	0,317	0,000 7	0,001 8	0,002 0	0,005 0	5
B	2,51	0,004 6	0,005 3	0,012 9	0,014 8	5
C	5,86	0,007 9	0,013 9	0,022 1	0,039 2	5
D	9,45	0,022 0	0,021 7	0,061 6	0,061 8	5
s_r is the within-laboratory standard deviation from the mean; s_R is the between-laboratory standard deviation from the mean; r is the within-laboratory repeatability limit ($= 2,8s_r$); R is the between-laboratory reproducibility limit ($= 2,8s_R$); DF is the number of degrees of freedom in the data.						

10.2 Precision

10.2.1 Repeatability, r : Comparing two replicate results for the same material, obtained by the same operator using the same equipment on the same day, the two results shall be judged not equivalent if they differ by more than the value of r given for that material in Table 1.

10.2.2 Reproducibility, R : Comparing two results, each the mean of replicates, for the same material, obtained by different operators using different equipment in different laboratories on different days, the two results shall be judged not equivalent if they differ by more than the value of R given for that material in Table 1.

10.2.3 Any judgement in accordance with 10.2.1 or 10.2.2 would have an approximately 95 % probability of being correct.

CAUTION — The explanations of r and R given above are intended only to present a meaningful way of considering the approximate precision of this test method. The data in Table 1 should not be applied rigorously to the acceptance or rejection of material, as those data are specific to the round-robin and may not be representative of other lots, conditions, materials or laboratories. Users of this test method should apply statistical principles to generate data specific to their laboratory and materials, or to reproducibility between specific laboratories. The principles of 10.2.1 to 10.2.3 would then be valid for such data.

10.3 Bias

Bias is the difference between the observed test results and an accepted reference value. There are no recognized standards by which to estimate the bias of this test method.

11 Test report

The test report shall include the following information:

- a) a reference to this International Standard;
- b) all details necessary to identify the product analysed (such as manufacturer, product type, lot or notebook number and date of manufacture, as required);
- c) the result obtained, expressed as percent nitrogen to the nearest 0,01 %, or as total amine value to the nearest 0,1 mg of KOH/g of sample;
- d) any incident or detail not stipulated in this International Standard which may have influenced the result;
- e) the date of the analysis.