



## Information technology — Coding of audio-visual objects — Part 3: Audio

AMENDMENT 2: Audio Lossless Coding (ALS), new audio profiles and BSAC extensions  
TECHNICAL CORRIGENDUM 2

*Technologies de l'information — Codage des objets audiovisuels —*

*Partie 3: Codage audio*

*AMENDEMENT 2: Codage audio sans perte (ALS), nouveaux profils audio et extensions BSAC*

*RECTIFICATIF TECHNIQUE 2*

Technical Corrigendum 2 to ISO/IEC 14496-3:2005/Amd.2:2006 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

Throughout this Corrigendum, modifications or additions to existing text are highlighted in grey.

Page 4, after Table 1.11A, replace:

A HE AAC v2 Profile decoder of a certain level shall operate the HQ SBR tool for streams containing Parametric Stereo data. For streams not containing Parametric Stereo data, the HE AAC v2 Profile decoder may operate the HQ SBR tool, or the LP SBR tool.

with:

An HE AAC v2 Profile decoder shall operate the HQ SBR tool for bitstreams containing Parametric Stereo data. For bitstreams not containing Parametric Stereo data, the HE AAC v2 Profile decoder may operate the HQ SBR tool, or the LP SBR tool.

Only bitstreams consisting of exactly one AAC single channel element may contain Parametric Stereo data. Bitstreams containing more than one channel in the AAC part shall not contain Parametric Stereo data.

Page 6, in Table 1.13 replace the rows:

|                                                                         |  |                       |
|-------------------------------------------------------------------------|--|-----------------------|
| case 36:<br>ALSSpecificConfig();<br>break;                              |  |                       |
| with:<br>case 36:<br><b>fillBits;</b><br>ALSSpecificConfig();<br>break; |  | <b>5</b> <b>bslbf</b> |

In ISO/IEC 14496-3:2005, after 1.6.3.14 add:

#### 1.6.3.15 FillBits

Fill bits for byte alignment of ALSSpecificConfig() relative to the start of AudioSpecificConfig().

Page 8, replace the final sentence:

Similarly the HE AAC v2 decoder can handle all HE AAC Profile streams as well as all AAC Profile streams.

with:

Similarly an HE AAC v2 profile decoder of a certain level can handle all HE AAC Profile streams of the same or lower level as well as all AAC Profile streams of the same or lower level.

In 11.2.1, replace:

(see subclause 11.6.7)

with:

(see subclause 11.6.5.2.1 and 11.6.7)

Page 18, at the end of 11.3.3 add:

x.y Fixed-point signed fractional representation, where x is the number of bits to the left of the binary point, and y is the number of bits to the right of the binary point (two's complement sign representation). 64-bit signed integer (two's complement)

Page 18, replace Table 11.1 with the following table:

|                                                              |                         |               |
|--------------------------------------------------------------|-------------------------|---------------|
| <b>als_id;</b>                                               | <b>32</b>               | <b>uimsbf</b> |
| <b>samp_freq;</b>                                            | <b>32</b>               | <b>uimsbf</b> |
| <b>samples;</b>                                              | <b>32</b>               | <b>uimsbf</b> |
| <b>channels;</b>                                             | <b>16</b>               | <b>uimsbf</b> |
| <b>file_type;</b>                                            | <b>3</b>                | <b>uimsbf</b> |
| <b>resolution;</b>                                           | <b>3</b>                | <b>uimsbf</b> |
| <b>floating;</b>                                             | <b>1</b>                | <b>uimsbf</b> |
| <b>msb_first;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>frame_length;</b>                                         | <b>16</b>               | <b>uimsbf</b> |
| <b>random_access;</b>                                        | <b>8</b>                | <b>uimsbf</b> |
| <b>ra_flag;</b>                                              | <b>2</b>                | <b>uimsbf</b> |
| <b>adapt_order;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>coef_table;</b>                                           | <b>2</b>                | <b>uimsbf</b> |
| <b>long_term_prediction;</b>                                 | <b>1</b>                | <b>uimsbf</b> |
| <b>max_order;</b>                                            | <b>10</b>               | <b>uimsbf</b> |
| <b>block_switching;</b>                                      | <b>2</b>                | <b>uimsbf</b> |
| <b>bgmc_mode;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>sb_part;</b>                                              | <b>1</b>                | <b>uimsbf</b> |
| <b>joint_stereo;</b>                                         | <b>1</b>                | <b>uimsbf</b> |
| <b>mc_coding;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_config;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_sort;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>crc_enabled;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>RLS_LMS</b>                                               | <b>1</b>                | <b>uimsbf</b> |
| <b>(reserved)</b>                                            | <b>5</b>                |               |
| <b>aux_data_enabled;</b>                                     | <b>1</b>                | <b>uimsbf</b> |
| if (chan_config) {                                           |                         |               |
| <b>chan_config_info;</b>                                     | <b>16</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if (chan_sort) {                                             |                         |               |
| for (c = 0; c < channels; c++)                               |                         |               |
| <b>chan_pos[c];</b>                                          | <b>1..16</b>            | <b>uimsbf</b> |
| }                                                            |                         |               |
| <b>byte_align;</b>                                           | <b>0..7</b>             | <b>bslbf</b>  |
| <b>header_size;</b>                                          | <b>32</b>               | <b>uimsbf</b> |
| <b>trailer_size;</b>                                         | <b>32</b>               | <b>uimsbf</b> |
| <b>orig_header[];</b>                                        | <b>header_size * 8</b>  | <b>bslbf</b>  |
| <b>orig_trailer[];</b>                                       | <b>trailer_size * 8</b> | <b>bslbf</b>  |
| if (crc_enabled) {                                           |                         |               |
| <b>crc;</b>                                                  | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if ((ra_flag == 2) && (random_access > 0)) {                 |                         |               |
| for (f = 0; f < ((samples-1) / (frame_length+1)) + 1; f++) { |                         |               |
| <b>ra_unit_size[f]</b>                                       | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| }                                                            |                         |               |
| if (aux_data_enabled) {                                      |                         |               |
| <b>aux_size;</b>                                             | <b>32</b>               | <b>uimsbf</b> |

|                                                              |                         |               |
|--------------------------------------------------------------|-------------------------|---------------|
| <b>als_id;</b>                                               | <b>32</b>               | <b>uimsbf</b> |
| <b>samp_freq;</b>                                            | <b>32</b>               | <b>uimsbf</b> |
| <b>samples;</b>                                              | <b>32</b>               | <b>uimsbf</b> |
| <b>channels;</b>                                             | <b>16</b>               | <b>uimsbf</b> |
| <b>file_type;</b>                                            | <b>3</b>                | <b>uimsbf</b> |
| <b>resolution;</b>                                           | <b>3</b>                | <b>uimsbf</b> |
| <b>floating;</b>                                             | <b>1</b>                | <b>uimsbf</b> |
| <b>msb_first;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>frame_length;</b>                                         | <b>16</b>               | <b>uimsbf</b> |
| <b>random_access;</b>                                        | <b>8</b>                | <b>uimsbf</b> |
| <b>ra_flag;</b>                                              | <b>2</b>                | <b>uimsbf</b> |
| <b>adapt_order;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>coef_table;</b>                                           | <b>2</b>                | <b>uimsbf</b> |
| <b>long_term_prediction;</b>                                 | <b>1</b>                | <b>uimsbf</b> |
| <b>max_order;</b>                                            | <b>10</b>               | <b>uimsbf</b> |
| <b>block_switching;</b>                                      | <b>2</b>                | <b>uimsbf</b> |
| <b>bgmc_mode;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>sb_part;</b>                                              | <b>1</b>                | <b>uimsbf</b> |
| <b>joint_stereo;</b>                                         | <b>1</b>                | <b>uimsbf</b> |
| <b>mc_coding;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_config;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_sort;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>crc_enabled;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>RLS_LMS</b>                                               | <b>1</b>                | <b>uimsbf</b> |
| <b>(reserved)</b>                                            | <b>5</b>                |               |
| <b>aux_data_enabled;</b>                                     | <b>1</b>                | <b>uimsbf</b> |
| if (chan_config) {                                           |                         |               |
| <b>chan_config_info;</b>                                     | <b>16</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if (chan_sort) {                                             |                         |               |
| for (c = 0; c < channels; c++)                               |                         |               |
| <b>chan_pos[c];</b>                                          | <b>1..16</b>            | <b>uimsbf</b> |
| }                                                            |                         |               |
| <b>byte_align;</b>                                           | <b>0..7</b>             | <b>bslbf</b>  |
| <b>header_size;</b>                                          | <b>32</b>               | <b>uimsbf</b> |
| <b>trailer_size;</b>                                         | <b>32</b>               | <b>uimsbf</b> |
| <b>orig_header[];</b>                                        | <b>header_size * 8</b>  | <b>bslbf</b>  |
| <b>orig_trailer[];</b>                                       | <b>trailer_size * 8</b> | <b>bslbf</b>  |
| if (crc_enabled) {                                           |                         |               |
| <b>crc;</b>                                                  | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if ((ra_flag == 2) && (random_access > 0)) {                 |                         |               |
| for (f = 0; f < ((samples-1) / (frame_length+1)) + 1; f++) { |                         |               |
| <b>ra_unit_size[f]</b>                                       | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| }                                                            |                         |               |
| if (aux_data_enabled) {                                      |                         |               |
| <b>aux_size;</b>                                             | <b>32</b>               | <b>uimsbf</b> |

|                                                              |                         |               |
|--------------------------------------------------------------|-------------------------|---------------|
| <b>als_id;</b>                                               | <b>32</b>               | <b>uimsbf</b> |
| <b>samp_freq;</b>                                            | <b>32</b>               | <b>uimsbf</b> |
| <b>samples;</b>                                              | <b>32</b>               | <b>uimsbf</b> |
| <b>channels;</b>                                             | <b>16</b>               | <b>uimsbf</b> |
| <b>file_type;</b>                                            | <b>3</b>                | <b>uimsbf</b> |
| <b>resolution;</b>                                           | <b>3</b>                | <b>uimsbf</b> |
| <b>floating;</b>                                             | <b>1</b>                | <b>uimsbf</b> |
| <b>msb_first;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>frame_length;</b>                                         | <b>16</b>               | <b>uimsbf</b> |
| <b>random_access;</b>                                        | <b>8</b>                | <b>uimsbf</b> |
| <b>ra_flag;</b>                                              | <b>2</b>                | <b>uimsbf</b> |
| <b>adapt_order;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>coef_table;</b>                                           | <b>2</b>                | <b>uimsbf</b> |
| <b>long_term_prediction;</b>                                 | <b>1</b>                | <b>uimsbf</b> |
| <b>max_order;</b>                                            | <b>10</b>               | <b>uimsbf</b> |
| <b>block_switching;</b>                                      | <b>2</b>                | <b>uimsbf</b> |
| <b>bgmc_mode;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>sb_part;</b>                                              | <b>1</b>                | <b>uimsbf</b> |
| <b>joint_stereo;</b>                                         | <b>1</b>                | <b>uimsbf</b> |
| <b>mc_coding;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_config;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>chan_sort;</b>                                            | <b>1</b>                | <b>uimsbf</b> |
| <b>crc_enabled;</b>                                          | <b>1</b>                | <b>uimsbf</b> |
| <b>RLS_LMS</b>                                               | <b>1</b>                | <b>uimsbf</b> |
| <b>(reserved)</b>                                            | <b>5</b>                |               |
| <b>aux_data_enabled;</b>                                     | <b>1</b>                | <b>uimsbf</b> |
| if (chan_config) {                                           |                         |               |
| <b>chan_config_info;</b>                                     | <b>16</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if (chan_sort) {                                             |                         |               |
| for (c = 0; c < channels; c++)                               |                         |               |
| <b>chan_pos[c];</b>                                          | <b>1..16</b>            | <b>uimsbf</b> |
| }                                                            |                         |               |
| <b>byte_align;</b>                                           | <b>0..7</b>             | <b>bslbf</b>  |
| <b>header_size;</b>                                          | <b>32</b>               | <b>uimsbf</b> |
| <b>trailer_size;</b>                                         | <b>32</b>               | <b>uimsbf</b> |
| <b>orig_header[];</b>                                        | <b>header_size * 8</b>  | <b>bslbf</b>  |
| <b>orig_trailer[];</b>                                       | <b>trailer_size * 8</b> | <b>bslbf</b>  |
| if (crc_enabled) {                                           |                         |               |
| <b>crc;</b>                                                  | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| if ((ra_flag == 2) && (random_access > 0)) {                 |                         |               |
| for (f = 0; f < ((samples-1) / (frame_length+1)) + 1; f++) { |                         |               |
| <b>ra_unit_size[f]</b>                                       | <b>32</b>               | <b>uimsbf</b> |
| }                                                            |                         |               |
| }                                                            |                         |               |
| if (aux_data_enabled) {                                      |                         |               |
| <b>aux_size;</b>                                             | <b>32</b>               | <b>uimsbf</b> |

Page 21, in Table 11.3, replace:

|                                                                                                                              |               |                  |
|------------------------------------------------------------------------------------------------------------------------------|---------------|------------------|
| <pre> if (adapt_order == 1) {     <b>opt_order;</b> } for (p = 0; p &lt; opt_order; p++) {     <b>quant_cof[p];</b> } </pre> | <b>1..10</b>  | <b>uimsbf</b>    |
|                                                                                                                              | <b>varies</b> | <b>Rice code</b> |

|                                                          |  |  |
|----------------------------------------------------------|--|--|
| <pre> if (RLSLMS) {     RLSLMS_extension_data() } </pre> |  |  |
|----------------------------------------------------------|--|--|

with:

|                                                                                                                                                                         |               |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------|
| <pre> if (adapt_order == 1) {     <b>opt_order;</b> } else {     <b>opt_order = max_order;</b> } for (p = 0; p &lt; opt_order; p++) {     <b>quant_cof[p];</b> } </pre> | <b>1..10</b>  | <b>uimsbf</b>    |
|                                                                                                                                                                         | <b>varies</b> | <b>Rice code</b> |

|                                                                               |             |              |
|-------------------------------------------------------------------------------|-------------|--------------|
| <pre> if (RLSLMS) {     RLSLMS_extension_data() } <b>byte_align;</b> } </pre> | <b>0..7</b> | <b>bslbf</b> |
|-------------------------------------------------------------------------------|-------------|--------------|



|                      |    |                                                                                                                                                                                                                                                                                                                  |
|----------------------|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| resolution           | 3  | 000 = 8-bit<br>001 = 16-bit<br>010 = 24-bit<br>011 = 32-bit<br>(other values are reserved)                                                                                                                                                                                                                       |
| floating             | 1  | 1 = IEEE 32-bit floating-point, 0 = integer                                                                                                                                                                                                                                                                      |
| msb_first            | 1  | Original byte order of the input audio data:<br>0 = least significant byte first (little-endian)<br>1 = most significant byte first (big-endian)<br>If resolution = 0 (8-bit data), msb_first = 0 indicates unsigned data (0...255), while msb_first = 1 indicates signed data (-128...127).                     |
| frame_length         | 16 | Frame Length - 1 (e.g. frame_length = 0x1FFF signals a frame length of N = 8192)                                                                                                                                                                                                                                 |
| random_access        | 8  | Distance between RA frames (in frames, 0...255). If no RA is used, the value is zero. If each frame is an RA frame, the value is 1.                                                                                                                                                                              |
| ra_flag              | 2  | Indicates where the size of random access units (ra_unit_size) is stored:<br>00: not stored<br>01: stored at the beginning of frame_data()<br>10: stored at the end of ALSSpecificConfig()                                                                                                                       |
| adapt_order          | 1  | Adaptive Order: 1 = on, 0 = off                                                                                                                                                                                                                                                                                  |
| coef_table           | 2  | Table index (00, 01, or 10, see Table 11.20) of Rice code parameters for entropy coding of predictor coefficients, 11 = no entropy coding                                                                                                                                                                        |
| long_term_prediction | 1  | Long term prediction (LTP): 1 = on, 0 = off                                                                                                                                                                                                                                                                      |
| max_order            | 10 | Maximum prediction order (0..1023)                                                                                                                                                                                                                                                                               |
| block_switching      | 2  | Number of block switching levels:<br>00 = no block switching<br>01 = up to 3 levels<br>10 = 4 levels<br>11 = 5 levels                                                                                                                                                                                            |
| bgmc_mode            | 1  | BGMC Mode: 1 = on, 0 = off (Rice coding only)                                                                                                                                                                                                                                                                    |
| sb_part              | 1  | Sub-block partition for entropy coding of the residual.<br>if bgmc_mode = 0:<br>0 = no partition, no ec_sub bit in block_data<br>1 = 1:4 partition, one ec_sub bit in block_data<br>if bgmc_mode = 1:<br>0 = 1:4 partition, one ec_sub bit in block_data<br>1 = 1:2:4:8 partition, two ec_sub bits in block_data |
| joint_stereo         | 1  | Joint Stereo: 1 = on, 0 = off<br>If channels = 0 (mono), joint_stereo = 0                                                                                                                                                                                                                                        |

|                  |                     |                                                                                                                                                                                                                                                                               |
|------------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mc_coding        | 1                   | Extended inter-channel coding: 1 = on, 0 = off<br>If channels = 0 (mono), mc_coding = 0                                                                                                                                                                                       |
| chan_config      | 1                   | Indicates that a chan_config_info field is present                                                                                                                                                                                                                            |
| chan_sort        | 1                   | Channel rearrangement: 1 = on, 0 = off<br>If channels = 0 (mono), chan_sort = 0                                                                                                                                                                                               |
| crc_enabled      | 1                   | Indicates that the crc field is present                                                                                                                                                                                                                                       |
| RLSLMS           | 1                   | Use RLS-LMS predictor: 1 = on, 0 = off                                                                                                                                                                                                                                        |
| (reserved)       | 5                   |                                                                                                                                                                                                                                                                               |
| aux_data_enabled | 1                   | Indicates that auxiliary data is present (fields aux_size and aux_data)                                                                                                                                                                                                       |
| chan_config_info | 16                  | Mapping of channels to loudspeaker locations. Each bit indicates whether a channel for a particular predefined location exists (see 11.6.1.5).                                                                                                                                |
| chan_pos[]       | (channels+1)*ChBits | If channel rearrangement is on (chan_sort = 1), these are the original channel positions. The number of bits per channel is<br>$\text{ChBits} = \text{ceil}[\log_2(\text{channels}+1)] = 1..16$<br>where channels+1 is the number of channels.                                |
| header_size      | 32                  | Header size of original audio file in bytes<br>If header_size = 0xFFFFFFFF (Hex), there is no orig_header[] field, but the original header may be stored elsewhere, e.g. in the meta data of an MPEG-4 file.                                                                  |
| trailer_size     | 32                  | Trailer size of original audio file in bytes<br>If trailer_size = 0xFFFFFFFF (Hex), there is no orig_trailer[] field, but the original trailer may be stored elsewhere, e.g. in the meta data of an MPEG-4 file.                                                              |
| orig_header[]    | header_size*8       | Header of original audio file                                                                                                                                                                                                                                                 |
| orig_trailer[]   | trailer_size*8      | Trailer of original audio file                                                                                                                                                                                                                                                |
| crc              | 32                  | 32-bit CCITT-32 CRC checksum of the original audio data bytes (polynomial: $x^{32} + x^{26} + x^{23} + x^{22} + x^{16} + x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1$ ).                                                                                   |
| ra_unit_size[]   | #frames*32          | Distances (in bytes) between the random access frames, i.e. the sizes of the random access units, where the number of frames is<br>$\text{\#frames} = ((\text{samples}-1) / (\text{frame\_length}+1)) + 1$<br>In ALSSpecificConfig(), this field appears only if ra_flag = 2. |
| aux_size         | 32                  | Size of the aux_data field in bytes<br>If aux_size = 0xFFFFFFFF (Hex), there is no aux_data[] field, but the auxiliary data may be stored elsewhere, e.g. in the meta data of an MPEG-4 file.                                                                                 |
| aux_data[]       | aux_size*8          | Auxiliary data (not required for decoding)                                                                                                                                                                                                                                    |

Page 28, in Table 11.10 replace:

ra\_flag = 2

with:

ra\_flag = 1

Page 30, replace Table 11.13 with the following table:

**Table 11.13 — Elements of RLSLMS\_extension\_data**

| Field          | #Bits       | Description / Values                                                                                                                                                                              |
|----------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mono_block     | 1           | mono_frame == 0: CPE coded with joint-stereo RLS<br>mono_frame == 1: CPE coded with mono RLS                                                                                                      |
| ext_mode       | 1           | RLS-LMS predictor parameters are updated in extension block.<br><br>1 == extension block<br>0 == non-extension block                                                                              |
| extension_bits | 3           | Type of RLS-LMS parameters carried in extension block<br><br>extension&01 == RLS-LMS predictors orders<br>extension&02 == RLS_lambda and RLS_lambda_ra<br>extension&04 == LMS_mu and LMS_stepsize |
| RLS_order      | 4           | RLS predictor order                                                                                                                                                                               |
| LMS_stage      | 3           | Number of LMS predictors in cascade                                                                                                                                                               |
| LMS_order[]    | 5*LMS_stage | LMS predictor order                                                                                                                                                                               |
| RLS_lambda     | 10          | RLS predictor parameter lambda.                                                                                                                                                                   |
| RLS_lambda_ra  | 10          | RLS predictor parameter lambda for random access frame                                                                                                                                            |
| LMS_mu[]       | 5*LMS_stage | LMS predictor parameter – NLMS stepsize                                                                                                                                                           |
| LMS_stepsize   | 3           | Linear combiner parameter – Sign-Sign LMS stepsize                                                                                                                                                |

Page 33, 11.6.1.2, add at the top of the list of bullet items:

- ALS identifier: This field must contain the value 1095521024 = 0x414C5300 (Hex). Using byte-wise reading, the first three bytes are equivalent to the ASCII codes for 'ALS'.

Page 34, 11.6.1.3, replace the pseudo code with the following pseudo code:

```

N = frame_length + 1.
frames = samples / N;
remainder = samples % N;
if (remainder)
{
    frames++;
    N_last = remainder;
}
else
    N_last = N;

```

and add the following paragraphs at the end of the subclause:

If the value of samples is 0xFFFFFFFF (Hex), the number of samples is not specified. If the ALS payload is stored using the MPEG-4 file format, the number of samples can be obtained from the meta data of the file. In that case, the number of frames and the length of the last frame are determined as described above.

If the number of samples is not available, the number of frames is undefined, and all frames are assumed to have the same length N. In that case, the sizes of random access units shall not be stored in ALSSpecificConfig (i.e. only ra\_flag = 0 or ra\_flag = 1 shall be used), since the number of random access units is undefined as well.

Page 37, 11.6.2, immediately before Table 11.18, add:

The frame length N must be divisible by  $2^{\text{levels}}$  without remainder, in order to obtain integer block lengths  $N_B$ .

Page 43, 11.6.3.2.1, replace:

The following algorithm describes the calculation of the residual  $d$  for an input signal  $x$ , a predictor order  $K$  and LPC coefficients  $\text{cof}$ .

with:

The following algorithm describes the calculation of the residual  $d$  for an input signal  $x$ , a block length  $N$ , a predictor order  $K$  and LPC coefficients  $\text{cof}$ .

Page 44, 11.6.3.2.1, second pseudo-code listing and Page 45, 11.6.3.2.2, second pseudo-code listing, replace in both cases the fourth line:

```

for (n = 0; n < K; n++)

```

with:

```

for (n = 0; n < min(K, N); n++)

```

Page 48, replace 11.6.5 entirely, with the following text:

#### 11.6.5 RLS-LMS Predictor

This subclause describes the backward-adaptive prediction scheme that uses adaptive RLS-LMS predictor. Block diagram of the corresponding encoder and decoder are shown in Figure 11.8 and Figure 11.9, respectively.




Figure 11.8 — Encoder of the RLS-LMS backward-adaptive prediction scheme

In the encoder, the RLS-LMS predictor generates an estimate of the current input audio sample by using the past samples. This estimate is subtracted from the current sample to generate the residual, which is subsequently coded by the entropy encoder (11.6.6) to form the ALS bit-stream.




Figure 11.9 — Decoder of the RLS-LMS backward-adaptive prediction scheme

In the decoder, a reverse process is performed. The entropy decoder decodes the ALS bit-stream to the residual, which is then added to the estimate of the RLS-LMS predictor to re-generate the original audio sample.

As shown in Figure 11.10, the RLS-LMS predictor consists of a cascade of predictors in the order of a Differential Pulse Code Modulation (DPCM) predictor (11.6.5.1), a Recursive Least Square (RLS) predictor (11.6.5.2), and a series of Least Mean Square (LMS) predictors (11.6.5.3). The input samples sequentially pass through the cascade of predictors. The residual of one predictor serves as the input to the next predictor. The estimates from the predictors in the cascade are weighted and added together by a linear combiner (11.6.5.4) to generate the final estimate of the current input sample.




Figure 11.1 — Block diagram of the RLS-LMS predictor

The RLS-LMS predictor can be turned on/off by setting RLSLMS in ALSSpecificConfig() to 1/0, respectively.

### 11.6.5.1 DPCM Predictor

**Input:**  $x(n)$  original audio sample

**Residual:**  $e_1(n)$  as input to the RLS predictor

**Estimate:**  $y_1(n)$  as input to the linear combiner

The DPCM predictor is the first predictor in the RLS-LMS predictor cascade. It is a simple first-order predictor with coefficient set to unity, i.e., the previous input sample is used as the estimate of the current input sample. This is illustrated as follows:

$$y_1(n) = x(n-1)$$

where  $y_1(n)$  is the estimate by the DPCM predictor, and  $x(n-1)$  is the previous input sample.

### 11.6.5.2 RLS Predictor

**Input:**  $e_1(n)$  residual of DPCM predictor

**Residual:**  $e_2(n)$  as input to the LMS predictor

**Estimate:**  $y_2(n)$  as input to the linear combiner

The RLS predictor is the second predictor in the RLS-LMS predictor cascade. The RLS algorithm is used to adapt the predictor weights. The algorithm is initialized by setting the  $M \times M$  inverse auto-correlation matrix  $\mathbf{P}$  to a predetermined value as follows:

$$\mathbf{P}(0) = \delta \mathbf{I}$$

where  $\delta$  is a small positive number,  $\mathbf{I}$  is an  $M \times M$  identity matrix, and  $M$  is the RLS predictor order.

The weight vector of the RLS predictor, defined as

$$\mathbf{w}_{\text{RLS}}(n) = [w_{\text{RLS},1}(n), w_{\text{RLS},2}(n), \dots, w_{\text{RLS},M}(n)]^T$$

is initialized by

$$\mathbf{w}_{\text{RLS}}(0) = 0$$

For each time index  $n$ ,  $n = 1, 2, \dots$ , the following calculations are made

$$\mathbf{v}(n) = \mathbf{P}(n-1)\mathbf{e}_1(n)$$

where  $\mathbf{e}_1(n)$  is the RLS predictor input vector defined as

$$\mathbf{e}_1(n) = [e_1(n-1), e_1(n-2), \dots, e_1(n-M)]^T$$

and

$$m = \begin{cases} \frac{1}{\mathbf{e}_1^T(n)\mathbf{v}(n)} & \text{if } \mathbf{e}_1^T(n)\mathbf{v}(n) \neq 0 \\ 1 & \text{else} \end{cases}$$

$$\mathbf{k}(n) = m \mathbf{v}(n)$$

$$y_2(n) = \mathbf{w}_{\text{RLS}}^T(n-1)\mathbf{e}_1(n)$$

$$e_2(n) = e_1(n) - y_2(n)$$

$$\mathbf{w}_{\text{RLS}}(n) = \mathbf{w}_{\text{RLS}}(n-1) + \mathbf{k}(n)e_2(n)$$

$$\mathbf{P}(n) = \text{Tri}\{\lambda^{-1}(\mathbf{P}(n-1) - \mathbf{k}(n)\mathbf{v}^T(n))\}$$

where  $\mathbf{k}(n)$  is the  $M \times 1$  gain vector,  $\lambda$  is the forgetting factor that is a positive value slightly smaller than 1,  $T$  is the transpose symbol, and  $\text{Tri}\{\ast\}$  denotes the operation to compute the lower triangular part of  $\mathbf{P}(n)$  and fill the upper triangular part of the matrix with the same values as in the lower triangular part. In other words, the value of  $\mathbf{P}(n)$  at the  $i$ -th row and  $j$ -th column ( $i > j$ ) is copied to the value of  $\mathbf{P}(n)$  at the  $j$ -th row and  $i$ -th column.

### 11.6.5.2.1 Joint-Stereo RLS Predictor

For a channel pair element (CPE), if `joint_stereo` in `ALSSpecificConfig()` is set to 1, the RLS predictor will work in the joint-stereo mode. In the joint-stereo mode, the RLS predictor employs both intra-channel prediction and inter-channel prediction. Figure 11.11 shows the joint-stereo RLS predictor for the left audio channel.




Figure 11.11 — Joint-stereo RLS predictor for L channel

As shown in the figure, the input signals to the predictor are L channel DPCM predictor residual  $e_{L,1}(n)$  and R channel DPCM predictor residual  $e_{R,1}(n)$ . The joint-stereo predictor consists of an intra-channel predictor  $\mathbf{a}_L$  and an inter-channel predictor  $\mathbf{b}_L$ . The intra-channel predictor  $\mathbf{a}_L$  generates an estimate of the L channel current input sample  $e_{L,1}(n)$  from past samples  $e_{L,1}(n-1)$ ,  $e_{L,1}(n-2)$ , ...,  $e_{L,1}(n-M/2)$ , where  $M$  is the order of the joint-stereo RLS predictor. At the same time, the inter-channel predictor  $\mathbf{b}_L$  generates another estimate of  $e_{L,1}(n)$  from R channel past input samples  $e_{R,1}(n-1)$ ,  $e_{R,1}(n-2)$ , ...,  $e_{R,1}(n-M/2)$ . These two estimates are added together. The result  $y_{L,1}(n)$  is the estimate of the L channel joint-stereo RLS predictor. This process is represented as

$$y_{L,1}(n) = \sum_{m=1}^{M/2} a_{L,m} e_{L,1}(n-m) + \sum_{m=1}^{M/2} b_{L,m} e_{R,1}(n-m)$$

Where  $a_{L,m}$  are coefficients of the intra-channel predictor  $\mathbf{a}_L$ ,  $b_{L,m}$  are coefficients of the inter-channel predictor  $\mathbf{b}_L$ . In the equation, the first summation term is the intra-channel predictor estimate, and the second summation term is the inter-channel predictor estimate. The residual  $e_{L,2}(n)$  is generated by subtracting estimate  $y_{L,1}(n)$  from  $e_{L,1}(n)$  as

$$e_{L,2}(n) = e_{L,1}(n) - y_{L,1}(n)$$

The L channel joint-stereo RLS predictor is updated by the RLS algorithm given in 11.6.5.2, where the weight vector, input vector, and residual in the RLS algorithm are redefined as follows:

$$\mathbf{w}_{\text{RLS}}(n) = [b_{L,1}, a_{L,1}, b_{L,2}, a_{L,2}, \dots, b_{L,M/2}, a_{L,M/2}]^T$$

$$\mathbf{e}_1(n) = [e_{R,1}(n-1), e_{L,1}(n-1), e_{R,1}(n-2), e_{L,1}(n-2), \dots, e_{R,1}(n-M/2), e_{L,1}(n-M/2)]^T$$

$$e_2(n) = e_{L,2}(n)$$

The joint-stereo predictor for the right audio channel is shown in Figure 11.12.




Figure 11.12 — Joint-stereo RLS predictor for R channel

As shown in the figure, the input signals to the predictor are L channel DPCM predictor residual  $e_{L,1}(n)$  and R channel DPCM predictor residual  $e_{R,1}(n)$ . The joint-stereo RLS predictor consists of an intra-channel predictor  $\mathbf{a}_R$  and an inter-channel predictor  $\mathbf{b}_R$ . The intra-channel  $\mathbf{a}_R$  predictor generates an estimate of the R channel current input sample  $e_{R,1}(n)$  from past samples  $e_{R,1}(n-1)$ ,  $e_{R,1}(n-2)$ , ...,  $e_{R,1}(n-M/2)$ , where  $M$  is the order of the joint-stereo RLS predictor. At the same time, the inter-channel predictor  $\mathbf{b}_R$  generates another estimate of  $e_{R,1}(n)$  from L channel input samples  $e_{L,1}(n)$ ,  $e_{R,1}(n-1)$ , ...,  $e_{R,1}(n-M/2+1)$ . These two estimates are added together. The result  $y_{R,1}(n)$  is the estimate of the R-channel joint-stereo RLS predictor. This process is represented as

$$y_{R,1}(n) = \sum_{m=1}^{M/2} a_{R,m} e_{R,1}(n-m) + \sum_{m=0}^{M/2-1} b_{R,m} e_{L,1}(n-m)$$

where  $a_{R,m}$  are coefficients of the intra-channel predictor  $\mathbf{a}_R$ ,  $b_{R,m}$  are coefficients of the inter-channel predictor  $\mathbf{b}_R$ . In the equation, the first summation term is the intra-channel predictor estimate, and the second summation term the inter-channel predictor estimate. The residual  $e_{R,2}(n)$  is generated by subtracting estimate  $y_{R,1}(n)$  from  $e_{R,1}(n)$ , that is

$$e_{R,2}(n) = e_{R,1}(n) - y_{R,1}(n)$$

The R channel joint-stereo RLS predictor is updated by the RLS algorithm given in 11.6.5.2, where the weight vector, input vector, and residual in the RLS algorithm are redefined as follows:

$$\begin{aligned} \mathbf{w}_{\text{RLS}}(n) &= [b_{L,0}, a_{L,1}, b_{L,1}, a_{L,2}, \dots, b_{L,M/2-1}, a_{L,M/2}]^T \\ \mathbf{e}_1(n) &= [e_{L,1}(n), e_{R,1}(n-1), e_{L,1}(n-1), e_{R,1}(n-2), \dots, e_{L,1}(n-M/2+1), e_{R,1}(n-M/2)]^T \\ e_2(n) &= e_{R,2}(n) \end{aligned}$$

The decoder processes a CPE in the order of LRLRLR.... The current L channel sample is always decoded before the current R channel sample.

#### 11.6.5.2.2 Mono RLS Predictor

For a single channel element (SCE), the RLS predictor operates in the mono mode. In the mono mode, the RLS predictor is updated by the RLS algorithm given in 11.6.5.2.

For a CPE, if `joint_stereo` in `ALSSpecificConfig()` is set to 0, mono RLS is used for each individual channel in the CPE. For a CPE, if `mono_block` in `RLSLMS_extension()` is set to 1, the CPE will be coded as two individual channels L and L-R. The L channel is treated as a SCE, whereas the difference channel L-R goes directly to the entropy encoder. For a SCE, if an input frame contains only constant values, the RLS-LMS predictor is bypassed for that frame. For a CPE, if both channels contain only constant values, the RLS-LMS predictor is bypassed for the frame.

#### 11.6.5.2.3 Filtering Operation in RLS predictor

The following pseudo code illustrates how an order- $M$  RLS predictor generates the estimate signal. The order of the RLS predictor is defined in 11.6.5.6.1.

| Pseudo code                                                                                                          | Comments                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 *w, *buf; INT64 temp = 0;  for (i=0; i&lt;M; i++)     temp += (INT64) w[i] * buf[i]; </pre>              | <p>w is RLS predictor weight vector (.16 format)<br/>buf is RLS predictor input vector (.0 format)</p> <p>temp = w * buf</p> |
| <pre> temp &gt;= 12;  if (temp&gt;0x40000000) temp = 0x40000000; if (temp&lt;-0x40000000) temp = -0x40000000; </pre> | <p>temp is .4 format</p> <p>Limit the range of temp to<br/>[-0x40000000, 0x40000000]</p>                                     |
| <pre> INT32 y;  y = (INT32) (temp); </pre>                                                                           | <p>y is RLS predictor estimate (.4 format)</p>                                                                               |

#### 11.6.5.2.4 Weight Adaptation in RLS predictor

The following pseudo code illustrates how the weight vector of an order-M RLS predictor is updated.

| Pseudo code                                                                                                | Comments                                                                                                                                                                                             |
|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 x, y, e;  e = x - y; </pre>                                                                    | <p>x is RLS predictor current input sample<br/>x is .4 format<br/>y is RLS predictor estimate (.4 format)<br/>e is RLS predictor residual (.4 format)</p>                                            |
| <pre> INT64 **P; INT32 *buf, *v; INT16 vs;  [v, vs] = MulMtxVec(P, buf); </pre>                            | <p>P is RLS algorithm matrix P (.60 format)<br/>buf is RLS predictor input vector (.0 format)<br/>v is RLS algorithm vector v<br/>vs is a scale factor</p> <p>v = P*buf<br/>v is .(28-vs) format</p> |
| <pre> INT64 temp; INT16 ds;  [temp, ds] = MulVecVec(buf, v); </pre>                                        | <p>ds is a scale factor</p> <p>temp = buf * v<br/>temp is .(60-vs-ds) format</p>                                                                                                                     |
| <pre> i = 0; while (temp&gt;0x20000000 &amp;&amp; temp!=0)     temp &gt;&gt;= 1; i++; i += vs + ds; </pre> | <p>temp is .(60-i) format</p>                                                                                                                                                                        |
| <pre> if (i&lt;=60)     temp += (((INT64) 1) &lt;&lt; (60-i)); else     reinit_P(P); </pre>                | <p>If (i&lt;=60)<br/>temp = temp + 1<br/>else<br/>Re-initialize matrix P</p>                                                                                                                         |

|                                                                                                                                                                                                                                                                                                         |                                                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT64 mm; INT32 m;  if (temp==0)     mm = 1L&lt;&lt;30; else if (i&lt;=28)     shift = 28-i;     mm = (((INT64)1)&lt;&lt;62) / temp;     if (shift&gt;32)         mm = 1L&lt;&lt;30;     else         mm &lt;=&lt; shift; else     mm = (((INT64)1)&lt;&lt;(90-i)) / temp;  m = (INT32)mm; </pre> | <p>m is the RLS algorithm variable m</p> <pre> If (temp==0)     m = 1; else     m = 1/temp; </pre> <p>m is .30 format</p>    |
| <pre> INT32 *k;  for (i=0; i&lt;M; i++)     temp = (INT64) v[i] * m;     if (vs&gt;=12)         k[i] = temp&lt;&lt;(vs-12);     else         k[i] = temp&gt;&gt;(11-vs);         k[i] = ROUND2(k[i]); </pre>                                                                                            | <p>k is the RLS algorithm gain vector k</p> <pre> k = m * v </pre> <p>Scale k</p> <p>k is .46 format</p>                     |
| <pre> temp = 0; for (i=0; i&lt;M; i++)     temp  = (k[i]&gt;0 ? k[i]:-k[i]); ds = fast_bitcount(temp); if (ds&gt;30)     ds -= 30;     for (i=0; i&lt;M; i++) k[i] &gt;&gt;= ds; else     ds = 0; </pre>                                                                                                | <p>Obtain MSB in k<br/>Get position of MSB bit</p> <p>Scale k</p> <p>k is .(46-ds) format</p>                                |
| <pre> INT32 *w;  for (i=0; i&lt;M; i++)     temp = (((INT64) k[i] * (e&gt;&gt;3))&gt;&gt;(30-ds));     temp = w[i] + ROUND2(temp);     w[i] = (long) temp;     vs += ds; </pre>                                                                                                                         | <p>w is RLS predictor weight vector</p> <p>Update RLS weight vector<br/> <math>w = w + k * e</math><br/> w is .16 format</p> |

|                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT16 lambda;  for (i=0; i&lt;M; i++)   for (j=0; j&lt;=i; j++)     temp = ((INT64) k[i] * v[j])&gt;&gt;(14-vs);     P[i][j] -= temp;     if (P[i][j]&gt;=0x4000000000000000            P[i][j]&lt;=-0x4000000000000000)       reinit_P(P); break;     temp = P[i][j] / lambda;     P[i][j] += temp; </pre> | <p>lambda is defined in 11.6.5.6.6</p> <p>Update matrix P (lower triangular)</p> <p><math>P = P - k * v</math><br/> <math>P = P * (1+1/\lambda)</math><br/> P is .60 format</p> |
| <pre> for (i=1; i&lt;M; i++)   for (j=0; j&lt;i; j++)     P[j][i] = P[i][j]; </pre>                                                                                                                                                                                                                               | Update matrix P (upper triangular)                                                                                                                                              |
| <pre> for (i=M-1; i&gt;0; i--)   buf[i] = buf[i-1]; buf[0] = x&gt;&gt;4; </pre>                                                                                                                                                                                                                                   | <p>Update RLS predictor input vector</p> <p>buf is .0 format</p>                                                                                                                |

| Pseudo code                                                                                                                                                           | Comments                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| <pre> [INT32 *v, INT16 vs] = MulMtxVec(INT64 **P, INT32 *buf); </pre>                                                                                                 | <p>Multiply matrix P by buf,<br/> Return the result in v<br/> P is .60 format, buf is .0 format</p>            |
| <pre> INT64 temp=0; INT16 ps;  for(i=0; i&lt;M; i++)   for(j=0; j&lt;=i; j++)     temp  = (P[i][j]&gt;0 ? P[i][j] : -P[i][j]);  ps = 63 - fast_bitcount(temp); </pre> | <p>ps is a scale factor</p> <p>Obtain MSB in matrix P</p> <p>Calculate the shift needed<br/> to maximize P</p> |
| <pre> INT64 *u;  for (i=0; i&lt;M; i++)   u[i]=0;   for (j=0; j&lt;M; j++) u[i] +=     (INT64) (((P[i][j]&lt;&lt;ps)+(INT64)0x80000000)&gt;&gt;32) * buf[j]; </pre>   | <p><math>u = P * buf</math><br/> u is .(28+ps) format.</p>                                                     |
| <pre> INT16 ns;  temp =0; for (i=0; i&lt;M; i++)   temp  = (u[i]&gt;0 ? u[i] : -u[i]);  ns = fast_bitcount(temp); </pre>                                              | <p>ns is a scale factor</p> <p>Obtain MSB</p> <p>Get the position of MSB bit</p>                               |

|                                                                                                                                                                                                       |                                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| <pre> if (ns&gt;28)     ns -= 28;     for(i=0; i&lt;M; i++)         v[i] = (INT32) (u[i]&gt;&gt;ns);     vs = ns - ps; else     for(i=0;i&lt;M;i++)         v[i] = (INT32) u[i];     vs = -ps; </pre> | <p>Scale v</p> <p>v is .(28-vs) format</p> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|

| Pseudo code                                                                                                                         | Comments                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <code>[INT64 z, INT16 ds] = MulVecVec(INT32 *buf, INT32 *v)</code>                                                                  | Compute inner product of buf and v, return the result in z<br>buf is .0 format, v is .(28-vs) format |
| <pre> INT 64 z = 0;  for (i=0; i&lt;M; i++)     z += (INT64) buf[i] * v[i]; </pre>                                                  | $z = \text{buf} \cdot v$                                                                             |
| <pre> INT64 temp;  temp = (z&gt;0 ? z : -z); ds = fast_bitcount(temp); </pre>                                                       | Get the position of MSB bit                                                                          |
| <pre> if (ds&gt;28)     ds -= 28;     z = (z&lt;&lt;(32-(ds-1)));     z = ROUND2(z); else     ds = 0;     z = (z&lt;&lt;32); </pre> | <p>Scale z</p> <p>z is .(60-vs-ds) format</p>                                                        |

| Pseudo code                                                                         | Comments                           |
|-------------------------------------------------------------------------------------|------------------------------------|
| <code>reinit_P(INT64 **P)</code>                                                    | Re-initialize matrix P             |
| <pre> for (i=0; i&lt;M; i++)     for (j=0; j&lt;M; j++)         P[i][j] = 0; </pre> | Clear P to zero                    |
| <pre> for (i=0; i&lt;M; i++)     P[i][i] = (INT64) JS_INIT_P; </pre>                | Initialize the diagonal components |

| Pseudo code                                                                                                                                          | Comments                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| [INT16 count] = fast_bitcount (INT64 temp)                                                                                                           | Return the MSB bit position |
| <pre> i = 56; j = 0; while((temp&gt;&gt;i)==0 &amp;&amp; i&gt;0) i -= 8; temp&gt;&gt;=i; while(temp&gt;0) temp&gt;&gt;=1; j++; count = i + j; </pre> |                             |

The RLS predictor can be turned off by setting RLS\_order to zero. In this case, the RLS predictor estimate  $y_2(n)$  is set to zero.

### 11.6.5.3 LMS Predictors

**Input:**  $e_{k-1}(n)$  residual of the previous predictor (could be RLS predictor or LMS predictor)

**Residual:**  $e_k(n)$  as input to the next LMS predictor

**Estimate:**  $y_k(n)$  as input to the linear combiner

The RLS-LMS predictor contains a series of LMS predictors. The Normalized LMS (NLMS) algorithm is used to adapt the predictor weights. For an order-M LMS predictor, its weight vector

$$\mathbf{w}_{\text{LMS}}(n) = [w_{\text{LMS},1}(n), w_{\text{LMS},2}(n), \dots, w_{\text{LMS},M}(n)]^T$$

is initialized by

$$\mathbf{w}_{\text{LMS}}(n) = 0$$

For each time index  $n$ ,  $n = 1, 2, \dots$ , the estimate is calculated as

$$y_k(n) = \mathbf{w}_{\text{LMS}}^T(n) \mathbf{e}_{k-1}(n)$$

where  $\mathbf{e}_{k-1}(n)$  is the input vector defined as

$$\mathbf{e}_{k-1}(n) = [e_{k-1}(n-1), e_{k-1}(n-2), \dots, e_{k-1}(n-M)]^T$$

The LMS predictor weight vector is updated according to

$$e_k(n) = e_{k-1}(n) - y_k(n)$$

$$\mathbf{w}_{\text{LMS}}(n) = \mathbf{w}_{\text{LMS}}(n-1) + \frac{e_k(n) \mathbf{e}_{k-1}(n)}{2^7 + \mu_k \mathbf{e}_{k-1}^T(n) \mathbf{e}_{k-1}(n)}$$

where  $\mu_k$  is the NLMS stepsize (Clause 0).

#### 11.6.5.3.1 Filtering operation in LMS Predictor

The following pseudo code illustrates how an order-M LMS predictor generates the estimate signal. The order of the LMS predictor is defined in Clause 0.

| Pseudo code                                                                                                      | Comments                                                                                                                     |
|------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 *w, *buf; INT64 temp = 0;  for (i=0; i&lt;M; i++)     temp += (INT64) w[i] * buf[i]; </pre>          | <p>w is LMS predictor weight vector (.24 format)<br/>buf is LMS predictor input vector (.0 format)</p> <p>temp = w * buf</p> |
| <pre> temp &gt;&gt;= 20;  if (temp&gt;0x7fffff) temp = 0x7fffff; if (temp&lt;-0x7fffff) temp = -0x7fffff; </pre> | <p>temp is .4 format</p> <p>Limit the range of temp to<br/>[-0x7fffff, 0x7fffff]</p>                                         |
| <pre> INT32 y;  y = (INT32) (temp); </pre>                                                                       | <p>y is LMS predictor estimate (.4 format)</p>                                                                               |

#### 11.6.5.3.2 Weight adaptation in LMS Predictor

The following pseudo code illustrates how the weight vector of an order-M LMS predictor is updated.

| Pseudo code                                                                                                                                                       | Comments                                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 x, y, e;  e = x - y; </pre>                                                                                                                           | <p>x is LMS predictor current input sample (.4 format)<br/>y is LMS predictor estimate (.4 format)<br/>e is LMS predictor residual (.4 format)</p> |
| <pre> INT32 *buf; INT64 pow = 0;  for (i=0; i&lt;M; i++)     pow += (INT64) buf[i] * buf[i];  if (pow&gt;0x4000000000000000)     pow = 0x4000000000000000; </pre> | <p>buf is LMS predictor input vector (.0 format)</p> <p>Compute total signal power in buf<br/>pow = buf * buf</p> <p>pow is .0 format</p>          |
| <pre> INT16 mu; INT64 temp, temp1;  temp = (INT64) mu * (pow&gt;&gt;7); temp1 = temp; </pre>                                                                      | <p>mu is NLMS algorithm stepsize (.0 format)<br/>mu is defined in xxx.yyy</p> <p>temp = mu * pow<br/>temp is .(-7) format</p>                      |
| <pre> i = 0; while(temp&gt;0x7fffff) temp&gt;&gt;=1; i++;  temp = ((INT64) e&lt;&lt;(29-i)) / (INT64)((temp1+1)&gt;&gt;i); </pre>                                 | <p>Compute the number of shifts needed<br/>to shift temp into the lower 32 bit</p> <p>temp = e / (128 + mu*buf*buf)<br/>temp is .40 format</p>     |

|                                                                                                               |                                                                                                                                                |
|---------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 *w;  for (i=0; i&lt;M;i++) w[i] +=   (INT32) (((INT64) buf[i] * temp + 0x8000)&gt;&gt;16); </pre> | <p>w is LMS predictor weight vector (.24 format)</p> <p>Update weight vector<br/> <math>w = w + (buf * e) / (128 + \mu * buf * buf)</math></p> |
| <pre> for (i=M-1; i&gt;0; i--)   buf[i] = buf[i-1]; buf[0] = x&gt;&gt;4; </pre>                               | <p>Update the input vector</p> <p>buf is .0 format</p>                                                                                         |

#### 11.6.5.4 Linear Combiner

**Input:**  $y_1(n), y_2(n), \dots, y_K(n)$  estimates from DPCM, RLS, and LMS predictors

**Output:**  $\hat{x}(n)$  final estimate of the RLS-LMS predictor

The linear combiner multiplies the estimates from the DPCM, RLS, and LMS predictors by a set of weights. The results are summed together to provide the final estimate of the RLS-LMS predictor. The Sign-Sign LMS algorithm is used to update the linear combiner weights. If there are in total K predictors in the RLS-LMS predictor cascade, the linear combiner weight vector is given by

$$\mathbf{c}(n) = [c_1(n), c_2(n), \dots, c_K(n)]^T$$

The linear combiner input vector is given by

$$\mathbf{y}(n) = [y_1(n), y_2(n), \dots, y_K(n)]^T$$

The final estimate of the RLS-LMS predictor is given by

$$\hat{x}(n) = \mathbf{c}^T(n) \mathbf{y}(n)$$

The linear combiner weight vector is updated by the Sign-Sign LMS algorithm

$$\mathbf{c}(n) = \mathbf{c}(n-1) + \alpha \operatorname{sgn}\{\mathbf{y}(n)\} \operatorname{sgn}\{x(n) - \hat{x}(n)\}$$

where  $x(n)$  is the RLS-LMS predictor current input sample,  $\alpha$  is the Sign-Sign LMS stepsize (11.6.5.6.5). The  $\operatorname{sgn}\{\cdot\}$  function is defined as

$$\operatorname{sgn}\{r\} = \begin{cases} 1 & r > 0 \\ 0 & r = 0 \\ -1 & r < 0 \end{cases}$$

The following pseudo code illustrates how an order-K linear combiner generates the final estimate of the RLS-LMS predictor. The order of linear combiner is given by (LMS\_stage+2). The code also shows how the linear combiner weight vector is updated. It shall be noted that the first two linear combiner weights are not updated.

| Pseudo code                                                                                                                                                                                                                                                      | Comments                                                                                                                                                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre> INT32 *c, *y; INT64 xhat = 0;  for (i=0; i&lt;K; i++)     xhat += (INT64) c[i] * y[i]; xhat &gt;&gt;= 24 ; </pre>                                                                                                                                          | <p>c is linear combiner weight vector (.24 format)<br/> y is linear combiner input vector (.4 format)<br/> xhat is linear combiner output, i.e., final estimate of RLS-LMS predictor.</p> <p>xhat is .4 format</p> |
| <pre> INT32 x; INT64 r;  r = (x&lt;&lt;4) - xhat; </pre>                                                                                                                                                                                                         | <p>x is RLS-LMS predictor current input sample<br/> x is .0 format</p> <p>Compute the difference between x and xhat<br/> r is .4 format</p>                                                                        |
| <pre> INT32 LMS_stepsize; INT64 temp;  for (i=2; i&lt;K; i++)     temp = (INT64) r * y[i];     if (temp&gt;0 &amp;&amp; c[i]&lt;0x40000000)         c[i] += LMS_stepsize;     if (temp&lt;0 &amp;&amp; c[i]&gt;-0x40000000)         c[i] -= LMS_stepsize; </pre> | <p>Sign-Sign LMS algorithm stepsize (.24 format)<br/> LMS_stepsize is defined in 11.6.5.6.5</p> <p>Sign-Sign LMS algorithm</p> <p>Only update linear combiner weights for the LMS predictors</p>                   |
| <pre> INT32 e;  e = x - ROUND1(xhat) </pre>                                                                                                                                                                                                                      | <p>e is RLS-LMS predictor residual (.0 format)</p>                                                                                                                                                                 |

#### 11.6.5.5 RLS-LMS Predictor Initialization

The RLS-LMS predictor is initialized at the following moments: start of encoding, start of decoding, start of each random access (RA) frame, and whenever filter order changes. The RLS-LMS predictor is initialized by zero-filling the following buffers: DPCM predictor previous input sample, RLS predictor input vector and weight vector, all LMS predictor input vectors and weight vectors, and linear combiner input vector. The RLS predictor P matrix is initialized by calling function reinit\_P(P). The linear combiner weight vector is set to constant FRACTION, which represents 1.0 in 8.24 format.

Table 11.27 lists the constants and macros used by the RLS-LMS predictor.

**Table 11.27 — Constants and Macros**

| Constants & Macros | Value                                | Comments              |
|--------------------|--------------------------------------|-----------------------|
| JS_INIT_P          | 115292150460684                      | 0.0001 in 4.60 format |
| FRACTION           | (1L<<24)                             | 1.0 in 8.24 format    |
| ROUND1(x)          | ((INT32) ((x+8)>>4))                 | Rounding function     |
| ROUND2(x)          | ((INT64) ((INT64) x + (INT64) 1)>>1) | Rounding function     |

### 11.6.5.6 RLS-LMS Predictor Parameters

The parameters of the RLS-LMS predictor can be changed every frame. This is signalled in `RLSLMS_extension()` when `ext_mode` = 1. Sub-sections 11.6.5.6.1 to 11.6.5.6.6 describe the RLS-LMS predictor parameters that can be changed.

#### 11.6.5.6.1 RLS\_order

This parameter specifies the order of the RLS predictor. Valid values and the corresponding 4-bit indices are listed in Table 11.28.

**Table 11.28 — RLS\_order**

| index | RLS_order | index | RLS_order |
|-------|-----------|-------|-----------|
| 0     | 0         | 8     | 16        |
| 1     | 2         | 9     | 18        |
| 2     | 4         | 10    | 20        |
| 3     | 6         | 11    | 22        |
| 4     | 8         | 12    | 24        |
| 5     | 10        | 13    | 26        |
| 6     | 12        | 14    | 28        |
| 7     | 14        | 15    | 30        |

#### 11.6.5.6.2 LMS\_stage

This parameter specifies the number of LMS predictors in the RLS-LMS predictor cascade. Valid values and the corresponding 3-bit indices are listed in Table 11.29.

**Table 11.29 — LMS\_stage**

| index | LMS_stage |
|-------|-----------|
| 0     | 1         |
| 1     | 2         |
| 2     | 3         |
| 3     | 4         |
| 4     | 5         |
| 5     | 6         |
| 6     | 7         |
| 7     | 8         |

**11.6.5.6.3 LMS\_order**

This parameter specifies the order of the LMS predictor. Valid values and the corresponding 5-bit indices are listed in Table 11.30.

**Table 11.30 — LMS\_order**

| index | LMS_order | index | LMS_order |
|-------|-----------|-------|-----------|
| 0     | 2         | 16    | 32        |
| 1     | 3         | 17    | 36        |
| 2     | 4         | 18    | 48        |
| 3     | 5         | 19    | 64        |
| 4     | 6         | 20    | 80        |
| 5     | 7         | 21    | 96        |
| 6     | 8         | 22    | 128       |
| 7     | 9         | 23    | 256       |
| 8     | 10        | 24    | 384       |
| 9     | 12        | 25    | 448       |
| 10    | 14        | 26    | 512       |
| 11    | 16        | 27    | 640       |
| 12    | 18        | 28    | 768       |
| 13    | 20        | 29    | 896       |
| 14    | 24        | 30    | 1024      |
| 15    | 28        | 31    | reserved  |

**11.6.5.6.4 LMS\_mu**

This parameter specifies the stepsize of NLMS algorithm that is used to update the LMS predictor. Valid values and the corresponding 5-bit indices are listed in Table 11.31.

**Table 11.31 — LMS\_mu**

| index | LMS_mu | index | LMS_mu |
|-------|--------|-------|--------|
| 0     | 1      | 16    | 18     |
| 1     | 2      | 17    | 20     |
| 2     | 3      | 18    | 22     |
| 3     | 4      | 19    | 24     |
| 4     | 5      | 20    | 26     |
| 5     | 6      | 21    | 28     |
| 6     | 7      | 22    | 30     |
| 7     | 8      | 23    | 35     |
| 8     | 9      | 24    | 40     |
| 9     | 10     | 25    | 45     |
| 10    | 11     | 26    | 50     |
| 11    | 12     | 27    | 55     |