

AS1733		REV. D									
TABLE 1 - BODY DIMENSIONS											
BASIC NO. AS1733 SIZE CODE	(TUBE SIZE)	THREAD PER FED-STD-H28/2	A + .005/- .000	B + .005/- .000	C + .010/- .000	D + .000/- .010	E + .005/- .000	F + .005/- .000	G + .005/- .000	TOL	H
04	.250	.687-12 UN-2A	.680	.529	.480	.298	.233	.375	.254	+ .005/- .000	.720
05	.312	.750-12 UN-2A	.743	.580	.535	.353	.295	.437	.316	+ .005/- .000	.720
06	.375	.812-12 UN-2A	.805	.635	.590	.408	.358	.500	.379	+ .005/- .000	.720
08	.500	.937-12 UN-2A	.930	.762	.716	.534	.483	.625	.504	+ .005/- .000	.720
10	.625	1.062-12 UN-2A	1.055	.900	.850	.668	.609	.750	.630	+ .005/- .000	.735
12	.750	1.250-12 UNF-2A	1.243	1.033	.984	.802	.734	.890	.755	+ .005/- .000	.735
16	1.000	1.500-12 UNF-2A	1.493	1.284	1.235	1.053	.984	1.142	1.005	+ .005/- .000	.735
20	1.250	1.750-12 UN-2A	1.743	1.534	1.485	1.303	1.235	1.392	1.256	+ .005/- .000	.735
24	1.500	2.000-12 UN-2A	1.993	1.783	1.735	1.553	1.480	1.642	1.506	+ .005/- .000	.825
28	1.750	2.250-12 UN-2A	2.243	2.045	1.965	1.783	1.730	1.895	1.756	+ .005/- .000	.835
32	2.000	2.500-12 UN-2A	2.493	2.292	2.235	2.053	1.981	2.145	2.006	+ .005/- .000	.835
36	2.250	2.750-12 UN-2A	2.743	2.545	2.485	2.283	2.231	2.395	2.257	+ .005/- .000	.835
40	2.500	3.000-12 UN-2A	2.993	2.800	2.713	2.531	2.481	2.645	2.507	+ .005/- .000	.835
44	2.750	3.250-12 UN-2A	3.243	3.045	2.961	2.781	2.731	2.895	2.757	+ .005/- .000	.835
48	3.000	3.625-12 UN-2A	3.618	3.395	3.340	3.158	2.979	3.145	3.007	+ .005/- .000	.785
56	3.500	4.125-12 UN-2A	4.118	3.895	3.840	3.658	3.479	3.645	3.509	+ .005/- .000	.785
64	4.000	4.625-12 /10/	4.603	4.395	4.340	4.158	3.979	4.155	4.009	+ .005/- .000	.770
72	4.500	5.125-12 /10/	5.103	4.895	4.840	4.658	4.479	4.655	4.509	+ .006/- .000	.950
80	5.000	5.625-12 /10/	5.602	5.378	5.325	5.143	4.979	5.155	5.009	+ .006/- .000	.950



SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

BODY, COUPLING, RIGID, FIXED CAVITY, THREADED,
FERRULE TYPE TUBE ENDS, TYPE II

AS1733
SHEET 2 OF 4

REV.
D

TABLE 2 - BODY DIMENSIONS AND DESIGN INFORMATION

BASIC NO. AS1733 SIZE CODE			K		M	N PLACES LAND		P PLACES GROOVE		S + .020/- .010	W	X	Y PLACES	O-RINGS DASH NO /11/	WEIGHT LB/EA MAX
J	LENGTH	TOL	K	K											
04	.234	.090	+ .005/- .000	.045	4	4	5	.210	.008/.010	.125	4	.012	.008		
05	.234	.090	+ .005/- .000	.045	4	4	5	.210	.008/.010	.125	4	.013	.009		
06	.234	.090	+ .005/- .000	.045	4	4	5	.210	.008/.010	.125	4	.014	.011		
08	.234	.090	+ .005/- .000	.045	4	4	5	.210	.008/.010	.125	4	.016	.014		
10	.250	.100	± .010	.045	4	4	5	.225	.008/.010	.125	8	.018	.017		
12	.250	.100	± .010	.045	4	4	5	.225	.008/.010	.187	8	.020	.022		
16	.250	.100	± .010	.045	4	4	5	.225	.008/.010	.187	8	.024	.028		
20	.250	.100	± .010	.045	4	4	5	.225	.008/.010	.187	8	.028	.033		
24	.250	.100	± .010	.045	5	5	6	.225	.008/.010	.187	8	.030	.041		
28	.250	.100	± .010	.075	5	5	6	.205	.008/.010	.250	8	.032	.046		
32	.250	.105	± .010	.075	5	5	6	.205	.008/.010	.250	8	.034	.052		
36	.279	.110	± .010	.075	5	5	6	.205	.008/.010	.250	8	.036	.060		
40	.279	.110	± .010	.075	5	5	6	.205	.008/.010	.250	8	.038	.067		
44	.279	.110	± .010	.075	5	5	6	.205	.008/.010	.250	8	.040	.092		
48	.309	.060	± .010	.075	5	5	6	.205	.008/.010	.250	8	.042	.092		
56	.309	.060	± .010	.075	5	5	6	.205	.014/.016	.250	8	.044	.105		
64	.309	.100	± .010	.075	4	4	5	.230	.014/.016	.250	8	.046	.118		
72	.409	.100	± .010	.075	6	6	7	.260	.020/.024	.250	8	.048	.196		
80	.409	.100	± .010	.075	6	6	7	.260	.020/.024	.250	8	.050	.229		