invites your written comments and suggestions

stabilized,

reaffirmed,


be revised,

time it may

every five years at which


least (

AS3105 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.



- FOR PART NUMBERS AS3105-15 THRU AS3105-17 THE THREAD PD SHALL REPLACE DATUM B.
- MATERIAL: CORROSION RESISTANT STEEL AMS 5731.
- MANUFACTURING SPECIFICATION: AMS 7477.
- FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
- SURFACE TEXTURE: ANSI 846,1-1962.
 (3.2 MICROMETRES) EXCEPT UPSET HEAD. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES.
- BREAK SHARP EDGES .903-,015 (0.08-0.38) UNLESS OTHERWISE SPECIFIED.
- DIMENSIONS IN INCHES (MILLIMETRES). METRIC CONVERSIONS ARE INTERNATIONAL SYSTEM UNITS (SI). UNLESS OTHERWISE SPECIFIED, TOLERANCES: ANGULAR DIMENSIONS $\pm 5^\circ$.
- DIMENSIONS AND TOLERANCING: ANSI Y14.5-1973.
- DO NOT USE UNASSIGNED PART NUMBERS.

SAE values your input. To provide feedback on this Technical Report, please visit http://www.sae.org/technical/standards/AS3105



REAFFIRMED 2012-11

1979-07

CUSTODIAN: E-25

AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, PD SHANK, CRES AMS5731, .5625-18 UNJF-3A

SAE AS3105 SHEET 1 OF 2

An SAE International Group

Copyright 2012 SAE International