

Connector Accessories, Electrical, Backshell, Straight, Self-locking and non-self-locking,
Pre-attached shield termination, (EMI/RFI), Boot accommodation, Category 3B
(For MIL-DTL-38999 Series I and II Connectors)

This amendment forms a part of AS85049/112B Dated 2007-06

1). Present Requirement: (Sheet 1)

The requirements for acquiring the accessories described herein shall consist of this specification and the latest issue of: AS85049.

Change Requirement: (sheet 1)

NOTICE

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Rationale for Change: Up-dated the procurement statement to comply with SAE guidelines.

2). Present Requirement: (Material and Finish, Table 3, sheet 3)

TABLE 3 - MATERIAL AND FINISH

FIGURE 1	FINISH DESCRIPTION	BASE MATERIAL	FINISH CODE
ADAPTER & COUPLING NUT	ELECTROLESS NICKEL	ALUMINUM ALLOY	N 1/
	CADMIUM OLIVE DRAB OVER ELECTROLESS NICKEL		W 3/
BAND 4/	TIN	COPPER	
BAND 4/	PASSIVATED	STAINLESS STEEL	
SHIELD 5/	NICKEL	COPPER	K 5/
SHIELD 2/	TIN	COPPER	T 5/
1/ NOT FOR NAVY USE. AIR FORCE USE IS FOR SPACE APPLICATIONS ONLY. W IS THE PREFERRED FINISH. 2/ BRAID SIMILAR TO A-A-59569. WIRE GAGE, NUMBER OF ENDS AND CARRIERS MAY VARY TO OBTAIN 90% COVERAGE. 3/ NOT FOR USE IN SPACE APPLICATIONS. 4/ CHOICE OF BAND IS OPTIONAL. 5/ BRAID WIRE SHALL CONFORM TO ASTM B 33 FOR FINISH 'T' AND ASTM B 355, CLASS 4 FOR FINISH 'K'.			

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/112B_A2