

REV.
B

SAE AS85049/9

FEDERAL SUPPLY CLASS
5935


RATIONALE

THIS REVISION IS REQUIRED TO INCORPORATE THE OUTSTANDING AMENDMENT AND UPDATE TO MEET SAE FORMAT GUIDELINES.

NOTICE

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF SAE AS85049.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




STYLE 1

FIGURE 1 - CONFIGURATION AND DIMENSIONS

SAENORM.COM : Click to view the full PDF of as85049/9

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS85049/9B>



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS85049

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, ENVIRONMENTAL, CABLE SEALING, 90°, CATEGORY 1A (FOR AS50151 CRIMP, MIL-DTL-26482 SERIES 2, AS81703 SERIES 3, AND MIL-DTL-83723 SERIES III CONNECTORS)

SAE AS85049/9
SHEET 1 OF 9

REV. B

Copyright 2011 SAE International


All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada) Fax: 724-776-0790

Tel: 724-776-4970 (outside USA) Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2001-07 REVISED 2011-01



STYLE 2

FIGURE 1 - CONFIGURATION AND DIMENSIONS (CONTINUED)

TABLE 1 - DIMENSIONS

DASH NO.	CONNECTOR SHELL SIZE				CLAMP SIZE	A (SEE NOTE 6)		STYLE	B ±.125	C REF
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	AS50151 CRIMP	MIL-DTL-83723 SERIES III		WIRE BUNDLE ACCOMMODATION RANGE				
						MIN	MAX			
1	3	N/A	N/A	N/A	4	.125 (3.18)	.250 (6.35)	1	1.800 (45.72)	1.027 (26.09)
2					6	.250 (6.35)	.437 (11.10)	2	1.320 (33.53)	1.027 (26.09)
3	N/A	8	8S	8	4	.125 (3.18)	.250 (6.35)	1	1.200 (30.48)	1.027 (26.09)
4					4	.125 (3.18)	.312 (7.92)	1	1.920 (48.77)	1.027 (26.09)
5					6	.250 (6.35)	.375 (9.53)	1	1.320 (33.53)	1.027 (26.09)
6	7	12	12, 12S	12	4	.125 (3.18)	.312 (7.92)	1	1.940 (49.28)	1.027 (26.09)
7					6	.250 (6.35)	.437 (11.10)	1	1.940 (49.28)	1.027 (26.09)
8					10	.350 (8.89)	.500 (12.70)	1	1.335 (33.91)	1.027 (26.09)
9	12	14	14, 14S	14	6	.250 (6.35)	.437 (11.10)	1	2.010 (51.05)	1.027 (26.09)
10					10	.350 (8.89)	.575 (14.61)	1	1.655 (42.04)	1.027 (26.09)
11	19	16	16, 16S	16	6	.250 (6.35)	.437 (11.10)	1	2.100 (53.34)	1.027 (26.09)
12					12	.500 (12.70)	.700 (17.78)	1	1.745 (44.32)	1.059 (26.90)
13	27	18	18	18	10	.350 (8.89)	.625 (15.88)	1	2.270 (57.66)	1.027 (26.09)
14					16	.625 (15.88)	.779 (19.79)	1	1.920 (48.77)	1.156 (29.36)
15	37	20	20	20	10	.350 (8.89)	.625 (15.88)	1	2.270 (57.66)	1.027 (26.09)
16					16	.625 (15.88)	.904 (22.96)	1	1.920 (48.77)	1.156 (29.36)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	D DIA MAX	E ±.125	V THREAD CLASS 2A	F MAX	G DIA MAX	H MAX
1	.669 (16.99)	.636 (16.15)	.625-24 UNEF	1.18 (29.97)	-	1.57 (39.88)
2	.669 (16.99)	1.386 (35.20)	.750-20 UNEF	2.02 (51.31)	.858 (21.79)	2.41 (61.21)
3	.617 (15.67)	.541 (13.74)	.625-24 UNEF	1.09 (27.69)	-	1.48 (37.59)
4	.734 (18.64)	.636 (16.15)	.625-24 UNEF	1.18 (29.97)	-	1.57 (39.88)
5	.734 (18.64)	.636 (16.15)	.750-20 UNEF	1.27 (32.26)	-	1.66 (42.16)
6	.858 (21.79)	.641 (16.28)	.625-24 UNEF	1.18 (29.97)	-	1.57 (39.88)
7	.858 (21.79)	.641 (16.28)	.750-20 UNEF	1.28 (32.51)	-	1.67 (42.42)
8	.858 (21.79)	.641 (16.28)	1.000-20 UNEF	1.37 (34.80)	-	1.76 (44.70)
9	.984 (24.99)	.741 (18.82)	.750-20 UNEF	1.38 (35.05)	-	1.77 (44.96)
10	.984 (24.99)	.741 (18.82)	1.000-20 UNEF	1.47 (37.34)	-	1.86 (47.24)
11	1.112 (28.24)	.926 (23.52)	.750-20 UNEF	1.59 (40.39)	-	1.98 (50.29)
12	1.112 (28.24)	.926 (23.52)	1.1875-18 UNEF	1.77 (44.96)	-	2.16 (54.86)
13	1.218 (30.94)	1.016 (25.81)	1.000-20 UNEF	1.80 (45.72)	-	2.19 (55.63)
14	1.218 (30.94)	1.016 (25.81)	1.4375-18 UNEF	1.97 (50.04)	-	2.36 (59.94)
15	1.345 (34.16)	1.016 (25.81)	1.000-20 UNEF	1.80 (45.72)	-	2.19 (55.63)
16	1.345 (34.16)	1.016 (25.81)	1.4375-18 UNEF	1.97 (50.04)	-	2.36 (59.94)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	CONNECTOR SHELL SIZE				CLAMP SIZE	A (SEE NOTE 6)		STYLE	B ±.125	C REF				
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	AS50151 CRIMP	MIL-DTL-83723 SERIES III		WIRE BUNDLE ACCOMMODATION RANGE								
						MIN	MAX							
17	N/A	22	22	22	12	.500 (12.70)	.750 (19.05)	1	2.380 (60.45)	1.059 (26.90)				
18					20	.875 (22.23)	1.029 (26.14)	1	2.025 (51.44)	1.375 (34.93)				
19					24	24	24	12	.500 (12.70)	.750 (19.05)	1	2.380 (60.45)	1.059 (26.90)	
20		20	.875 (22.23)	1.144 (29.06)				1	2.025 (51.44)	1.375 (34.93)				
21		N/A	28	N/A	N/A	16	.625 (15.88)	.937 (23.80)	1	2.550 (64.77)	1.156 (29.36)			
22						24	1.000 (25.40)	1.375 (34.93)	1	2.195 (55.75)	1.500 (38.10)			
23						32	N/A	N/A	16	.625 (15.88)	.937 (23.80)	1	2.800 (71.12)	1.156 (29.36)
24									20	.875 (22.23)	1.250 (31.75)	1	2.800 (71.12)	1.375 (34.93)
25									28	1.250 (31.75)	1.625 (41.28)	1	2.445 (62.10)	1.781 (45.24)
26									36	N/A	N/A	16	.625 (15.88)	.937 (23.80)
27			24	1.000 (25.40)	1.375 (34.93)	1	2.770 (70.36)	1.500 (38.10)						
28			32	1.437 (36.50)	1.840 (46.74)	1	2.415 (61.34)	1.830 (46.48)						
29			40	N/A	N/A	16	.625 (15.88)	.937 (23.80)				1	2.770 (70.36)	1.156 (29.36)
30						24	1.000 (25.40)	1.375 (34.93)	1	2.770 (70.36)	1.500 (38.10)			
31		32				1.437 (36.50)	1.875 (47.63)	1	2.415 (61.34)	1.830 (46.48)				

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	D DIA MAX	E ±.125	V THREAD CLASS 2A	F MAX	G DIA MAX	H MAX
17	1.468 (37.29)	1.166 (29.62)	1.1875-18 UNEF	2.11 (53.59)	—	2.50 (63.50)
18	1.468 (37.29)	1.166 (29.62)	1.750-18 UNS	2.29 (58.17)	—	2.68 (68.07)
19	1.593 (40.46)	1.166 (29.62)	1.1875-18 UNEF	2.11 (53.59)	—	2.50 (63.50)
20	1.593 (40.46)	1.166 (29.62)	1.750-18 UNS	2.29 (58.17)	—	2.68 (68.07)
21	1.969 (50.01)	1.266 (32.16)	1.4375-18 UNEF	2.33 (59.18)	—	2.88 (73.15)
22	1.969 (50.01)	1.266 (32.16)	2.000-18 UNS	2.51 (63.75)	—	3.06 (77.72)
23	2.219 (56.36)	1.616 (41.05)	1.4375-18 UNEF	2.81 (71.37)	—	3.36 (85.34)
24	2.219 (56.36)	1.616 (41.05)	1.750-18 UNS	2.81 (71.37)	—	3.36 (85.34)
25	2.219 (56.36)	1.616 (41.05)	2.250-16 UN	3.07 (77.98)	—	3.62 (91.95)
26	2.469 (62.71)	1.816 (46.13)	1.4375-18 UNEF	3.13 (79.50)	—	3.68 (93.47)
27	2.469 (62.71)	1.816 (46.13)	2.000-18 UNS	3.13 (79.50)	—	3.68 (93.47)
28	2.469 (62.71)	1.816 (46.13)	2.500-16 UN	3.39 (86.11)	—	3.94 (100.08)
29	2.719 (69.06)	2.566 (65.18)	1.4375-18 UNEF	3.88 (98.55)	—	4.43 (112.52)
30	2.719 (69.06)	2.566 (65.18)	2.000-18 UNS	3.88 (98.55)	—	4.43 (112.52)
31	2.719 (69.06)	2.566 (65.18)	2.500-16 UN	4.14 (105.16)	—	4.69 (119.13)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	CONNECTOR SHELL SIZE				CLAMP SIZE	A (SEE NOTE 6)		STYLE	B ±.125	C REF
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	AS50151 CRIMP	MIL-DTL-83723 SERIES III		WIRE BUNDLE ACCOMMODATION RANGE				
						MIN	MAX			
32	N/A	N/A	44	N/A	16	.625 (15.88)	.937 (23.80)	1	2.770 (70.36)	1.156 (29.36)
33					24	1.000 (25.40)	1.375 (34.93)	1	2.770 (70.36)	1.500 (38.10)
34					32	1.437 (36.50)	1.875 (47.63)	1	2.415 (61.34)	1.830 (46.48)
35					16	.625 (15.88)	.937 (23.80)	1	2.770 (70.36)	1.156 (29.36)
36					24	1.000 (25.40)	1.375 (34.93)	1	2.770 (70.36)	1.500 (38.10)
37					32	1.437 (36.50)	1.875 (47.63)	1	2.415 (61.34)	1.830 (46.48)
38					61	N/A	N/A	N/A	12	.500 (12.70)
39	20	.875 (22.23)	1.184 (30.07)	1					2.025 (51.44)	1.375 (34.93)
40	19	16	16, 16S	16					10	.350 (8.89)
41	27	18	18	18	4	.125 (3.18)	.312 (7.92)	1	2.270 (57.66)	1.027 (26.09)
42					6	.250 (6.35)	.437 (11.10)	1	2.270 (57.66)	1.027 (26.09)
43	37	20	20	20	6	.250 (6.35)	.437 (11.10)	1	2.270 (57.66)	1.027 (26.09)
44	N/A	22	22	22	4	.125 (3.18)	.312 (7.92)	1	2.380 (60.45)	1.027 (26.09)
45					6	.250 (6.35)	.437 (11.10)	1	2.380 (60.45)	1.027 (26.09)
46					24	24	24	10	.350 (8.89)	.625 (15.88)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	D DIA MAX	E ±.125	V THREAD CLASS 2A	F MAX	G DIA MAX	H MAX
32	2.969 (75.41)	2.566 (65.18)	1.4375-18 UNEF	3.88 (98.55)	–	4.43 (112.52)
33	2.969 (75.41)	2.566 (65.18)	2.000-18 UNS	3.88 (98.55)	–	4.43 (112.52)
34	2.969 (75.41)	2.566 (65.18)	2.500-16 UN	4.14 (105.16)	–	4.69 (119.13)
35	3.219 (81.76)	2.566 (65.18)	1.4375-18 UNEF	3.88 (98.55)	–	4.43 (112.52)
36	3.219 (81.76)	2.566 (65.18)	2.000-18 UNS	3.88 (98.55)	–	4.43 (112.52)
37	3.219 (81.76)	2.566 (65.18)	2.500-16 UN	4.14 (105.16)	–	4.69 (119.13)
38	1.653 (41.99)	1.166 (29.62)	1.1875-18 UNEF	2.11 (53.59)	–	2.50 (63.50)
39	1.653 (41.99)	1.166 (29.62)	1.750-18 UNS	2.29 (58.17)	–	2.68 (68.07)
40	1.112 (28.24)	.926 (23.52)	1.000-20 UNEF	1.66 (42.16)	–	2.05 (52.07)
41	1.218 (30.94)	1.016 (25.81)	.625-24 UNEF	1.80 (45.72)	–	2.19 (55.63)
42	1.218 (30.94)	1.016 (25.81)	.750-20 UNEF	1.80 (45.72)	–	2.19 (55.63)
43	1.345 (34.16)	1.016 (25.81)	.750-20 UNEF	1.80 (45.72)	–	2.19 (55.63)
44	1.468 (37.29)	1.166 (29.62)	.625-24 UNEF	2.11 (53.59)	–	2.50 (63.50)
45	1.468 (37.29)	1.166 (29.62)	.750-20 UNEF	2.11 (53.59)	–	2.50 (63.50)
46	1.593 (40.46)	1.166 (29.62)	1.000-20 UNEF	2.11 (53.59)	–	2.50 (63.50)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	CONNECTOR SHELL SIZE				CLAMP SIZE	A (SEE NOTE 6)		STYLE	B ±.125	C REF
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	AS50151 CRIMP	MIL-DTL-83723 SERIES III		WIRE BUNDLE ACCOMMODATION RANGE				
						MIN	MAX			
47	N/A	N/A	36	N/A	12	.500 (12.70)	.750 (19.05)	1	2.770 (70.36)	1.059 (26.90)
48			40		12	.500 (12.70)	.750 (19.05)	1	2.770 (70.36)	1.059 (26.90)
49			10		10S, 10SL	10	6	.250 (6.35)	.437 (11.10)	2
50	12	14	14, 14S	14	12	.500 (12.70)	.750 (19.05)	2	2.270 (57.66)	1.059 (26.90)
51	19	16	16, 16S	16	16	.625 (15.88)	.937 (23.80)	2	2.380 (60.45)	1.156 (29.36)
52	27	18	18	18	12	.500 (12.70)	.750 (19.05)	1	2.270 (57.66)	1.059 (26.90)
53	61	N/A	N/A	N/A	16	.625 (15.88)	.937 (23.80)	1	2.025 (51.44)	1.156 (29.36)
54	37	20	20	20	12	.500 (12.70)	.750 (19.05)	1	2.270 (57.66)	1.059 (26.90)
55					20	.875 (22.23)	1.250 (31.75)	2	2.550 (64.77)	1.375 (34.93)
56					10	.350 (8.89)	.625 (15.88)	1	2.380 (60.45)	1.027 (26.09)
57	N/A	22	22	22	16	.625 (15.88)	.937 (23.80)	1	2.380 (60.45)	1.156 (29.36)
58					20	.875 (22.23)	1.250 (31.75)	2	2.550 (64.77)	1.375 (34.93)
59					24	.625 (15.88)	.937 (23.80)	1	2.380 (60.45)	1.156 (29.36)
60	N/A	N/A	28	N/A	12	.500 (12.70)	.750 (19.05)	1	2.550 (64.77)	1.059 (26.90)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	D DIA MAX	E ±.125	V THREAD CLASS 2A	F MAX	G DIA MAX	H MAX
47	2.469 (62.71)	1.816 (46.13)	1.1875-18 UNEF	3.13 (79.50)	–	3.68 (93.47)
48	2.719 (69.06)	1.816 (46.13)	1.1875-18 UNEF	3.88 (98.55)	–	4.43 (112.52)
49	.734 (18.64)	1.391 (35.33)	.750-20 UNEF	2.03 (51.56)	.858 (21.79)	2.42 (61.47)
50	.984 (24.99)	1.766 (44.86)	1.1875-18 UNEF	2.61 (66.29)	1.218 (30.94)	3.00 (76.20)
51	1.112 (28.24)	1.916 (48.67)	1.4375-18 UNEF	2.87 (72.90)	1.468 (37.29)	3.26 (82.80)
52	1.218 (30.94)	1.016 (25.81)	1.1875-18 UNEF	1.86 (47.24)	–	2.25 (57.15)
53	1.653 (41.99)	1.166 (29.62)	1.4375-18 UNEF	2.14 (54.36)	–	2.53 (64.26)
54	1.345 (34.16)	1.016 (25.81)	1.1875-18 UNEF	1.86 (47.24)	–	2.25 (57.15)
55	1.345 (34.16)	2.016 (51.21)	1.750-18 UNS	3.14 (79.76)	1.969 (50.01)	3.53 (89.66)
56	1.468 (37.29)	1.166 (29.62)	1.000-20 UNEF	2.11 (53.59)	–	2.50 (63.50)
57	1.468 (37.29)	1.166 (29.62)	1.4375-18 UNEF	2.12 (53.85)	–	2.51 (63.75)
58	1.468 (37.29)	2.016 (51.21)	1.750-18 UNS	3.14 (79.76)	1.969 (50.01)	3.53 (89.66)
59	1.593 (40.46)	1.166 (29.62)	1.4375-18 UNEF	2.14 (54.36)	–	2.53 (64.26)
60	1.969 (50.01)	1.266 (32.16)	1.1875-18 UNEF	2.33 (59.18)	–	2.88 (73.15)

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	CONNECTOR SHELL SIZE				CLAMP SIZE	A (SEE NOTE 6)		STYLE	B ±.125	C REF			
	AS81703 SERIES 3	MIL-DTL-26482 SERIES 2	AS50151 CRIMP	MIL-DTL-83723 SERIES III		WIRE BUNDLE ACCOMMODATION RANGE							
						MIN	MAX						
61	N/A	N/A	28	N/A	20	.875 (22.23)	1.250 (31.75)	1	2.550 (64.77)	1.375 (34.93)			
62			32		24	1.000 (25.40)	1.375 (34.93)	1	2.800 (71.12)	1.500 (38.10)			
63			36		20	.875 (22.23)	1.250 (31.75)	1	2.770 (70.36)	1.375 (34.93)			
64					28	1.250 (31.75)	1.625 (41.28)	1	2.770 (70.36)	1.781 (45.24)			
65			40		N/A	44	20	.875 (22.23)	1.250 (31.75)	1	2.770 (70.36)	1.375 (34.93)	
66							28	1.250 (31.75)	1.625 (41.28)	1	2.770 (70.36)	1.781 (45.24)	
67							20	.875 (22.23)	1.250 (31.75)	1	2.770 (70.36)	1.375 (34.93)	
68							28	1.250 (31.75)	1.625 (41.28)	1	2.770 (70.36)	1.781 (45.24)	
69							48	20	.875 (22.23)	1.250 (31.75)	1	2.770 (70.36)	1.375 (34.93)
70								28	1.250 (31.75)	1.625 (41.28)	1	2.770 (70.36)	1.781 (45.24)
71	7	12		12, 12S			12	10	.350 (8.89)	.625 (15.88)	2	2.100 (53.34)	1.027 (26.09)
72	27	18		18			18	16	.625 (15.88)	.937 (23.80)	2	2.380 (60.45)	1.156 (29.36)
73	N/A	24	24	24	20	.875 (22.23)	1.250 (31.75)	2	2.550 (64.77)	1.375 (34.93)			
74	12	14	14, 14S	14	4	.125 (3.18)	.312 (7.92)	1	2.010 (51.05)	1.027 (26.09)			
75	19	16	16, 16S	16	4	.125 (3.18)	.312 (7.92)	1	2.100 (53.34)	1.027 (26.09)			

TABLE 1 - DIMENSIONS (CONTINUED)

DASH NO.	D DIA MAX	E ±.125	V THREAD CLASS 2A	F MAX	G DIA MAX	H MAX
61	1.969 (50.01)	1.266 (32.16)	1.750-18 UNS	2.39 (60.71)	–	2.94 (74.68)
62	2.219 (56.36)	1.616 (41.05)	2.000-18 UNS	2.86 (72.64)	–	3.41 (86.61)
63	2.469 (62.71)	1.816 (46.13)	1.750-18 UNS	3.13 (79.50)	–	3.68 (93.47)
64	2.469 (62.71)	1.816 (46.13)	2.250-16 UN	3.27 (83.06)	–	3.82 (97.03)
65	2.719 (69.06)	2.566 (65.18)	1.750-18 UNS	3.88 (98.55)	–	4.43 (112.52)
66	2.719 (69.06)	2.566 (65.18)	2.250-16 UN	4.02 (102.11)	–	4.57 (116.08)
67	2.969 (75.41)	2.566 (65.18)	1.750-18 UNS	3.88 (98.55)	–	4.43 (112.52)
68	2.969 (75.41)	2.566 (65.18)	2.250-16 UN	4.02 (102.11)	–	4.57 (116.08)
69	3.219 (81.76)	2.566 (65.18)	1.750-18 UNS	3.88 (98.55)	–	4.43 (112.52)
70	3.219 (81.76)	2.566 (65.18)	2.250-16 UN	4.02 (102.11)	–	4.57 (116.08)
71	.858 (21.79)	1.686 (42.82)	1.000-20 UNEF	2.42 (61.47)	1.112 (28.24)	2.81 (71.37)
72	1.218 (30.94)	1.926 (48.92)	1.4375-18 UNEF	2.88 (73.15)	1.468 (37.29)	3.27 (83.06)
73	1.593 (40.46)	2.026 (51.46)	1.750-18 UNS	3.15 (80.01)	1.969 (50.01)	3.54 (89.92)
74	.984 (24.99)	.741 (18.82)	.625-24 UNEF	1.31 (33.27)	–	1.70 (43.18)
75	1.112 (28.24)	.926 (23.52)	.625-24 UNEF	1.59 (40.39)	–	1.98 (50.29)

NOTES:

- DIMENSIONS ARE IN INCHES AND APPLY AFTER PLATING.
- METRIC EQUIVALENTS ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
- MILLIMETERS ARE IN PARENTHESES.
- UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE: .XX = ±.01; .XXX = ±.005; ANGULAR; X DEGREES = ±1 DEGREE; X DEGREES XX' = ±0 DEGREES 30'.
- LOOSELY ASSEMBLED IS DEFINED AS THE AS85049/42 CLAMP TIGHTENED TO THE AS85049/9 CONNECTOR ACCESSORY BODY A MINIMUM OF TWO FULL THREAD LENGTHS.
- "WIRE BUNDLE ACCOMMODATION RANGE" IS DEFINED AS THE ENVELOPE AREA FOR THE WIRE BUNDLE. THIS DIMENSION IS NOT MEANT TO DEFINE THE CLAMP HARDWARE LIMITS.

REQUIREMENTS:

- DESIGN AND CONSTRUCTION:
 - DIMENSIONS AND CONFIGURATION: SEE FIGURE 1 AND TABLE 1.
 - INTERFACE DIMENSIONS SHALL CONFORM TO SAE AS85049 FIGURE 4 OR 4A.
 - FIGURE 1 CONSISTS OF A COUPLING NUT AND FOLLOWER. THE COUPLING NUT SHALL BE CAPTIVATED TO AND FREE TO ROTATE ON THE FOLLOWER.

 An SAE International Group	AEROSPACE STANDARD CONNECTOR ACCESSORIES, ELECTRICAL, BACKSHELL, ENVIRONMENTAL, CABLE SEALING, 90°, CATEGORY 1A (FOR AS50151 CRIMP, MIL-DTL-26482 SERIES 2, AS81703 SERIES 3, AND MIL-DTL-83723 SERIES III CONNECTORS)	SAE AS85049/9 SHEET 7 OF 9	REV. B