


**NOTES:**

- Δ 1. PARTS SHALL CONFORM WITH APPLICABLE REQUIREMENTS OF MIL-F-18280, LATEST REVISION, UNLESS OTHERWISE SPECIFIED BY PROCURING ACTIVITY.
- Δ 2. MATERIAL CODE: IN PLACE OF DASH IN PART NUMBER, ADD MATERIAL CODE AS FOLLOWS:

NO LETTER INDICATES STEEL (USE DASH "--")  
 LETTER "D" INDICATES TYPE 2014-T6 ALUMINUM ALLOY  
 LETTER "J" INDICATES CORROSION RESISTANT STEEL, CLASS 304  
 LETTER "K" INDICATES CORROSION RESISTANT STEEL, CLASS 316  
 LETTER "S" INDICATES CORROSION RESISTANT STEEL, CLASS 347  
 LETTER "W" INDICATES TYPE 7075-T73 ALUMINUM ALLOY

- 3. SPECIFY END SIZES IN THIS ORDER: FLARELESS TUBE END ON RUN FIRST (PORT #1), PIPE END SECOND (PORT #2), FLARELESS TUBE END ON SIDE THIRD (PORT #3).
- 4. USE FORGING SIZE AS DETERMINED FROM TABLE 1.
- 5. EXAMPLE OF PART NUMBER:



- 6. TOLERANCE ON 90° ANGLE: ±2 1/2° FOR DASH 6 AND SMALLER, ±1 1/2° FOR DASH 8 AND LARGER.
- 7. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES.
- 8. FITTING END PER MS33514 SHALL CONFORM TO STYLE G WHEN NORMAL THREAD SIZE EQUALS NORMAL FORGING SIZE. USE STYLE E WHEN THREAD SIZE IS SMALLER THAN FORGING SIZE, EXCEPT OMIT HEX.
- 9. AT OPTION OF MANUFACTURER, THE FLUID PASSAGE MAY CONFORM TO THE SMALLER DIAMETER HOLE ON ALL PORTS.
- Δ 10. ALL MACHINED SURFACES SHALL BE SMOOTH TO 125 MICROINCHES Ra MAX PER ANSI B46.1.
- Δ 11. PARTS FOR OXYGEN SERVICE SHALL BE FURNISHED CLEANED, PACKAGED, AND LABELED PER AIR 1176 (OR OTHER CUSTOMER SPECIFIED DOCUMENT) WHEN SPECIFIED BY PROCURING ACTIVITY.
- Δ 12. IDENTIFY PER MIL-F-18280 EXCEPT SUBSTITUTE AS OR AS894 MARKING IN PLACE OF MS OR MSXXXXX AS APPLICABLE.
- Δ 13. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

1983 CHANGE DESIGNATED BY Δ

REATTAINED  
 APRIL 1993  
 ISSUED 12-1-83  
 REVISED 1-15-76

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."  
 SAE reserves each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

PREPARED BY SAE SUBCOMMITTEE G-3B, AEROSPACE FITTINGS, OF SAE COMMITTEE G-3, AEROSPACE FITTINGS, HOSE, & TUBING ASSEMBLIES

<p>400 Commonwealth Drive Warren, PA 15090</p>	<b>AEROSPACE STANDARD</b>  <b>TEE, FLARELESS TUBE TO MALE PIPE ON RUN</b>	<b>AS 894</b>  SHEET 1 OF 2	<b>Rev. A</b>
--	---	-----------------------------------	---------------