

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS9284™

RATIONALE

FIGURE REDRAWN, HEAD HEIGHT KEPT AS EXISTING MINOR EDITORIAL CHANGES TO TABLES, USAGE NOTE ADDED SPECS UPDATED.

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9284(ASG). THIS SAE STANDARD MAY RETAIN THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL'S) MAY CONTINUE TO BE MANDATORY FOR DoD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

FEDERAL SUPPLY CLASS
5306





FIGURE 1 - BOLT

For more information on this standard, visit
<https://www.sae.org/standards/content/AS9284C/>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7452 /3/



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, PD SHANK,
BLACK OXIDE, STEEL UNS G87400, 125 KSI MIN,
.2500-28 UNJF-3A

AS9284™
SHEET 1 OF 3

REV.
C

Copyright © 2021 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 1998-11 REAFFIRMED 2004-07 REVISED 2021-09

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	K	APPROX MASS LB/100	PART NO.	L	K	APPROX MASS LB/100
MS9284-04	.365-.385	.079-.099	1.16	MS9284-34	2.490-2.510	1.940-2.000	3.88
MS9284-05	.428-.448	.079-.099	1.23	MS9284-35	2.615-2.635	2.065-2.125	4.02
MS9284-06	.490-.510	.079-.099	1.30	MS9284-36	2.740-2.760	2.190-2.250	4.16
MS9284-07	.552-.572	.079-.099	1.37	MS9284-37	2.865-2.885	2.315-2.375	4.31
MS9284-08	.615-.635	.079-.099	1.44	MS9284-38	2.990-3.010	2.440-2.500	4.45
MS9284-09	.678-.698	.079-.099	1.51	MS9284-39	3.115-3.135	2.565-2.625	4.60
MS9284-10	.740-.760	.079-.099	1.58	MS9284-40	3.240-3.260	2.690-2.750	4.74
MS9284-11	.802-.822	.079-.099	1.66	MS9284-41	3.365-3.385	2.815-2.875	4.88
MS9284-12	.865-.885	.079-.125	1.73	MS9284-42	3.490-3.510	2.940-3.000	5.03
MS9284-13	.928-.948	.128-.188	1.80	MS9284-43	3.615-3.635	3.065-3.125	5.17
MS9284-14	.990-1.010	.190-.250	1.87	MS9284-44	3.740-3.760	3.190-3.250	5.31
MS9284-15	1.052-1.072	.252-.312	1.94	MS9284-45	3.865-3.885	3.315-3.375	5.46
MS9284-16	1.115-1.135	.315-.375	2.01	MS9284-46	3.990-4.010	3.440-3.500	5.60
MS9284-17	1.178-1.198	.378-.438	2.09	MS9284-47	4.115-4.135	3.565-3.625	5.74
MS9284-18	1.240-1.260	.440-.500	2.16	MS9284-48	4.240-4.260	3.690-3.750	5.89
MS9284-19	1.302-1.322	.502-.562	2.23	MS9284-49	4.365-4.385	3.815-3.875	6.03
MS9284-20	1.365-1.385	.565-.625	2.30	MS9284-50	4.490-4.510	3.940-4.000	6.17
MS9284-21	1.428-1.448	.628-.688	2.37	MS9284-51	4.615-4.635	4.065-4.125	6.32
MS9284-22	1.490-1.510	.690-.750	2.44	MS9284-52	4.740-4.760	4.190-4.250	6.45
MS9284-23	1.552-1.572	.752-.812	2.52	MS9284-53	4.865-4.885	4.315-4.375	6.60
MS9284-24	1.615-1.635	.815-.875	2.59	MS9284-54	4.990-5.010	4.440-4.500	6.75
MS9284-25	1.678-1.698	.878-.938	2.66	MS9284-55	5.115-5.135	4.565-4.625	6.89
MS9284-26	1.740-1.760	.940-1.000	2.73	MS9284-56	5.240-5.260	4.690-4.750	7.03
MS9284-27	1.802-1.822	1.065-1.125	2.87	MS9284-57	5.365-5.385	4.815-4.875	7.18
MS9284-28	1.865-1.885	1.190-1.250	3.02	MS9284-58	5.490-5.510	4.940-5.000	7.32
MS9284-29	1.928-1.948	1.315-1.375	3.16	MS9284-59	5.615-5.635	5.065-5.125	7.48
MS9284-30	1.990-2.010	1.440-1.500	3.30	MS9284-60	5.740-5.760	5.190-5.250	7.61
MS9284-31	2.115-2.135	1.565-1.625	3.45	MS9284-61	5.865-5.885		
MS9284-32	2.240-2.260	1.690-1.750	3.59	MS9284-62	5.990-6.010		
MS9284-33	2.365-2.385	1.815-1.875	3.73				



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, PD SHANK,
BLACK OXIDE, STEEL UNS G87400, 125 KSI MIN,
.2500-28 UNJF-3A

AS9284™
SHEET 2 OF 3

REV.
C