

(R) FUEL TANK FILLER CAP AND CAP RETAINER THREADED

1. SCOPE:

This document was developed primarily for passenger car and truck, applications but it may be used in marine, industrial, and similar applications.

2. PURPOSE:

The purpose of this document is to provide dimensions for threaded fuel tank filler caps and cap retainers (see Figs. 1 and 2).

S. A. E.
LIBRARY

The (R) symbol is for the convenience of the user in locating areas where technical revisions have been made to the previous issue of the report. If the symbol is next to the report title, it indicates a complete revision of the report.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.




FIGURE 1 - Pressure/Vacuum (Clockwise Rotation)
Cap can be interchangeable with Fig. 2 fillerneck.




FIGURE 2 - Nonvented or Vacuum Only (Clockwise Rotation)
Cap is not interchangeable with Fig. 1 fillerneck.

RATIONALE:

Not applicable.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

REFERENCE SECTION:

Not applicable.

APPLICATION:

This document was developed primarily for passenger car and truck applications but it may be used in marine, industrial, and similar applications.

COMMITTEE COMPOSITION:DEVELOPED BY THE SAE FUEL SUPPLY SYSTEMS FORUM COMMITTEE:

M. J. Harrigan, Sr., Ford Motor Co., Dearborn, MI - Chairman
 G. E. Moore, Dover Corp., Cincinnati, OH - Vice Chairman
 P. B. Anderson, Dover Corp., Cincinnati, OH
 R. Babcock, Toyota Technical Center USA, Ann Arbor, MI
 P. D. Carmack, Catrow Inc., Tipp City, OH
 T. J. Carr, Motor Vehicle Mfrs. Assn. of US, Detroit, MI
 C. Covert, GMC, Henrietta, NY
 W. G. Crute, Purolator Inc., Connersville, IN
 M. J. Del Percio, Bennett Pump Co., Muskegon, MI
 T. Detwiler, Parker-Hannifin Corp., Troy, MI
 E. Ellsworth, Ford Motor Co., Dearborn, MI
 H. M. Faulconer, National LP-Gas Association, Oak Brook, IL
 A. C. Fink, Jr., Husky Corporation, Pacific, MO
 L. E. Freeman, General Motors Corp., Warren, MI
 R. W. Furrow, Gilbarco Inc., Greensboro, NC
 L. W. Gibbs, Underwriters Labs Inc., Northbrook, IL
 K. A. Kerby, Chrysler Corp., Highland Park, MI
 R. L. Kirkpatrick, GMC, Lansing, MI
 E. Klop, Enterprise Brass Works, Muskegon, MI
 T. C. Laurell, GMC, Detroit, MI
 D. K. Lawrence, Amoco Corp., Naperville, IL
 J. R. Madden, Volkswagen of America Inc., Troy, MI
 M. A. Maher, General Motors Corp., Milford, MI
 J. Mueller, Environmental Protection Agency, Ann Arbor, MI
 R. L. Murray, Dover Corporation, Cincinnati, OH
 L. Nitzberg, Catrow Inc., Tipp City, OH
 P. R. O'Connell, Fitzsimons Mfg. Co., Detroit, MI
 G. W. Passavant, Environ. Protection Agency, Ann Arbor, MI
 A. R. Podgers, Emco Wheaton Inc., Conneaut, OH
 B. J. Schelske, Intelligent Controls inc., Novi, MI
 H. J. Silver, Jr., Texaco, Inc., Beacon, NY
 T. A. Stacey, Jr., GMC, Flint, MI
 D. R. Sterzinger, Allied Signal, South Bend, IN
 E. G. Strager, Fitzsimons Mfg. Co., Detroit, MI
 C. Taylor, Rochester Gauges Inc. of Texas, Dallas, TX
 R. H. Thompson, Stant, Connersville, IN
 M. E. Tokarsky, Ford Motor Company, Dearborn, MI