

|                                                                                  |                                         |                                                       |
|----------------------------------------------------------------------------------|-----------------------------------------|-------------------------------------------------------|
|  | <b>SURFACE<br/>VEHICLE<br/>STANDARD</b> | <b>SAE</b> <b>J2494-4 OCT2011</b>                     |
|                                                                                  |                                         | Issued            2002-07<br>Reaffirmed       2011-10 |
|                                                                                  |                                         | Superseding J2494-4 JUL2002                           |
| Cartridge Cavity                                                                 |                                         |                                                       |

## RATIONALE

J2494-4 has been reaffirmed to comply with the SAE 5-Year Review policy.

**1. Scope**—This SAE Standard covers complete general and dimensional data for the manufacture of, T6061-T6 Aluminum cavities designed to receive Push To Connect threadless fittings known as “cartridges”, for air brake applications. This document is not intended to specify or recommend any style or manufacture of such cartridges but to establish uniform cavity dimensions for interchangeability purposes.

## 2. References

**2.1 Applicable Publications**—The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest version of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale PA 15096-0001

SAE J844—Nonmetallic Air Brake Tubing

SAE J1131—Performance Requirements for SAE J844 Nonmetallic Tubing and Fitting Assemblies used in Automotive Air Brake Systems

SAE J2494-3—Performance Requirements for SAE J844 Nonmetallic Air Brake Tubing and Push to Connect Fitting Assemblies used in Vehicular Air Brake Systems

**2.2 Related Publication**—The following publication is for information purposes only and is not a required part of this document.

2.2.1 SAE PUBLICATIONS—Available from SAE, 400 Commonwealth Drive, Warrendale PA 15096-0001

SAE J451—Aluminum Alloys

## 3. General Requirements

**3.1** Test Cavity material is to be T6061-T6 Aluminum

**3.2** All dimensions unless specified differently are  $\pm 0.05$  mm ( $\pm 0.002$  in).

**3.3** All testing of subsequent assemblies must be performed with SAE J844 Air Brake Tubing

SAE Technical Standards Board Rules provide that: “This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user.”

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:    Tel:    877-606-7323 (inside USA and Canada)  
                                                   Tel:    +1 724-776-4970 (outside USA)  
                                                   Fax:    724-776-0790  
                                                   Email: CustomerService@sae.org  
 SAE WEB ADDRESS:                    http://www.sae.org

**SAE values your input. To provide feedback  
on this Technical Report, please visit  
[http://www.sae.org/technical/standards/J2494/4\\_201110](http://www.sae.org/technical/standards/J2494/4_201110)**

#### 4. General Specifications

4.1 See Table 1 for cavity dimensions.

TABLE 1—CAVITY DIMENSIONS

| Nominal<br>Tubing<br>OD | D1<br>mm | D1<br>in | K<br>mm | K<br>in | L1 (min)<br>mm | L1 (min)<br>in | R1<br>mm | R1<br>in |
|-------------------------|----------|----------|---------|---------|----------------|----------------|----------|----------|
| 5/32                    | 8.8      | 0.346    | 0.5     | 0.02    | 11.4           | 0.45           | 0.5      | 0.02     |
| 3/16                    | 9.7      | 0.382    | 0.5     | 0.02    | 12.1           | 0.48           | 0.5      | 0.02     |
| 1/4                     | 12.8     | 0.504    | 0.5     | 0.02    | 12.7           | 0.50           | 0.5      | 0.02     |
| 5/16                    | 14.3     | 0.563    | 0.5     | 0.02    | 15.2           | 0.60           | 0.5      | 0.02     |
| 3/8                     | 16.5     | 0.650    | 0.5     | 0.02    | 16.5           | 0.65           | 0.5      | 0.02     |
| 1/2                     | 19.7     | 0.775    | 0.5     | 0.02    | 19.8           | 0.78           | 0.5      | 0.02     |
| 5/8                     | 23.5     | 0.925    | 0.8     | 0.03    | 22.4           | 0.88           | 0.8      | 0.03     |
| 3/4                     | 27.1     | 1.067    | 0.8     | 0.03    | 23.9           | 0.94           | 0.8      | 0.03     |

NOTE—Cavities made from materials other than T6061-T6 SHALL be adjusted dimensionally so that when installed; the tube/cartridge/cavity assembly will pass the applicable tests in SAE J1131 and SAE J2494-3.

4.2 **Recommended Wall Thickness**—Unless otherwise designated, the wall thickness at any point on a cartridge body, which may be subjected to internal pressure, is recommended to not be less than the thickness established by the specified dimensions and tolerances for inner and outer surfaces.

4.3 See Figure 1 for cavity detail and Table 2 for minimum wall thickness




FIGURE 1—CAVITY DETAIL